



debian

# **Leitfaden für Debian-Betreuer**

Osamu Aoki, Helge Kreutzmann, and Mechtilde Stehmann

October 31, 2024

---

## Leitfaden für Debian-Betreuer

by Osamu Aoki, Helge Kreutzmann, and Mechtilde Stehmann

Copyright © 2014-2024 Osamu Aoki

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Diese Anleitung wurde mit den nachfolgenden Dokumenten als Referenz erstellt:

- »Making a Debian Package (AKA the Debmake Manual)«, Copyright © 1997 Jaldhar Vyas.
- »The New-Maintainer's Debian Packaging Howto«, Copyright © 1997 Will Lowe.
- »Debian-Leitfaden für Neue Paketbetreuer«, Copyright © 1998-2002 Josip Rodin, 2005-2017 Osamu Aoki, 2010 Craig Small und 2010 Raphaël Hertzog.

Die neuste Version dieser Anleitung sollte

- in the [debmake-doc package](#) and
- at the [Debian Documentation web site](#).

# Contents

<b>1</b>	<b>Vorwort</b>	<b>1</b>
<b>2</b>	<b>Überblick</b>	<b>3</b>
<b>3</b>	<b>Voraussetzungen</b>	<b>5</b>
3.1	Leute bei Debian	5
3.2	Wie Sie beitragen können	5
3.3	Soziale Dynamik von Debian	6
3.4	Technische Erinnerungen	6
3.5	Debian-Dokumentation	7
3.6	Hilfequellen	8
3.7	Archivsituation	8
3.8	Wege, beizutragen	9
3.9	Neue Beitragende und Betreuer	10
<b>4</b>	<b>Werkzeugeinrichtung</b>	<b>12</b>
4.1	Email setup	12
4.2	<b>mc</b> setup	12
4.3	<b>git</b> setup	13
4.4	<b>quilt</b> setup	13
4.5	<b>devscripts</b> setup	14
4.6	<b>sbuild</b> setup	14
4.7	Persistent chroot setup	16
4.8	<b>gbp</b> setup	16
4.9	HTTP-Proxy	16
4.10	Privates Debian-Depot	17
4.11	Virtuelle Maschinen	17
4.12	Local network with virtual machines	17
<b>5</b>	<b>Simple packaging</b>	<b>18</b>
5.1	Packaging tarball	18
5.2	Gesamtbild	18
5.3	Was ist Debmake?	19
5.4	Was ist Debuild?	20
5.5	Schritt 1: Holen der Quellen der Originalautoren	20
5.6	Step 2: Generate template files with <b>debmake</b>	21
5.7	Schritt 3: Anpassung der Vorlagendateien	25
5.8	Step 4: Building package with <b>debuild</b>	27
5.9	Step 3 (alternatives): Modification to the upstream source	30
5.10	Patch by “ <b>diff -u</b> ” approach	30
5.11	Patch by <b>dquilt</b> approach	31
5.12	Patch by “ <b>dpkg-source --auto-commit</b> ” approach	33
<b>6</b>	<b>Basics for packaging</b>	<b>36</b>
6.1	Arbeitsablauf des Paketierens	36
6.2	<b>debhelper</b> package	38
6.3	Paketname und -version	39
6.4	Natives Debian-Paket	40
6.5	<b>debian/rules</b> file	40
6.6	<b>debian/control</b> file	41
6.7	<b>debian/changelog</b> file	42
6.8	<b>debian/copyright</b> file	42
6.9	<b>debian/patches/*</b> files	43
6.10	<b>debian/source/include-binaries</b> file	44

6.11	<b>debian/watch</b> file	44
6.12	<b>debian/upstream/signing-key.asc</b> file	44
6.13	<b>debian/salsa-ci.yml</b> file	45
6.14	Other <b>debian/*</b> files	45
<b>7</b>	<b>Sanitization of the source</b>	<b>50</b>
7.1	Fix with <b>Files-Excluded</b>	50
7.2	Fix with “ <b>debian/rules clean</b> ”	50
7.3	Fix with <b>extend-diff-ignore</b>	51
7.4	Fix with <b>tar-ignore</b>	51
7.5	Fix with “ <b>git clean -dfx</b> ”	51
<b>8</b>	<b>More on packaging</b>	<b>53</b>
8.1	Package customization	53
8.2	Customized <b>debian/rules</b>	53
8.3	Variables for <b>debian/rules</b>	54
8.4	New upstream release	54
8.5	Manage patch queue with <b>dquilt</b>	55
8.6	Build commands	55
8.7	Note on <b>sbuild</b>	55
8.8	Special build cases	56
8.9	Upload <b>orig.tar.gz</b>	56
8.10	Skipped uploads	57
8.11	Bug reports	57
<b>9</b>	<b>Advanced packaging</b>	<b>58</b>
9.1	Historical perspective	58
9.2	Current trends	58
9.3	Note on build system	59
9.4	Continuous integration	59
9.5	Bootstrapping	59
9.6	Compiler hardening	60
9.7	Reproduzierbares Bauen	60
9.8	Substvar	60
9.9	Bibliothekspaket	61
9.10	Multiarch	61
9.11	Aufteilung eines Debian-Binärpakets	62
9.12	Pakettrennungsszenarien und -beispiele	62
9.13	Multiarch library path	62
9.14	Multiarch header file path	63
9.15	Multiarch *. <b>pc</b> file path	63
9.16	Bibliothekssymbole	63
9.17	Library package name	65
9.18	Bibliotheksübergänge	66
9.19	biNMU-sicher	66
9.20	Fehlersuchinformationen	66
9.21	<b>-dbgsym</b> package	67
9.22	<b>debconf</b>	67
<b>10</b>	<b>Packaging with git</b>	<b>68</b>
10.1	Salsa repository	69
10.2	Salsa account setup	69
10.3	Salsa CI service	69
10.4	Branch names	69
10.5	Patch unapplied Git repository	70
10.6	Patch applied Git repository	70
10.7	Note on <b>gbp</b>	71
10.8	Note on <b>dgit</b>	72
10.9	Patch by “ <b>gbp-pq</b> ” approach	72

10.10	Manage patch queue with <b>gbp-pq</b>	72
10.11	<b>gbp import-dscs --debsnap</b>	73
10.12	Note on <b>dgkit-maint-debrebase</b> workflow	73
10.13	<b>Quasi-native</b> Debian packaging	74
<b>11</b>	<b>Tipps</b>	<b>75</b>
11.1	Build under UTF-8	75
11.2	UTF-8 conversion	75
11.3	Hints for Debugging	75
<b>12</b>	<b>Tool usages</b>	<b>77</b>
12.1	<b>debdiff</b>	77
12.2	<b>dget</b>	77
12.3	<b>mk-origtargz</b>	78
12.4	<b>origtargz</b>	78
12.5	<b>git deborig</b>	78
12.6	<b>dpkg-source -b</b>	78
12.7	<b>dpkg-source -x</b>	78
12.8	<b>debc</b>	78
12.9	<b>piuparts</b>	78
12.10	<b>bts</b>	79
<b>13</b>	<b>Weitere Beispiele</b>	<b>80</b>
13.1	Cherry-pick templates	80
13.2	Kein Makefile (Shell, CLI)	82
13.3	Makefile (Shell, CLI)	88
13.4	pyproject.toml (Python3, CLI)	90
13.5	Makefile (Shell, GUI)	95
13.6	pyproject.toml (Python3, GUI)	97
13.7	Makefile (Paket mit einem Programm)	100
13.8	Makefile.in + configure (Paket mit einem Programm)	103
13.9	Autotools (Paket mit einem Programm)	106
13.10	CMake (Paket mit einem Programm)	109
13.11	Autotools (Paket mit mehreren Programmen)	112
13.12	CMake (multi-binary package)	118
13.13	Internationalization	123
13.14	Details	128
<b>14</b>	<b>debmake(1)-Handbuchseite</b>	<b>130</b>
14.1	BEZEICHNUNG	130
14.2	ÜBERSICHT	130
14.3	BESCHREIBUNG	130
14.3.1	Optionale Argumente:	130
14.4	BEISPIELE	133
14.5	HELFERPAKETE	134
14.6	CAVEAT	134
14.7	DEBUG	134
14.8	AUTOR	135
14.9	LIZENZ	135
14.10	SIEHE AUCH	135
<b>15</b>	<b>debmake options</b>	<b>136</b>
15.1	Shortcut options ( <b>-a</b> , <b>-i</b> )	136
15.2	<b>debmake -b</b>	136
15.3	<b>debmake -cc</b>	137
15.4	Snapshot upstream tarball ( <b>-d</b> , <b>-t</b> )	138
15.5	<b>debmake -j</b>	138
15.6	<b>debmake -k</b>	139
15.7	<b>debmake -P</b>	139

15.8 <b>debmake -T</b> . . . . .	139
15.9 <b>debmake -x</b> . . . . .	140

### **Abstract**

Dieser Anleitung »Leitfaden für Debian-Betreuer« (2024-10-01) beschreibt gewöhnlichen Debian-Benutzern und angehenden Entwicklern den Bau des Debian-Pakets mittels des Befehls **debmake**.

Diese Anleitung konzentriert sich auf die moderne Paketierart und enthält viele einfache Beispiele.

- POSIX-Shell-Skript-Paketierung
- Python3-Skript-Paketierung
- C mit Makefile/Autotools/CMake
- mehrere Binärpakete mit Laufzeitbibliotheken usw.

Diese »Anleitung für Debian-Betreuer« kann als Nachfolger des »Debian-Leitfaden für Neue Paketbetreuer« angesehen werden.



# Chapter 1

## Vorwort

Falls Sie ein etwas erfahrener Debian-Benutzer [1](#) sind, könnten Ihnen die folgende Situationen bekannt vorkommen:

- Sie möchten ein bestimmtes, noch nicht im Debian-Archiv verfügbares Softwarepaket installieren.
- Sie möchten ein Debian-Paket mit einer neueren Version der Originalautoren aktualisieren.
- Sie möchten Fehler in einem Debian-Paket mit Patches korrigieren.

Falls Sie ein Debian-Paket erstellen möchten, um diese Wünsche zu erfüllen und Ihre Arbeit der Debian-Gemeinschaft zur Verfügung stellen wollen, dann sind Sie die Zielgruppe dieser Anleitung als angehender Debian-Betreuer. [2](#) Willkommen in der Debian-Gemeinschaft.

Debian muss vielen sozialen und technischen Regeln und Konventionen folgen, da es eine große Organisation Freiwilliger mit einer Geschichte ist. Debian hat auch eine große Anzahl an Paketierungswerkzeugen und Archivverwaltungswerkzeugen entwickelt, um eine konsistente Menge an Binärpaketen zu bauen, die viele technische Ziele adressieren:

- packages build across many architectures (“Section [8.3](#)”)
- reproduzierbarer Bau (“Section [9.7](#)”)
- clean build under clearly specified package dependencies and patches (“Section [6.6](#)”, “Section [6.9](#)”, “Section [4.6](#)”)
- optimale Trennung in mehrere Binärpakete (“Section [9.11](#)”)
- reibungslose Bibliotheksübergänge (“Section [9.18](#)”)
- interaktive Anpassung der Installation (“Section [9.22](#)”)
- Multiarch-Unterstützung (“Section [9.10](#)”)
- Sicherheitserweiterung mittels bestimmter Compiler-Schalter (“Section [9.6](#)”)
- kontinuierliche Integration (“Section [9.4](#)”)
- Systemstarteinrichtung (“Section [9.5](#)”)
- ...

Dies ist für viele angehende Debian-Entwickler beim Einstieg in Debian etwas überwältigend. Diese Anleitung versucht, für ihren Start Einstiegspunkte bereitzustellen. Sie beschreibt folgendes:

- Was Sie wissen sollten, bevor Sie als angehender Betreuer bei Debian mitmachen.
- Wie es aussieht, ein einfaches Debian-Paket zu erstellen.

---

<sup>1</sup>Sie müssen ein bisschen über Unix-Programmierung wissen, aber Sie müssen definitiv kein Meister sein. Über den grundlegenden Umgang mit einem Debian-System können Sie in “[Debian-Referenz](#)” mehr erfahren. Es enthält auch einige Hinweise zum Lernen der Unix-Programmierung.

<sup>2</sup>Falls Sie nicht daran interessiert sind, das Debian-Paket anderen zugänglich zu machen, können Sie natürlich Ihre lokale Situation auch dadurch beheben, dass Sie die korrigierten Quellen der Originalautoren übersetzen und in `/usr/local/` installieren.

- Welche Art von Regeln für das Erstellen des Debian-Pakets existieren.
- Tipps zur Erstellung des Debian-Pakets.
- Beispiele für das Erstellen von Debian-Paketen für mehrere typische Szenarien.

The author felt limitations of updating the original “New Maintainers’ Guide” with the **dh-make** package and decided to create an alternative tool and its matching document to address modern requirements such as multi-arch. The result was the **debmake** package version: 4.0 in 2013. The current **debmake** is version: 4.5.0. It comes with this updated “[Guide for Debian Maintainers](#)” in the **debmake-doc** (version: 1.20-1) package. (In 2016, **dh-make** was ported from perl to python with updated features.)

Many chores and tips have been integrated into the **debmake** command allowing this guide to be terse. This guide also offers many packaging examples for you to get started.

#### Caution



Es bedarf vieler Stunden, um Debian-Pakete zu erstellen und zu betreuen. Der Debian-Betreuer muss **sowohl technisch kompetent als auch sorgfältig** sein, um diese Herausforderung zu meistern.

Einige wichtige Themen sind im Detail erklärt. Einige mögen Ihnen unwichtig erscheinen. Seien Sie geduldig. Einige Sonderfälle werden nur durch Referenzen auf externe Dokumente berücksichtigt. Dies passiert absichtlich, um diese Anleitung einfach und wartbar zu halten.

## Chapter 2

# Überblick

Das Debian-Paket für *package-1.0.tar.gz*, das eine einzige, einfache C-Quelle enthält, die “GNU-Programmier-Standard” und “FHS” folgt, kann mit dem Befehl **debmake** wie folgt erstellt werden:

```
$ tar -xvzf package-1.0.tar.gz
$ cd package-1.0
$ debmake
... Make manual adjustments of generated configuration files
$ debuild
```

Falls die manuellen Anpassungen der erstellten Konfigurationsdateien übersprungen werden, fehlt dem erstellten Binärpaket eine sinnvolle Paketbeschreibung. Es funktioniert aber dennoch unter dem Befehl **dpkg** gut für Ihren lokalen Einsatz.

### Caution



The **debmake** command only provides decent template files. These template files must be manually adjusted to their perfection to comply with the strict quality requirements of the Debian archive, if the generated package is intended for general consumption.

Falls Sie beim Debian-Paketieren neu sind, machen Sie sich keine Kopf über die Details und erkennen Sie nur das große Ganze.

If you have been exposed to Debian packaging, this looks vgrly much like the **dh\_make** command. This is because the **debmake** command is intended to replace functions offered historically by the **dh\_make** command. <sup>1</sup>

Der Befehl **debmake** wurde mit den folgenden Funktionalitäten gestaltet:

- moderner Paketierstil
  - **debian/copyright**: “DEP-5”-konform
  - **debian/control**: **substvar** support, **multiarch** support, multi binary packages, ...
  - **debian/rules**: **dh** syntax, compiler hardening options, ...
- Flexibilität
  - many options (see “Section 15.2”, “Chapter 14”, and “Chapter 15”)
- vernünftige Standardaktionen
  - Ausführung ohne Unterbrechung mit sauberen Ergebnissen
  - Erstellung des Multiarch-Pakets, außer die Option **-m** wird explizit angegeben
  - generate the non-native Debian package with the Debian source format “3.0 (quilt)”, unless the **-n** option is explicitly specified.

---

<sup>1</sup>Der Befehl **deb-make** war vor dem Befehl **dh\_make** beliebt. Das aktuelle Paket **debmake** beginnt seine Version bei **4.0**, um Überlappungen mit dem veralteten Paket **debmake**, das den Befehl **deb-make** bereitstellte, zu vermeiden.

- zusätzliche Nützlichkeiten
  - verification of the **debian/copyright** file against the current source (see “Section [15.6](#)”)

Der Befehl **debmake** delegiert den größten Teil der eigentlichen Arbeit an seine Backend-Pakete: **debhelper**, **dpkg-dev**, **devscripts**, **sbuild**, **schroot** usw.

Tip



Stellen Sie sicher, dass die Argumente **-b**, **-f**, **-l** und **-w** durch Maskieren vor dem Einfluss der Shell geschützt sind.

Tip



Das nicht-native Debian-Paket ist das normale Debian-Paket.

Tip



Das detaillierte Protokoll aller Paketbaubeispiele in diesem Dokument kann durch Folgen der Anweisungen in “Section [13.14](#)” erhalten werden.

Note



The generation of the **debian/copyright** file, and the outputs from the **-c** (see “Section [15.3](#)”) and **-k** (see “Section [15.6](#)”) options involve heuristic operations on the copyright and license information. They may produce some erroneous results.

# Chapter 3

## Voraussetzungen

Hier sind die Voraussetzungen, die Sie verstehen müssen, um bei Debian mitzumachen.

### 3.1 Leute bei Debian

Es nehmen verschiedene Arten von Leuten mit verschiedenen Rollen rund um Debian teil:

- **Originalautor:** die Person, die das ursprüngliche Programm erstellte.
- **Originalbetreuer:** Die Person, die derzeit das Programm betreut.
- **Betreuer:** Die Person, die das Debian-Paket des Programms erstellt.
- **Sponsor:** Eine Person, die den Betreuern beim Hochladen (nach Prüfen des Inhalts) des Pakets in das offizielle Debian-Paketarchiv hilft.
- **Mentor:** Eine Person, die neuen Betreuern beim Paketieren usw. hilft.
- **Debian-Entwickler (DD):** ein Mitglied des Debian-Projekts mit vollen Hochlade-Rechten in das offizielle Debian-Paketarchiv.
- **Debian-Betreuer (DM):** Eine Person, mit begrenzten Hochladerechten in das offizielle Debian-Paketarchiv.

Bitte beachten Sie, dass Sie nicht über Nacht ein offizieller **Debian-Entwickler (DD)** werden können, da es mehr als technischer Fähigkeit bedarf. Seien Sie davon nicht entmutigt. Falls es für andere nützlich ist, können Sie dennoch Ihre Pakete hochladen, entweder als **Betreuer** durch einen **Sponsor** oder als ein **Debian-Betreuer**.

Please note that you do not need to create any new packages to become an official Debian Developer. Contributing to the existing packages can provide a path to becoming an official Debian Developer too. There are many packages waiting for good maintainers (see “”Section 3.8””).

### 3.2 Wie Sie beitragen können

Bitte lesen Sie die folgenden Dokumenten, um zu verstehen, wie Sie zu Debian beitragen können:

- [“Wie können Sie Debian helfen?”](#) (offiziell)
- [“The Debian GNU/Linux FAQ, Chapter 13 - Contributing to the Debian Project”](#) (semi-official)
- [“Debian Wiki, HelpDebian”](#) (ergänzend)
- [“Debian New Member site”](#) (offiziell)
- [“Debian Mentors FAQ”](#) (ergänzend)

### 3.3 Soziale Dynamik von Debian

Bitte verstehen Sie die soziale Dynamik, um sich für die Wechselwirkungen mit Debian vorzubereiten:

- Wir sind alle Freiwillige.
  - Sie können anderen nicht vorschreiben, was getan werden soll.
  - Sie sollten motiviert sein, die Dinge selbst zu tun.
- Freundliche Zusammenarbeit ist der Motor.
  - Ihr Beitrag sollte Andere nicht überlasten.
  - Ihr Beitrag hat nur Wert, wenn ihn andere wertschätzen.
- Debian ist nicht Ihre Schule, bei der die Lehrer sich automatisch um Sie kümmern.
  - Sie sollten vieles selbst lernen können.
  - Aufmerksamkeit von anderen Freiwilligen ist ein rares Gut.
- Debian verbessert sich ständig.
  - Es wird erwartet, dass Sie hochqualitative Pakete erstellen.
  - Sie sollten sich Änderungen anpassen.

Da in der restlichen Anleitung nur auf die technischen Aspekte der Paketierung fokussiert wird, wird auf folgendes zum Verständnis der sozialen Dynamik von Debian verwiesen:

- [“Debian: 17 years of Free Software, ”do-ocracy”, and democracy”](#) (Introductory slides by the ex-DPL)

### 3.4 Technische Erinnerungen

Es folgen ein paar technische Erinnerungen, die anderen Betreuern bei der Arbeit an Ihrem Paket helfen und das Ergebnis von Debian insgesamt effektiv maximieren.

- Ermöglichen Sie in Ihrem Paket eine leichte Fehlersuche.
  - Halten Sie Ihr Paket einfach.
  - Machen Sie Ihr Paket nicht zu komplex.
- Halten Sie Ihr Paket gut dokumentiert.
  - Verwenden Sie einen lesbaren Code-Stil.
  - Fügen Sie in den Code Kommentare ein.
  - Formatieren Sie Code konsistent.
  - Verwalten Sie das Git-Depot [1](#) des Pakets.

#### Note



Die Fehlersuche in Software kann mehr Zeit verbrauchen, als die eigentliche Erstellung.

It is unwise to run your base system under the **unstable** suite even for the development system.

- Creation of binary **deb** packages and their verification should use minimal **unstable** chroot described in “Section [4.6](#)”.
- Basic interactive package development activities should use **unstable** chroot described in “Section [4.7](#)”.

<sup>1</sup>Die überwältigende Mehrheit der Debian-Betreuer verwenden **git** statt anderer VCS-Systeme wie **hg**, **bzr**, usw.

**Note**

Advanced package development activities such as testing of full Desktop systems, network daemons, and system installer packages, should use **unstable** suite running under the “[virtualization](#)”.

## 3.5 Debian-Dokumentation

Bitte lesen Sie nach Bedarf den einschlägigen Anteil der neusten Debian-Dokumentation, um perfekte Debian-Pakete zu erstellen:

- “Debian Policy Manual”
  - The official “must follow” rules (<https://www.debian.org/doc/devel-manuals#policy>)
- “Debian Developer’s Reference”
  - The official “best practice” document (<https://www.debian.org/doc/devel-manuals#devref>)
- “Guide for Debian Maintainers” — this guide
  - A “tutorial reference” document (<https://www.debian.org/doc/devel-manuals#debmake-doc>)

All these documents are published to <https://www.debian.org> using the **unstable** suite versions of corresponding Debian packages. If you wish to have local accesses to all these documents from your base system, please consider to use techniques such as “[apt-pinning](#)” and “[chroot](#)”.

Falls dieser Leitfaden der offiziellen Debian-Dokumentation widerspricht, dann ist die offizielle Debian-Dokumentation korrekt. Bitte reichen Sie mittels des Befehls **reportbug** (auf englisch) einen Fehlerbericht gegen das Paket **debmake-doc** ein.

Hier sind alternative Anleitungen, die Sie zusammen mit diesem Leitfaden lesen können:

- “Debian Packaging Tutorial”
  - <https://www.debian.org/doc/devel-manuals#packaging-tutorial>
  - <https://packages.qa.debian.org/p/packaging-tutorial.html>
- “Ubuntu Packaging Guide” (Ubuntu is Debian based.)
  - <http://packaging.ubuntu.com/html/>
- “Debian New Maintainers’ Guide” (predecessor of this tutorial, deprecated)
  - <https://www.debian.org/doc/devel-manuals#maint-guide>
  - <https://packages.qa.debian.org/m/maint-guide.html>

**Tip**

When reading these, you may consider using the **debmake** command in place of the **dh\_make** command.

## 3.6 Hilfequellen

Bevor Sie Ihre Fragen an einem öffentlichen Ort stellen, bemühen Sie sich vorher, die Antwort zu ermitteln, z.B. lesen Sie die gute Dokumentation:

- Paketierinformationen, die über die Befehle **aptitude**, **apt-cache** und **dpkg** verfügbar sind.
- Dateien in **/usr/share/doc/Paket** für alle einschlägigen Pakete.
- Inhalte von **man Befehl** für alle einschlägigen Befehle.
- Inhalte von **info Befehl** für alle einschlägigen Befehle.
- Inhalte von “[debian-mentors@lists.debian.org](mailto:debian-mentors@lists.debian.org)-Mailinglist-Archiv”.
- Inhalte von “[debian-devel@lists.debian.org](mailto:debian-devel@lists.debian.org)-Mailinglist-Archiv”.

Your desired information can be found effectively by using a well-formed search string such as “keyword **site:lists.debian.org**” to limit the search domain of the web search engine.

Die Herstellung eines kleinen Testpaketes ist eine gute Möglichkeit, Details des Paketierens zu erfahren. Bestehende, gut gewartete Debian-Pakete zu inspizieren ist der beste Weg, um zu lernen, wie andere Menschen Debian-Pakete erstellen.

Falls Sie immer noch Fragen über das Paketieren haben, können Sie die Fragen direkt stellen (auf Englisch):

- [debian-mentors@lists.debian.org](mailto:debian-mentors@lists.debian.org) mailing list. (This mailing list is for the novice.)
- [debian-devel@lists.debian.org](mailto:debian-devel@lists.debian.org) mailing list. (This mailing list is for the expert.)
- **IRC** such as #debian-mentors.
- Teams focusing on a specific set of packages. (Full list at <https://wiki.debian.org/Teams>)
- Sprachspezifische Mailinglisten
  - “[debian-devel-{french,italian,portuguese,spanish}@lists.debian.org](mailto:debian-devel-{french,italian,portuguese,spanish}@lists.debian.org)”
  - “[debian-chinese-gb@lists.debian.org](mailto:debian-chinese-gb@lists.debian.org)” (Diese Mailingliste ist für allgemeine Diskussion auf (vereinfachtem) Chinesisch.)
  - “[debian-devel@debian.or.jp](mailto:debian-devel@debian.or.jp)”

Die erfahreneren Debian-Entwickler werden Ihnen gerne helfen, wenn Sie nach den erforderlichen Vorarbeiten richtig fragen.

### Caution



Debian development is a moving target. Some information found on the web may be outdated, incorrect, and non-applicable. Please use them carefully.

## 3.7 Archivsituation

Bitte begreifen Sie die Situation des Debian-Archivs.

- Debian hat bereits Pakete für die meisten Programmarten.
- Die Anzahl an Paketen im Debian-Archiv ist mehrere zehnmal so groß wie die Anzahl der aktiven Betreuer.
- Bei einigen Paketen fehlt leider die entsprechende Aufmerksamkeit des Betreuers.



Daher werden Beiträge zu Paketen, die sich bereits im Archiv befinden, von anderen Betreuern weitaus mehr geschätzt (und erhalten eher Sponsoring für das Hochladen).

#### Tip



Der Befehl **wnpp-alert** aus dem Paket **devscripts** kann prüfen, ob installierte Pakete zur Adoption freigegeben oder verwaist sind.

#### Tip



The **how-can-i-help** package can show opportunities for contributing to Debian on packages installed locally.

## 3.8 Wege, beizutragen

Hier ist Pseudo-Python-Code für Ihre Wege, zu Debian mit einem **Programm** beizutragen:

```
if exist_in_debian(program):
    if is_team_maintained(program):
        join_team(program)
    if is_orphaned(program): # maintainer: Debian QA Group
        adopt_it(program)
    elif is_RFA(program): # Request for Adoption
        adopt_it(program)
    else:
        if need_help(program):
            contact_maintainer(program)
            triaging_bugs(program)
            preparing_QA_or_NMU_uploads(program)
        else:
            leave_it(program)
else: # new packages
    if not is_good_program(program):
        give_up_packaging(program)
    elif not is_distributable(program):
        give_up_packaging(program)
    else: # worth packaging
        if is_ITPed_by_others(program):
            if need_help(program):
                contact_ITPer_for_collaboration(program)
            else:
                leave_it_to_ITPer(program)
        else: # really new
            if is_applicable_team(program):
                join_team(program)
            if is_DFSG(program) and is_DFSG(dependency(program)):
                file_ITP(program, area="main") # This is Debian
            elif is_DFSG(program):
                file_ITP(program, area="contrib") # This is not Debian
            else: # non-DFSG
                file_ITP(program, area="non-free") # This is not Debian
            package_it_and_close_ITP(program)
```

Hier:

- Für das Prüfen von `exist_in_debian()` und `is_team_maintained()`:

- der Befehl **aptitude**
- “[Debian-Pakete](#)”-Webseite
- Debian wiki “[Teams](#)” page
- Für das Prüfen von `is_orphaned()`, `is_RFA()` und `is_ITPed_by_others()`:
  - Die Ausgabe des Befehls **wnpp-alert**.
  - “[Arbeit-bedürfende und voraussichtliche Pakete](#)”
  - “[Debian-Fehlerberichtsprotokolle: Fehler im Pseudo-Paket wnpp in Unstable](#)”
  - “[Debian-Pakete, die liebgewonnen werden müssen](#)”
  - “[Durchsuchen Sie wnpp Fehlerberichte basierend auf Debtags](#)”
- Für das Prüfen von `is_good_program()`:
  - Das Programm sollte nützlich sein.
  - Das Programm sollte keine Sicherheits- und Wartungsbedenken in das Debian-System einbringen.
  - Das Programm sollte gut dokumentiert sein und sein Code muss verständlich (d.h. nicht verschleiert) sein.
  - Die Autoren des Programms stimmen mit der Paketierung überein und sind mit Debian einvernehmlich.  
[2](#)
- Für die Prüfung von `is_it_DFSG()` und `is_its_dependency_DFSG()`:
  - “[Debian Richtlinien für Freie Software](#)” (DfSG).
- Für die Prüfung von `is_it_distributable()`:
  - Die Software muss eine Lizenz haben und sie sollte ihre Verbreitung erlauben.

You either need to file an **ITP** or adopt a package to start working on it. See the “Debian Developer’s Reference”:

- “[5.1. Neue Pakete](#)”.
- “[5.9. Verschieben, Entfernen, Verweisen, Adoptieren und Wiedereinführen von Paketen](#)”.

### 3.9 Neue Beitragende und Betreuer

Die neuen Beitragenden und Betreuer könnten sich fragen, was sie lernen sollten, um zu Debian beizutragen. Hier sind meine Vorschläge, abhängig von Ihrem Schwerpunkt:

- Paketierung
  - Grundlagen der **POSIX-Shell** und **Make**.
  - Etwas rudimentäres Wissen von **Perl** und **Python**.
- Übersetzungen
  - Grundlagen, wie das PO-basierte Übersetzungssystem funktioniert.
- Dokumentation
  - Basics of text markups (XML, ReST, Wiki, ...).

Der neue Beitragende und Betreuer könnte sich fragen, wo er mit Beiträgen zu Debian beginnen sollte. Hier sind meine Vorschläge, abhängig von Ihren Fertigkeiten:

- **POSIX-Shell**-, **Perl**- und **Python**-Fertigkeiten:
  - Schicken Sie Patches zum Debian-Installer.

---

<sup>2</sup>Das ist nicht die absolute Voraussetzung. Die ablehnende Einstellung der Originalautoren kann für uns alle zu einem großen Ressourcenproblem werden. Die freundlichen Originalautoren können konsultiert werden, um alle Probleme mit dem Programm zu lösen.

- Schicken Sie Patches an Paketierhelferskripte von Debian wie **Devscripts**, **Sbuild**, **Schroot** usw., die in diesem Dokument erwähnt sind.
- C- und C++-Fähigkeiten:
  - Schicken Sie Patches an Pakete mit den Prioritäten **required** und **important**.
- Sprachfähigkeiten jenseits von Englisch:
  - Schicken Sie Patches zu den PO-Dateien des Debian-Installers.
  - Schicken Sie Patches an den PO-Dateien der Pakete mit den Prioritäten **required** und **important**.
- Dokumentations-Fähigkeiten
  - Aktualisieren Sie Inhalte auf “[Debian-Wiki](#)”.
  - Schicken Sie Patches an das existierende “[Debian-Dokumentation](#)”.

Diese Aktivitäten sollten Ihnen einen guten Kontakt zu den anderen Debian-Menschen verschaffen, um Ihre Glaubwürdigkeit zu begründen.

Der unerfahrene Betreuer sollte das Paketieren von Programmen mit einer hohen Sicherheitsexposition vermeiden:

- **Setuid-** oder **Setgid-**Programme
- **Daemon-**Programme
- Programme, die in den Verzeichnissen **/sbin/** oder **/usr/sbin/** installiert werden

Wenn Sie mehr Erfahrung beim Paketieren gesammelt haben, werden Sie in der Lage sein, solche Programme zu paketieren.

## Chapter 4

# Werkzeugeinrichtung

Das Paket **build-essential** muss in Ihrer Bauumgebung installiert sein.

The **devscripts** package should be installed in the development environment of the maintainer.

It is a good idea to install and set up all of the popular set of packages mentioned in this chapter. These enable us to share the common baseline working environment, although these are not necessarily absolute requirements.

Please also consider to install the tools mentioned in the “[Overview of Debian Maintainer Tools](#)” in the “Debian Developer’s Reference”, as needed.

### Caution



Die hier vorgestellte Einrichtung der Werkzeuge ist nur als Beispiel gedacht und kann nicht mit den neuesten im System installierten Paketen übereinstimmen. Debian-Entwicklung ist ein voranschreitendes Ziel. Lesen Sie die relevante Dokumentation und aktualisieren Sie Ihre Konfiguration wo notwendig.

## 4.1 Email setup

Verschiedene Debian-Betreuungswerkzeuge erkennen Ihre zu verwendene E-Mail-Adresse und Ihren Namen über die Shell-Umgebungsvariablen **\$DEBEMAIL** und **\$DEBFULLNAME**.

Let’s set these environment variables by adding the following lines to **~/.bashrc** [1](#).

**Fügen Sie zur **~/.bashrc** folgendes hinzu**

```
DEBEMAIL="osamu@debian.org"
DEBFULLNAME="Osamu Aoki"
export DEBEMAIL DEBFULLNAME
```

### Note



The above is for the author of this manual. The configuration and operation examples presented in this manual use these email address and name settings. You must use your email address and name for your system.

## 4.2 mc setup

Der Befehl **mc** bietet Ihnen einen sehr leichten Zugang zur Verwaltung von Dateien. Es kann binäre **deb**-Dateien zum Prüfen ihrer Inhalte öffnen, indem die Eingabetaste über der binären **deb**-Datei gedrückt wird. Es verwendet den Befehl **dpkg-deb** als seinen Backend. Lassen Sie es uns wie folgt einrichten, um leichtes **chdir** zu ermöglichen.

<sup>1</sup>Hierbei wird angenommen, dass Sie die Bash als Ihre Anmelde-Shell verwenden. Falls Sie eine andere Anmelde-Shell, wie die Z-Shell, verwenden, verwenden Sie deren entsprechenden Konfigurationsdateien statt **~/.bashrc**.

Fügen Sie zur `~/bashrc` folgendes hinzu

```
# mc related
if [ -f /usr/lib/mc/mc.sh ]; then
    . /usr/lib/mc/mc.sh
fi
```

## 4.3 git setup

Heutzutage ist der Befehl **git** ein unverzichtbares Werkzeug, um den Quellbau mit Verlauf zu verwalten.

Die globale Benutzerkonfiguration für den Befehl **git**, wie Ihren Namen und Ihre E-Mail-Adresse, können in `~/gitconfig` wie folgt gesetzt werden:

```
$ git config --global user.name "Osamu Aoki"
$ git config --global user.email osamu@debian.org
```

Falls Sie an die CVS- oder Subversion-Befehle gewöhnt sind, möchten Sie vielleicht eine Reihe von Aliasen wie folgt setzen:

```
$ git config --global alias.ci "commit -a"
$ git config --global alias.co checkout
```

Sie können Ihre globale Konfiguration wie folgt prüfen:

```
$ git config --global --list
```

### Tip



Es ist essentiell, einige GUI git-Werkzeuge wie **gitk** oder **gitg** zu verwenden, um effektiv mit der Chronik des git-Depots zu arbeiten.

## 4.4 quilt setup

Der Befehl **quilt** bietet eine grundlegende Methode zur Aufzeichnung von Änderungen. Für die Debian-Paketierung sollte es so angepasst werden, dass Änderungen im **debian/patches**/-Verzeichnis anstelle des voreingestellten **patches**/-Verzeichnisses aufgezeichnet werden.

Um zu vermeiden, dass das Verhalten des Befehls **quilt** selbst geändert wird, erstellen wir einen Alias **dquilt** für das Debian-Paket, indem wir die folgenden Zeilen in die Datei `~/bashrc` einfügen. Die zweite Zeile bietet die gleiche Shell-Vervollständigungs-Funktion des **quilt**-Befehls für den **dquilt**-Befehl.

Fügen Sie zur `~/bashrc` folgendes hinzu

```
alias dquilt="quilt --quiltrc=${HOME}/.quiltrc-dpkg"
. /usr/share/bash-completion/completions/quilt
complete -F _quilt_completion $ _quilt_complete_opt dquilt
```

Dann erstellen wir `~/quiltrc-dpkg` wie folgt.

```
d=.
while [ ! -d $d/debian -a `readlink -e $d` != / ];
do d=$d/..; done
if [ -d $d/debian ] && [ -z $QUILT_PATCHES ]; then
    # if in Debian packaging tree with unset $QUILT_PATCHES
    QUILT_PATCHES="debian/patches"
    QUILT_PATCH_OPTS="--reject-format=unified"
    QUILT_DIFF_ARGS="-p ab --no-timestamps --no-index --color=auto"
    QUILT_REFRESH_ARGS="-p ab --no-timestamps --no-index"
    QUILT_COLORS="diff_hdr=1;32:diff_add=1;34:diff_rem=1;31:diff_hunk=1;33:"
    QUILT_COLORS="${QUILT_COLORS}diff_ctx=35:diff_cctx=33"
```

```
if ! [ -d $d/debian/patches ]; then mkdir $d/debian/patches; fi
fi
```

See **quilt**(1) and “[How To Survive With Many Patches or Introduction to Quilt \(quilt.html\)](#)” on how to use the **quilt** command.

Siehe “Section 5.9” für beispielhafte Verwendungen.

## 4.5 devscripts setup

Der Befehl **debsign**, der im Paket **devscripts** enthalten ist, wird verwendet, um das Debian-Paket mit Ihrem privaten GPG-Schlüssel zu signieren.

Der Befehl **debuild**, der im Paket **devscripts** enthalten ist, baut das Binärpaket und überprüft es mit dem Befehl **lintian**. Es ist praktisch, ausführliche Ausgaben von dem Befehl **lintian** zu haben.

Sie können diese in `~/.devscripts` wie folgt einrichten.

```
DEBUILD_DPKG_BUILDPACKAGE_OPTS="-i -I -us -uc"
DEBUILD_LINTIAN_OPTS="-i -I --show-overrides"
DEBSIGN_KEYID="Your_GPG_keyID"
```

The **-i** and **-I** options in **DEBUILD\_DPKG\_BUILDPACKAGE\_OPTS** for the **dpkg-source** command help rebuilding of Debian packages without extraneous contents (see “Chapter 7”).

Derzeit ist ein RSA-Schlüssel mit 4096 Bits eine gute Idee. Siehe “[Einen neuen GPG-Key erstellen](#)”.

## 4.6 sbuild setup

The **sbuild** package provides a clean room (“**chroot**”) build environment. It offers this efficiently with the help of **schroot** using the bind-mount feature of the modern Linux kernel.

Since it is the same build environment as the Debian’s **build** infrastructure, it is always up to date and comes full of useful features.

It can be customized to offer following features:

- Das **Schroot**-Paket, um die Geschwindigkeit der Chroot-Erstellung zu erhöhen.
- Das **lintian**-Paket, um Fehler im Paket zu finden.
- Das **Piuparts**-Paket, um Fehler im Paket zu finden.
- Das **Autopkgtest**-Paket, um Fehler im Paket zu finden.
- Das **ccache**-Paket, um die **gcc**-Geschwindigkeit zu erhöhen. (optional)
- Das **libeatmydata1**-Paket zur Erhöhung der **dpkg**-Geschwindigkeit. (optional)
- Die parallele **make**, um die Baugeschwindigkeit zu erhöhen. (optional)

Let’s set up **sbuild** environment [2](#):

```
$ sudo apt install sbuild piuparts autopkgtest lintian
$ sudo apt install sbuild-debian-developer-setup
$ sudo sbuild-debian-developer-setup -s unstable
```

Let’s update your group membership to include **sbuild** and verify it:

```
$ newgrp -
$ id
uid=1000(<yourname>) gid=1000(<yourname>) groups=...,132(sbuild)
```

Here, “reboot of system” or “**kill -TERM -1**” can be used instead to update your group membership [3](#).

Let’s create the configuration file `~/.sbuilder` in line with recent Debian practice of “[source-only-upload](#)” as:

<sup>2</sup>Be careful since some older HOWTOs may use different chroot setups.

<sup>3</sup>Simply “logout and login under some modern GUI Desktop environment” may not update your group membership.

```

cat >~/.sbuilderdrc << 'EOF'
#####
# PACKAGE BUILD RELATED (source-only-upload as default)
#####
# -d
$distribution = 'unstable';
# -A
$build_arch_all = 1;
# -s
$build_source = 1;
# --source-only-changes
$source_only_changes = 1;
# -v
$verbose = 1;

#####
# POST-BUILD RELATED (turn off functionality by setting variables to 0)
#####
$run_lintian = 1;
$lintian_opts = ['-i', '-I'];
$run_piuparts = 1;
$piuparts_opts = ['--schroot', 'unstable-amd64-sbuild'];
$run_autopkgtest = 1;
$autopkgtest_root_args = '';
$autopkgtest_opts = [ '--', 'schroot', '%r-%a-sbuild' ];

#####
# PERL MAGIC
#####
1;
EOF

```

**Note**

There are some exceptional cases such as NEW uploads, uploads with NEW binary packages, and security uploads where you can't do [source-only-upload](#) but are required to upload with binary packages. The above configuration needs to be adjusted for those exceptional cases.

Following document assumes that **sbuild** is configured this way.

Edit this to your needs. Post-build tests can be turned on and off by assigning 1 or 0 to the corresponding variables,

**Warning**

Die optionale Anpassung kann negative Auswirkungen haben. Im Zweifelsfall deaktivieren Sie sie.

**Note**

The parallel **make** may fail for some existing packages and may make the build log difficult to read.

## Tip



Many **sbuild** related hints are available at “Section 8.7” and [“https://wiki.debian.org/sbuild”](https://wiki.debian.org/sbuild).

## 4.7 Persistent chroot setup

## Note



Use of independent copied chroot filesystem prevents contaminating the source chroot used by **sbuild**.

For building new experimental packages or for debugging buggy packages, let's setup dedicated persistent chroot “**source:unstable-amd64-desktop**” by:

```
$ sudo cp -a /srv/chroot/unstable-amd64-sbuild-$suffix /srv/chroot/unstable-amd64 ↵
  -desktop
$ sudo tee /etc/schroot/chroot.d/unstable-amd64-desktop << EOF
[unstable-desktop]
description=Debian sid/amd64 persistent chroot
groups=root,sbuild
root-groups=root,sbuild
profile=desktop
type=directory
directory=/srv/chroot/unstable-amd64-desktop
union-type=overlay
EOF
```

Here, **desktop** profile is used instead of **sbuild** profile. Please make sure to adjust **/etc/schroot/desktop/fstab** to make package source accessible from inside of the chroot.

You can log into this chroot “**source:unstable-amd64-desktop**” by:

```
$ sudo schroot -c source:unstable-amd64-desktop
```

## 4.8 gbp setup

The **git-buildpackage** package offers the **gbp(1)** command. Its user configuration file is **~/.gbp.conf**.

```
# Configuration file for "gbp <command>"
```

```
[DEFAULT]
# the default build command:
builder = sbuild
# use pristine-tar:
pristine-tar = True
# Use color when on a terminal, alternatives: on/true, off/false or auto
color = auto
```

## 4.9 HTTP-Proxy

You should set up a local HTTP caching proxy to save the bandwidth for the Debian package repository access. There are several choices:



- Specialized HTTP caching proxy using the **apt-cacher-ng** package.
- Generic HTTP caching proxy (**squid** package) configured by **squid-deb-proxy** package

In order to use this HTTP proxy without manual configuration adjustment, it's a good idea to install either **auto-apt-proxy** or **squid-deb-proxy-client** package to everywhere.

## 4.10 Privates Debian-Depot

Sie können ein privates Debian-Depot mit dem Paket **reprepro** einrichten.

## 4.11 Virtuelle Maschinen

For testing GUI application, it is a good idea to have virtual machines. Install **virt-manager** and **qemu-kvm** packages.

Use of chroot and virtual machines allows us not to update the whole host PC to the latest **unstable** suite.

## 4.12 Local network with virtual machines

In order to access virtual machines easily over the local network, setting up multicast DNS service discovery infrastructure by installing **avahi-utils** is a good idea.

For all running virtual machines and the host PC, we can use each host name appended with **.local** for SSH to access each other.

## Chapter 5

# Simple packaging

There is an old Latin saying: “**Longum iter est per praecepta, breve et efficax per exempla**” (“It’s a long way by the rules, but short and efficient with examples”).

### 5.1 Packaging tarball

Hier ist ein Beispiel zur Erstellung eines einfachen Debian-Pakets aus einer einfachen C-Quelle mittels einer **Make-file** als Bausystem.

Nehmen wir an, der Tarball der Originalautoren heißt **debhello-0.0.tar.gz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

**Basics for the install from the upstream tarball**

```
$ tar -xzmf debhello-0.0.tar.gz
$ cd debhello-0.0
$ make
$ make install
```

Debian packaging requires changing this “**make install**” process to install files to the target system image location instead of the normal location under **/usr/local**.

#### Note



Beispiele zur Erstellung von Debian-Paketen aus anderen, komplizierteren Bausystemen werden in “Chapter 13” beschrieben.

### 5.2 Gesamtbild

The big picture for building a single non-native Debian package from the upstream tarball **debhello-0.0.tar.gz** can be summarized as:

- The maintainer obtains the upstream tarball **debhello-0.0.tar.gz** and untars its contents to the **debhello-0.0** directory.
- The **debmake** command debianizes the upstream source tree by adding template files only in the **debian** directory.
  - The **debhello\_0.0.orig.tar.gz** symlink is created pointing to the **debhello-0.0.tar.gz** file.
  - The maintainer customizes template files.
- The **debuild** command builds the binary package from the debianized source tree.
  - **debhello-0.0-1.debian.tar.xz** is created containing the **debian** directory.

**Big picture of package building**

```
$ tar -xzmf debhello-0.0.tar.gz
$ cd debhello-0.0
$ debmake
... manual customization
$ debuild
...
```

#### Tip



The **debuild** command in this and following examples may be substituted by equivalent commands such as the **sbuild** command.

#### Tip



If the upstream tarball in the **.tar.xz** format is available, use it instead of the one in the **.tar.gz** and **.tar.bz2** formats. The **xz** compression format offers the better compression than the **gzip** and **bzip2** compressions.

## 5.3 Was ist Debmake?

#### Note



Actual packaging activities are often performed manually without using **debmake** while referencing only existing similar packages and “[Debian Policy Manual](#)”.

The **debmake** command is the helper script for the Debian packaging. (“Chapter 14”)

- It creates good template files for the Debian packages.
- It always sets most of the obvious option states and values to reasonable defaults.
- Es erstellt den Tarball der Originalautoren und die benötigten Symlinks, falls sie fehlen.
- Es setzt die bestehenden Konfigurationsdateien im Verzeichnis **debian/** nicht außer Kraft.
- Es unterstützt die **Multiarch**-Pakete.
- It provides short extracted license texts as **debian/copyright** in decent accuracy to help license review.

Diese Funktionalitäten ermöglichen ein einfaches und moderens Paketieren für Debian mit **debmake**.

In retrospective, I created **debmake** to simplify this documentation. I consider **debmake** to be more-or-less a demonstration session generator for tutorial purpose.

The **debmake** command isn’t the only helper script to make a Debian package. If you are interested alternative packaging helper tools, please see:

- Debian wiki: “[AutomaticPackagingTools](#)” — Extensive comparison of packaging helper scripts
- Debian wiki: “[CopyrightReviewTools](#)” — Extensive comparison of copyright review helper scripts

## 5.4 Was ist Debuild?

Hier ist eine Zusammenfassung von Befehlen, die dem Befehl **debuild** ähnlich sind.

- Die Datei **debian/rules** definiert, wie das binäre Debian-Paket gebaut wird.
- Der Befehl **dpkg-buildpackage** ist der offizielle Befehl, ein Debian-Binärpaket zu bauen. Bei einem normalen Binärbau führt er grob die folgenden Schritte aus:
  - “**dpkg-source --before-build**” (apply Debian patches, unless they are already applied)
  - “**fakeroot debian/rules clean**”
  - “**dpkg-source --build**” (build the Debian source package)
  - “**fakeroot debian/rules build**”
  - “**fakeroot debian/rules binary**”
  - “**dpkg-genbuildinfo**” (generate a **\*.buildinfo** file)
  - “**dpkg-genchanges**” (generate a **\*.changes** file)
  - “**fakeroot debian/rules clean**”
  - “**dpkg-source --after-build**” (unapply Debian patches, if they are applied during **--before-build**)
  - “**debsign**” (sign the **\*.dsc** and **\*.changes** files)
    - \* If you followed “Section 4.5” to set the **-us** and **-uc** options, this step is skipped and you must run the **debsign** command manually.
- The **debuild** command is a wrapper script of the **dpkg-buildpackage** command to build the Debian binary package under the proper environment variables.
- The **sbuild** command is a wrapper script to build the Debian binary package under the proper chroot environment with the proper environment variables.

### Note



Siehe **dpkg-buildpackage(1)** für die Details.

## 5.5 Schritt 1: Holen der Quellen der Originalautoren

Let's get the upstream source.

**Download debhello-0.0.tar.gz**

```
$ wget http://www.example.org/download/debhello-0.0.tar.gz
...
$ tar -xzmf debhello-0.0.tar.gz
$ tree
.
+-- debhello-0.0
|   +-- Makefile
|   +-- README.md
|   +-- src
|       +-- hello.c
+-- debhello-0.0.tar.gz

3 directories, 4 files
```

Here, the C source **hello.c** is a very simple one.

**hello.c**

```
$ cat debhello-0.0/src/hello.c
#include <stdio.h>
int
main()
{
    printf("Hello, world!\n");
    return 0;
}
```

Here, the **Makefile** supports “[GNU Coding Standards](#)” and “[FHS](#)”. Notably:

- build binaries honoring **\$(CPPFLAGS)**, **\$(CFLAGS)**, **\$(LDFLAGS)**, etc.
- install files with **\$(DESTDIR)** defined to the target system image
- install files with **\$(prefix)** defined, which can be overridden to be **/usr**

#### Makefile

```
$ cat debhello-0.0/Makefile
prefix = /usr/local

all: src/hello

src/hello: src/hello.c
    @echo "CFLAGS=$(CFLAGS)" | \
        fold -s -w 70 | \
        sed -e 's/^/# /'
    $(CC) $(CPPFLAGS) $(CFLAGS) $(LDCFLAGS) -o $@ $^

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello

.PHONY: all install clean distclean uninstall
```

#### Note



The **echo** of the **\$(CFLAGS)** variable is used to verify the proper setting of the build flag in the following example.

## 5.6 Step 2: Generate template files with debmake

Die Ausgabe des Befehls **debmake** ist sehr ausführlich und erklärt seine Tätigkeiten wie folgt:

#### The output from the debmake command

```
$ cd /path/to/debhello-0.0
$ debmake -x1
I: set parameters
I: sanity check of parameters
I: pkg="debhello", ver="0.0", rev="1"
```

```

I: *** start packaging in "debhello-0.0". ***
I: provide debhello_0.0.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-0.0.tar.gz debhello_0.0.orig.tar.gz
I: pwd = "/path/to/debhello-0.0"
I: parse binary package settings:
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: analyze the source tree
I: build_type = make
I: scan source for copyright+license text and file extensions
I: 50 %, ext = md
I: 50 %, ext = c
I: check_all_licenses
I: ...
I: check_all_licenses completed for 3 files.
I: bunch_all_licenses
I: format_all_licenses
I: make debian/* template files
I: debmake -x "1" ...
I: creating => debian/control
I: creating => debian/copyright
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra0_changel...
I: creating => debian/changelog
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra0_rules.t...
I: creating => debian/rules
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra0source_f...
I: creating => debian/source/format
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_README....
I: creating => debian/README.Debian
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_README....
I: creating => debian/README.source
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_clean.t...
I: creating => debian/clean
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_gbp.con...
I: creating => debian/gbp.conf
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_salsa-c...
I: creating => debian/salsa-ci.yml
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1_watch.t...
I: creating => debian/watch
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1tests_co...
I: creating => debian/tests/control
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1upstream...
I: creating => debian/upstream/metadata
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1patches_...
I: creating => debian/patches/series
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1source.n...
I: creating => debian/source/local-options.ex
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1source.n...
I: creating => debian/source/local-patch-header.ex
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1single_d...
I: creating => debian/dirs
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1single_i...
I: creating => debian/install
I: substituting => /usr/lib/python3/dist-packages/debmake/data/extra1single_l...
I: creating => debian/links
I: $ wrap-and-sort
I: $ wrap-and-sort complete. Now, debian/* may have a blank line at the top....

```

The **debmake** command generates all these template files based on command line options. Since no options are specified, the **debmake** command chooses reasonable default values for you:

- Der Quellpaketname: **debhello**
- Die Version der Originalautoren: **0.0**

- Deb Binärpaketname: **debhello**
- Die Debian-Revision: **1**
- The package type: **bin** (the ELF binary executable package)
- The **-x** option: **-x1** (without maintainer script supports for simplicity)

#### Note



Here, the **debmake** command is invoked with the **-x1** option to keep this tutorial simple. Use of default **-x3** option is highly recommended.

Lassen Sie uns die erstellten Vorlagendateien anschauen.

#### Der Quellbaum, nach der grundlegenden Ausführung von debmake.

```
$ cd /path/to
$ tree
.
+-- debhello-0.0
|   +-- Makefile
|   +-- README.md
|   +-- debian
|       +-- README.Debian
|       +-- README.source
|       +-- changelog
|       +-- clean
|       +-- control
|       +-- copyright
|       +-- dirs
|       +-- gbp.conf
|       +-- install
|       +-- links
|       +-- patches
|       |   +-- series
|       +-- rules
|       +-- salsa-ci.yml
|       +-- source
|       |   +-- format
|       |   |   +-- local-options.ex
|       |   |   +-- local-patch-header.ex
|       +-- tests
|       |   +-- control
|       +-- upstream
|       |   +-- metadata
|       +-- watch
|   +-- src
|       +-- hello.c
+-- debhello-0.0.tar.gz
+-- debhello_0.0.orig.tar.gz -> debhello-0.0.tar.gz

8 directories, 24 files
```

The **debian/rules** file is the build script provided by the package maintainer. Here is its template file generated by the **debmake** command.

#### debian/rules (Vorlagendatei):

```
$ cd /path/to/debhello-0.0
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
```

```
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1

%:
    dh $@

#override_dh_auto_install:
#    dh_auto_install -- prefix=/usr

#override_dh_install:
#    dh_install --list-missing -X.pyc -X.pyo
```

This is essentially the standard **debian/rules** file with the **dh** command. (There are some commented out contents for you to customize it.)

The **debian/control** file provides the main meta data for the Debian package. Here is its template file generated by the **debmake** command.

**debian/control (Vorlagendatei):**

```
$ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/debhello

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: auto-generated package by debmake
    This Debian binary package was auto-generated by the
    debmake(1) command provided by the debmake package.
```

#### Warning



If you leave “**Section: unknown**” in the template **debian/control** file unchanged, the **lintian** error may cause the build to fail.

Since this is the ELF binary executable package, the **debmake** command sets “**Architecture: any**” and “**Multi-Arch: foreign**”. Also, it sets required **substvar** parameters as “**Depends: \${shlibs:Depends}, \${misc:Depends}**”. These are explained in “Chapter 6”.

#### Note



Please note this **debian/control** file uses the RFC-822 style as documented in “[5.2 Source package control files — debian/control](#)” of the “Debian Policy Manual”. The use of the empty line and the leading space are significant.

The **debian/copyright** file provides the copyright summary data of the Debian package. Here is its template file generated by the **debmake** command.

**debian/copyright (Vorlagendatei):**



```
$ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: <preferred name and address to reach the upstream project>
Source: <url://example.com>
#
# Please double check copyright with the licensecheck(1) command.

Files:      Makefile
           README.md
           src/hello.c
Copyright:  __NO_COPYRIGHT_NOR_LICENSE__
License:    __NO_COPYRIGHT_NOR_LICENSE__

#-----
# Files marked as NO_LICENSE_TEXT_FOUND may be covered by the following
# license/copyright files.
```

## 5.7 Schritt 3: Anpassung der Vorlagendateien

Um ein geeignetes Debian-Paket zu erstellen, sind manuelle Anpassungen durch den Betreuer notwendig.

In order to install files as a part of the system files, the **\$(prefix)** value of **/usr/local** in the **Makefile** should be overridden to be **/usr**. This can be accommodated by the following the **debian/rules** file with the **override\_dh\_auto\_install** target setting “**prefix=/usr**”.

**debian/rules (Betreuerversion):**

```
$ cd /path/to/debhello-0.0
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_install:
    dh_auto_install -- prefix=/usr
```

Exportieren der Umgebungsvariable **DH\_VERBOSE** in der Datei **debian/rules** zwingt das Werkzeug **debhelper** dazu, einen feingranularen Baubericht zu erstellen.

Exporting **DEB\_BUILD\_MAINT\_OPTION** as above sets the hardening options as described in the “FEATURE AREAS/ENVIRONMENT” in **dpkg-buildflags(1)**. [1](#)

Durch Exportieren von **DEB\_CFLAGS\_MAINT\_APPEND** wie oben wird der C-Compiler gezwungen, alle Warnungen auszugeben.

Durch Exportieren von **DEB\_LDFLAGS\_MAINT\_APPEND** wie oben wird der Linker gezwungen, nur zu linken, wenn die Bibliothek tatsächlich benötigt wird. [2](#)

The **dh\_auto\_install** command for the Makefile based build system essentially runs “**\$(MAKE) install DESTDIR=debian/debhello**”. The creation of this **override\_dh\_auto\_install** target changes its behavior to “**\$(MAKE) install DESTDIR=debian/debhello prefix=/usr**”.

Hier sind die Betreuerversionen der Dateien **debian/control** und **debian/copyright**.

**debian/control (Betreuerversion):**

<sup>1</sup>This is a cliché to force a read-only relocation link for the hardening and to prevent the lintian warning “**W: debhello: hardening-no-relro usr/bin/hello**”. This is not really needed for this example but should be harmless. The lintian tool seems to produce a false positive warning for this case which has no linked library.

<sup>2</sup>This is a cliché to prevent overlinking for the complex library dependency case such as Gnome programs. This is not really needed for this simple example but should be harmless.

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: Simple packaging example for debmake
 This Debian binary package is an example package.
(This is an example only)
```

#### debian/copyright (Betreuerversion):

```
$ vim debian/copyright
... hack, hack, hack, ...
$ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright:  2015-2021 Osamu Aoki <osamu@debian.org>
License:     Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

Let's remove unused template files and edit remaining template files:

- **debian/README.source**
- **debian/source/local-option.ex**
- **debian/source/local-patch-header.ex**
- **debian/patches/series** (No upstream patch)
- **clean**
- **dirs**
- **install**

- **links**

**Vorlagendateien unter debian/. (v=0.0):**

```
$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 11 files
```

#### Tip



Konfigurationsdateien, die vom Befehl **dh\_\*** aus dem Paket **debhelper** verwandt werden, behandeln normalerweise # als Beginn einer Kommentarzeile.

## 5.8 Step 4: Building package with debuild

You can create a non-native Debian package using the **debuild** command or its equivalents (see “Section 5.4”) in this source tree. The command output is very verbose and explains what it does as follows.

### Building package with debuild

```
$ cd /path/to/debhello-0.0
$ debuild
dpkg-buildpackage -us -uc -ui -i
dpkg-buildpackage: info: source package debhello
dpkg-buildpackage: info: source version 0.0-1
dpkg-buildpackage: info: source distribution unstable
dpkg-buildpackage: info: source changed by Osamu Aoki <osamu@debian.org>
dpkg-source -i --before-build .
dpkg-buildpackage: info: host architecture amd64
debian/rules clean
dh clean
  dh_auto_clean
    make -j12 distclean
...
debian/rules binary
dh binary
  dh_update_autotools_config
  dh_autoreconf
  dh_auto_configure
  dh_auto_build
    make -j12 "INSTALL=install --strip-program=true"
make[1]: Entering directory '/path/to/debhello-0.0'
```

```
# CFLAGS=-g -O2
...
Finished running lintian.
```

Sie können überprüfen, dass **CFLAGS** korrekt mit **-Wall** und **-pedantic** durch die Variable **DEB\_CFLAGS\_MAINT\_APPEND** aktualisiert ist.

Wie vom Paket **lintian** berichtet sollte eine Handbuchseite zum Paket hinzugefügt werden, wie dies in späteren Beispielen gezeigt wird (siehe “Chapter 13”). Lassen Sie uns jetzt weitermachen.

Lassen Sie uns die Ergebnisse anschauen.

**Die durch den Befehl `debuild` erstellten Dateien von `debhello` Version 0.0:**

```
$ cd /path/to
$ tree -FL 1
./
+-- debhello-0.0/
+-- debhello-0.0.tar.gz
+-- debhello-dbgsym_0.0-1_amd64.deb
+-- debhello_0.0-1.debian.tar.xz
+-- debhello_0.0-1.dsc
+-- debhello_0.0-1_amd64.build
+-- debhello_0.0-1_amd64.buildinfo
+-- debhello_0.0-1_amd64.changes
+-- debhello_0.0-1_amd64.deb
+-- debhello_0.0.orig.tar.gz -> debhello-0.0.tar.gz

2 directories, 9 files
```

You see all the generated files.

- Das **debhello\_0.0.orig.tar.gz** ist ein Symlink auf den Tarball der Originalautoren.
- The **debhello\_0.0-1.debian.tar.xz** contains the maintainer generated contents.
- The **debhello\_0.0-1.dsc** is the meta data file for the Debian source package.
- The **debhello\_0.0-1\_amd64.deb** is the Debian binary package.
- The **debhello-dbgsym\_0.0-1\_amd64.deb** is the Debian debug symbol binary package. See “Section 9.21”.
- The **debhello\_0.0-1\_amd64.build** file is the build log file.
- The **debhello\_0.0-1\_amd64.buildinfo** file is the meta data file generated by **dpkg-genbuildinfo(1)**.
- The **debhello\_0.0-1\_amd64.changes** is the meta data file for the Debian binary package.

The **debhello\_0.0-1.debian.tar.xz** contains the Debian changes to the upstream source as follows.

**The compressed archive contents of `debhello_0.0-1.debian.tar.xz`:**

```
$ tar -tzf debhello-0.0.tar.gz
debhello-0.0/
debhello-0.0/src/
debhello-0.0/src/hello.c
debhello-0.0/Makefile
debhello-0.0/README.md
$ tar --xz -tf debhello_0.0-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/gbp.conf
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/tests/
```

```

debian/tests/control
debian/upstream/
debian/upstream/metadata
debian/watch

```

The **debhello\_0.0-1\_amd64.deb** contains the binary files to be installed to the target system.

The **debhello-debsym\_0.0-1\_amd64.deb** contains the debug symbol files to be installed to the target system.

**The binary package contents of all binary packages:**

```

$ dpkg -c debhello-dbgsym_0.0-1_amd64.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/lib/
drwxr-xr-x root/root ... ./usr/lib/debug/
drwxr-xr-x root/root ... ./usr/lib/debug/.build-id/
drwxr-xr-x root/root ... ./usr/lib/debug/.build-id/be/
-rw-r--r-- root/root ... ./usr/lib/debug/.build-id/be/f1e0185834f3c3e2614cf8...
drwxr-xr-x root/root ... ./usr/share/
drwxr-xr-x root/root ... ./usr/share/doc/
lrwxrwxrwx root/root ... ./usr/share/doc/debhello-dbgsym -> debhello
$ dpkg -c debhello_0.0-1_amd64.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/bin/
-rwxr-xr-x root/root ... ./usr/bin/hello
drwxr-xr-x root/root ... ./usr/share/
drwxr-xr-x root/root ... ./usr/share/doc/
drwxr-xr-x root/root ... ./usr/share/doc/debhello/
-rw-r--r-- root/root ... ./usr/share/doc/debhello/README.Debian
-rw-r--r-- root/root ... ./usr/share/doc/debhello/changelog.Debian.gz
-rw-r--r-- root/root ... ./usr/share/doc/debhello/copyright

```

The generated dependency list of all binary packages.

**The generated dependency list of all binary packages (v=0.0):**

```

$ dpkg -f debhello-dbgsym_0.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: debhello (= 0.0-1)
$ dpkg -f debhello_0.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libc6 (>= 2.34)

```

### Caution



Many more details need to be addressed before uploading the package to the Debian archive.

### Note



If manual adjustments of auto-generated configuration files by the **debmake** command are skipped, the generated binary package may lack meaningful package description and some of the policy requirements may be missed. This sloppy package functions well under the **dpkg** command, and may be good enough for your local deployment.

## 5.9 Step 3 (alternatives): Modification to the upstream source

The above example did not touch the upstream source to make the proper Debian package. An alternative approach as the maintainer is to modify files in the upstream source. For example, **Makefile** may be modified to set the **\$(prefix)** value to **/usr**.

### Note



The above “Section 5.7” using the **debian/rules** file is the better approach for packaging for this example. But let’s continue on with this alternative approaches as a leaning experience.

In the following, let’s consider 3 simple variants of this alternative approach to generate **debian/patches/\*** files representing modifications to the upstream source in the Debian source format “**3.0 (quilt)**”. These substitute “Section 5.7” in the above step-by-step example:

- “Section 5.10”
- “Section 5.11”
- “Section 5.12”

Please note the **debian/rules** file used for these examples doesn’t have the **override\_dh\_auto\_install** target as follows:

#### **debian/rules (alternative maintainer version):**

```
$ cd /path/to/debhello-0.0
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@
```

## 5.10 Patch by “diff -u” approach

Here, the patch file **000-prefix-usr.patch** is created using the **diff** command.

#### **Patch by diff -u**

```
$ cp -a debhello-0.0 debhello-0.0.orig
$ vim debhello-0.0/Makefile
... hack, hack, hack, ...
$ diff -Nru debhello-0.0.orig debhello-0.0 >000-prefix-usr.patch
$ cat 000-prefix-usr.patch
diff -Nru debhello-0.0.orig/Makefile debhello-0.0/Makefile
--- debhello-0.0.orig/Makefile    2024-07-24 10:12:40.382927188 +0900
+++ debhello-0.0/Makefile        2024-07-24 10:12:40.478928659 +0900
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello

$ rm -rf debhello-0.0
$ mv -f debhello-0.0.orig debhello-0.0
```

Please note that the upstream source tree is restored to the original state after generating a patch file **000-prefix-usr.patch**.

This **000-prefix-usr.patch** is edited to be **DEP-3** conforming and moved to the right location as below.

**000-prefix-usr.patch (DEP-3):**

```
$ echo '000-prefix-usr.patch' >debian/patches/series
$ vim ../000-prefix-usr.patch
... hack, hack, ...
$ mv -f ../000-prefix-usr.patch debian/patches/000-prefix-usr.patch
$ cat debian/patches/000-prefix-usr.patch
From: Osamu Aoki <osamu@debian.org>
Description: set prefix=/usr patch
diff -Nru debhello-0.0.orig/Makefile debhello-0.0/Makefile
--- debhello-0.0.orig/Makefile
+++ debhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello
```

#### Note



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of “Section 5.8”, the **dpkg-source** command assumes that no patch was applied to the upstream source, since the **.pc/applied-patches** is missing.

## 5.11 Patch by **dquilt** approach

Here, the patch file **000-prefix-usr.patch** is created using the **dquilt** command.

**dquilt** is a simple wrapper of the **quilt** program. The syntax and function of the **dquilt** command is the same as the **quilt(1)** command, except for the fact that the generated patch is stored in the **debian/patches/** directory.

**Patch by **dquilt****

```
$ dquilt new 000-prefix-usr.patch
Patch debian/patches/000-prefix-usr.patch is now on top
$ dquilt add Makefile
File Makefile added to patch debian/patches/000-prefix-usr.patch
... hack, hack, ...
$ head -1 Makefile
prefix = /usr
$ dquilt refresh
Refreshed patch debian/patches/000-prefix-usr.patch
$ dquilt header -e --dep3
... edit the DEP-3 patch header with editor
$ tree -a
.
+-- debian
|   +-- changelog
|   +-- clean
|   +-- control
|   +-- copyright
|   +-- dirs
|   +-- gbp.conf
|   +-- install
|   +-- links
|   +-- patches
|   |   +-- 000-prefix-usr.patch
```

```

| | +-- series
| +-- README.Debian
| +-- README.source
| +-- rules
| +-- salsa-ci.yml
| +-- source
| | +-- format
| | +-- local-options.ex
| | +-- local-patch-header.ex
| +-- tests
| | +-- control
| +-- upstream
| | +-- metadata
| +-- watch
+-- Makefile
+-- .pc
| +-- 000-prefix-usr.patch
| | +-- Makefile
| | +-- .timestamp
| +-- applied-patches
| +-- .quilt_patches
| +-- .quilt_series
| +-- .version
+-- README.md
+-- src
    +-- hello.c

9 directories, 29 files
$ cat debian/patches/series
000-prefix-usr.patch
$ cat debian/patches/000-prefix-usr.patch
Description: set prefix=/usr patch
Author: Osamu Aoki <osamu@debian.org>
Index: debhello-0.0/Makefile
=====
--- debhello-0.0.orig/Makefile
+++ debhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello

```

Here, **Makefile** in the upstream source tree doesn't need to be restored to the original state for the packaging.

#### Note



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of “Section 5.8”, the **dpkg-source** command assumes that patches were applied to the upstream source, since the **.pc/applied-patches** exists.

The upstream source tree can be restored to the original state for the packaging.

#### The upstream source tree (restored):

```

$ dquilt pop -a
Removing patch debian/patches/000-prefix-usr.patch
Restoring Makefile

No patches applied
$ head -1 Makefile
prefix = /usr/local
$ tree -a .pc

```



```
.pc
+-- .quilt_patches
+-- .quilt_series
+-- .version

1 directory, 3 files
```

Here, **Makefile** is restored and the **.pc/applied-patches** is missing.

## 5.12 Patch by “dpkg-source --auto-commit” approach

Here, the patch file isn’t created in this step but the source files are setup to create **debian/patches/\*** files in the following step of “Section 5.8”.

Bearbeiten Sie die Quellen der Originalautoren.

### Modified Makefile

```
$ vim Makefile
... hack, hack, hack, ...
$ head -n1 Makefile
prefix = /usr
```

Let’s edit **debian/source/local-options**:

### debian/source/local-options for auto-commit

```
$ mv debian/source/local-options.ex debian/source/local-options
$ vim debian/source/local-options
... hack, hack, hack, ...
$ cat debian/source/local-options
# == Patch applied strategy (merge) ==
#
# The source outside of debian/ directory is modified by maintainer and
# different from the upstream one:
# * Workflow using dpkg-source commit (commit all to VCS after dpkg-source ...
#   https://www.debian.org/doc/manuals/debmake-doc/ch04.en.html#dpkg-sour...
# * Workflow described in dgit-maint-merge(7)
#
single-debian-patch
auto-commit
```

Let’s edit **debian/source/local-patch-header**:

### debian/source/local-patch-header for auto-commit

```
$ mv debian/source/local-patch-header.ex debian/source/local-patch-header
$ vim debian/source/local-patch-header
... hack, hack, hack, ...
$ cat debian/source/local-patch-header
Description: debian-changes
Author: Osamu Aoki <osamu@debian.org>
```

Let’s remove **debian/patches/\*** files and other unused template files.

### Remove unused template files

```
$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree debian
debian
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- rules
+-- salsa-ci.yml
```

```
+-- source
|   +-- format
|   +-- local-options
|   +-- local-patch-header
+-- tests
|   +-- control
+-- upstream
|   +-- metadata
+-- watch

4 directories, 13 files
```

There are no **debian/patches/\*** files at the end of this step.

#### Note



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of “Section 5.8”, the **dpkg-source** command uses options specified in **debian/source/local-options** to auto-commit modification applied to the upstream source as **patches/debian-changes**.

Let’s inspect the Debian source package generated after the following “Section 5.8” step and extracting files from **debhello-0.0.debian.tar.xz**.

#### Inspect debhello-0.0.debian.tar.xz after debuild

```
$ tar --xz -xvf debhello_0.0-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/gbp.conf
debian/patches/
debian/patches/debian-changes
debian/patches/series
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/tests/
debian/tests/control
debian/upstream/
debian/upstream/metadata
debian/watch
```

Let’s check generated **debian/patches/\*** files.

#### Inspect debian/patches/\* after debuild

```
$ cat debian/patches/series
debian-changes
$ cat debian/patches/debian-changes
Description: debian-changes
Author: Osamu Aoki <osamu@debian.org>

--- debhello-0.0.orig/Makefile
+++ debhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello
```

The Debian source package **debhello-0.0.debian.tar.xz** is confirmed to be generated properly with **debian/patches/\*** files for the Debian modification.

## Chapter 6

# Basics for packaging

Here, a broad overview is presented without using VCS operations for the basic rules of Debian packaging focusing on the non-native Debian package in the “**3.0 (quilt)**” format.

### Note



Zu Gunsten der Klarheit werden einige Details bewusst übergangen. Bitte lesen Sie die Handbuchseiten von **dpkg-source(1)**, **dpkg-buildpackage(1)**, **dpkg(1)**, **dpkg-deb(1)**, **deb(5)** usw.

Das Debian-Quellpaket ist eine Gruppe von Eingabedateien (d.h. nicht eine einzelne Datei), die zum Bau des Debian-Binärpakets verwandt werden.

Das Debian-Binärpaket ist eine besondere Archivdatei, die die Gruppe der installierbaren Binärdaten mit ihren zugehörigen Informationen enthält.

Ein einzelnes Debian-Quellpaket kann mehrere Debian-Binärpakete, die in der Datei **debian/control** definiert sind, installieren.

The non-native Debian package in the Debian source format “**3.0 (quilt)**” is the most normal Debian source package format.

### Note



There are many wrapper scripts. Use them to streamline your workflow but make sure to understand the basics of their internals.

## 6.1 Arbeitsablauf des Paketierens

The Debian packaging workflow to create a Debian binary package involves generating several specifically named files (see “Section 6.3”) as defined in the “Debian Policy Manual”. This workflow can be summarized in 10 steps with some over simplification as follows.

1. Der Tarball der Originalautoren wird als Datei *Paket-Version.tar.gz* heruntergeladen.
2. The upstream tarball is untarred to create many files under the *package-version/* directory.
3. The upstream tarball is copied (or symlinked) to the particular filename *packagename\_version.orig.tar.gz*.
  - the character separating *package* and *version* is changed from - (hyphen) to \_ (underscore)
  - **.orig** is added in the file extension.
4. The Debian package specification files are added to the upstream source under the *package-version/debian/* directory.

- Required specification files under the **debian/** directory:
    - debian/rules** Das ausführbare Skript zum Bau des Debian-Pakets (siehe “Section 6.5”)
    - debian/control** The package configuration file containing the source package name, the source build dependencies, the binary package name, the binary dependencies, etc. (see “Section 6.6”)
    - debian/changelog** The Debian package history file defining the upstream package version and the Debian revision in its first line (see “Section 6.7”)
    - debian/copyright** The copyright and license summary (see “Section 6.8”)
  - Optional specification files under the **debian/\*** (see “Section 6.14”):
  - The **debmake** command invoked in the *package-version/* directory may be used to provide the initial template of these configuration files.
    - Required specification files are generated even with the **-x0** option.
    - The **debmake** command does not overwrite any existing configuration files.
  - These files must be manually edited to their perfection according to the “[Debian Policy Manual](#)” and “[Debian Developer’s Reference](#)”.
5. The **dpkg-buildpackage** command (usually from its wrapper **debuild** or **sbuild**) is invoked in the *package-version/* directory to make the Debian source and binary packages by invoking the **debian/rules** script.
    - The current directory is set as: “**CURDIR=/path/to/package-version/**”
    - Create the Debian source package in the Debian source format “**3.0 (quilt)**” using **dpkg-source(1)**
      - *package\_version.orig.tar.gz* (copy or symlink of *package-version.tar.gz*)
      - *package\_version-revision.debian.tar.xz* (tarball of **debian/** found in *package-version/*)
      - *package\_version-revision.dsc*
    - Build the source using “**debian/rules build**” into **\$(DESTDIR)**
      - “**DESTDIR=debian/binarypackage/**” for single binary package <sup>1</sup>
      - “**DESTDIR=debian/tmp/**” for multi binary package
    - Create the Debian binary package using **dpkg-deb(1)**, **dpkg-genbuildinfo(1)**, and **dpkg-genchanges(1)**.
      - *binarypackage\_version-revision\_arch.deb*
      - ... (There may be multiple Debian binary package files.)
      - *package\_version-revision\_arch.changes*
      - *package\_version-revision\_arch.buildinfo*
  6. Check the quality of the Debian package with the **lintian** command. (recommended)
    - Follow the rejection guidelines from [ftp-master](#).
      - “[REJECT-FAQ](#)”
      - “[NEW-Checkliste](#)”
      - “[Lintian Autorejects](#)” (“[lintian tag list](#)”)
  7. Test the goodness of the generated Debian binary package manually by installing it and running its programs.
  8. After confirming the goodness, prepare files for the normal source-only upload to the Debian archive.
  9. Sign the Debian package file with the **debsign** command using your private GPG key.
    - Use “**debsign package\_version-revision\_source.changes**” (normal source-only upload situation)
    - Use “**debsign package\_version-revision\_arch.changes**” (exceptional binary upload situation such as NEW uploads, and security uploads) files for the binary Debian package upload.
  10. Upload the set of the Debian package files with the **dput** command to the Debian archive.
    - Use “**dput package\_version-revision\_source.changes**” (source-only upload)
    - Use “**dput package\_version-revision\_arch.changes**” (binary upload)

---

<sup>1</sup>This is the default up to **debhelper** v13. At **debhelper** v14, it warns the default change. After **debhelper** v15, it will change the default to **DESTDIR=debian/tmp/**.

Test building and confirming of the binary package goodness as above is the moral obligation as a diligent Debian developer but there is no physical barrier for people to skip such operations at this moment for the source-only upload.

Here, please replace each part of the filename as:

- the *package* part with the Debian source package name
- the *binarypackage* part with the Debian binary package name
- the *version* part with the upstream version
- the *revision* part with the Debian revision
- the *arch* part with the package architecture (e.g., **amd64**)

See also “[Source-only uploads](#)”.

#### Tip



Many patch management and VCS usage strategies for the Debian packaging are practiced. You don't need to use all of them.

#### Tip



There is very extensive documentation in “[Chapter 6. Best Packaging Practices](#)” in the “Debian Developer's Reference”. Please read it.

## 6.2 debhelper package

Although a Debian package can be made by writing a **debian/rules** script without using the **debhelper** package, it is impractical to do so. There are too many modern “[Debian Policy](#)” required features to be addressed, such as application of the proper file permissions, use of the proper architecture dependent library installation path, insertion of the installation hook scripts, generation of the debug symbol package, generation of package dependency information, generation of the package information files, application of the proper timestamp for reproducible build, etc.

**Debhelper** package provides a set of useful scripts in order to simplify Debian's packaging workflow and reduce the burden of package maintainers. When properly used, they will help packagers handle and implement “[Debian Policy](#)” required features automatically.

The modern Debian packaging workflow can be organized into a simple modular workflow by:

- using the **dh** command to invoke many utility scripts automatically from the **debhelper** package, and
- configuring their behavior with declarative configuration files in the **debian/** directory.

You should almost always use **debhelper** as your package's build dependency. This document also assumes that you are using a fairly contemporary version of **debhelper** to handle packaging works in the following contents.

#### Note



For **debhelper** “compat  $\geq 9$ ”, the **dh** command exports compiler flags (**CFLAGS**, **CXXFLAGS**, **FFLAGS**, **CPPFLAGS** and **LDFLAGS**) with values as returned by **dpkg-buildflags** if they are not set previously. (The **dh** command calls **set\_buildflags** defined in the **Debian::Debhelper::Dh\_Lib** module.)

## Note



**debhelper(1)** changes its behavior with time. Please make sure to read **debhelper-compat-upgrade-checklist(7)** to understand the situation.

## 6.3 Paketname und -version

Falls die Quellen der Originalautoren als **hello-0.9.12.tar.gz** vorliegen, können Sie **hello** als Namen des Quellpakets der Originalautoren und **0.9.12** als Version der Originalautoren nehmen.

There are some limitations for what characters may be used as a part of the Debian package. The most notable limitation is the prohibition of uppercase letters in the package name. Here is a summary as a set of regular expressions:

- Upstream package name (**-p**): `[ -+ . a - z 0 - 9 ] { 2 , }`
- Binary package name (**-b**): `[ -+ . a - z 0 - 9 ] { 2 , }`
- Upstream version (**-u**): `[ 0 - 9 ] [ -+ . : ~ a - z 0 - 9 A - Z ] *`
- Debian revision (**-r**): `[ 0 - 9 ] [ + . ~ a - z 0 - 9 A - Z ] *`

See the exact definition in “[Chapter 5 - Control files and their fields](#)” in the “Debian Policy Manual”.

You must adjust the package name and upstream version accordingly for the Debian packaging.

In order to manage the package name and version information effectively under popular tools such as the **aptitude** command, it is a good idea to keep the length of package name to be equal or less than 30 characters; and the total length of version and revision to be equal or less than 14 characters. <sup>2</sup>

In order to avoid name collisions, the user visible binary package name should not be chosen from any generic words.

If upstream does not use a normal versioning scheme such as **2.30.32** but uses some kind of date such as **11Apr29**, a random codename string, or a VCS hash value as part of the version, make sure to remove them from the upstream version. Such information can be recorded in the **debian/changelog** file. If you need to invent a version string, use the **YYYYMMDD** format such as **20110429** as upstream version. This ensures that the **dpkg** command interprets later versions correctly as upgrades. If you need to ensure a smooth transition to a normal version scheme such as **0.1** in the future, use the **0~YYYYMMDD** format such as **0~110429** as upstream version, instead.

Version strings can be compared using the **dpkg** command as follows.

```
$ dpkg --compare-versions ver1 op ver2
```

The version comparison rule can be summarized as:

- Strings are compared from the head to the tail.
- Letters are larger than digits.
- Numbers are compared as integers.
- Letters are compared in ASCII code order.

There are special rules for period (.), plus (+), and tilde (~) characters, as follows.

```
0.0 < 0.5 < 0.10 < 0.99 < 1 < 1.0~rc1 < 1.0 < 1.0+b1 < 1.0+nm1 < 1.1 < 2.0
```

One tricky case occurs when the upstream releases **hello-0.9.12-ReleaseCandidate-99.tar.gz** as the pre-release of **hello-0.9.12.tar.gz**. You can ensure the Debian package upgrade to work properly by renaming the upstream source to **hello-0.9.12~rc99.tar.gz**.

<sup>2</sup>For more than 90% of packages, the package name is equal or less than 24 characters; the upstream version is equal or less than 10 characters and the Debian revision is equal or less than 3 characters.

## 6.4 Natives Debian-Paket

The non-native Debian package in the Debian source format “**3.0 (quilt)**” is the most normal Debian source package format. The **debian/source/format** file should have “**3.0 (quilt)**” in it as described in **dpkg-source(1)**. The above workflow and the following packaging examples always use this format.

A native Debian package is the rare Debian binary package format. It may be used only when the package is useful and valuable only for Debian. Thus, its use is generally discouraged.

### Caution



A native Debian package is often accidentally built when its upstream tarball is not accessible from the **dpkg-buildpackage** command with its correct name *package\_version.orig.tar.gz*. This is a typical newbie mistake caused by making a symlink name with “-” instead of the correct one with “\_”.

A native Debian package has no separation between the **upstream code** and the **Debian changes** and consists only of the following:

- *package\_version.tar.gz* (copy or symlink of *package-version.tar.gz* with **debian/\*** files.)
- *package\_version.dsc*

If you need to create a native Debian package, create it in the Debian source format “**3.0 (native)**” using **dpkg-source(1)**.

### Tip



There is no need to create the tarball in advance if the native Debian package format is used. The **debian/source/format** file should have “**3.0 (native)**” in it as described in **dpkg-source(1)** and The **debian/source/format** file should have the version without the Debian revision (**1.0** instead of **1.0-1**). Then, the tarball containing is generated when “**dpkg-source -b**” is invoked in the source tree.

## 6.5 debian/rules file

The **debian/rules** file is the executable script which re-targets the upstream build system to install files in the **\$(DESTDIR)** and creates the archive file of the generated files as the **deb** file. The **deb** file is used for the binary distribution and installed to the system using the **dpkg** command.

The Debian policy compliant **debian/rules** file supporting all the required targets can be written as simple as 3:

**Simple debian/rules:**

```
#!/usr/bin/make -f
#export DH_VERBOSE = 1

%:
dh $@
```

The **dh** command functions as the sequencer to call all required “**dh target**” commands at the right moment. <sup>4</sup>

- **dh clean**: bereinigt Dateien in dem Quellbaum.
- **dh build**: build the source tree
- **dh build-arch**: build the source tree for architecture dependent packages
- **dh build-indep**: build the source tree for architecture independent packages

<sup>3</sup>The **debmake** command generates a bit more complicated **debian/rules** file. But this is the core part.

<sup>4</sup>This simplicity is available since version 7 of the **debhelper** package. This guide assumes the use of **debhelper** version 13 or newer.



- **dh install** : install the binary files to **\$(DESTDIR)**
- **dh install-arch** : install the binary files to **\$(DESTDIR)** for architecture dependent packages
- **dh install-indep** : install the binary files to **\$(DESTDIR)** for architecture independent packages
- **dh binary** : generate the **deb** file
- **dh binary-arch** : generate the **deb** file for architecture dependent packages
- **dh binary-indep** : generate the **deb** file for architecture independent packages

Here, **\$(DESTDIR)** path depends on the build type.

- “**DESTDIR=debian/binarypackage/**” for single binary package <sup>5</sup>
- “**DESTDIR=debian/tmp/**” for multi binary package

See “Section 8.2” and “Section 8.3” for customization.

#### Tip



Setting “**export DH\_VERBOSE = 1**” outputs every command that modifies files on the build system. Also it enables verbose build logs for some build systems.

## 6.6 debian/control file

Die Datei **debian/control** besteht aus Metadatenblöcken, die durch Leerzeilen getrennt sind. Jeder Metadatenblock definiert folgendes in dieser Reihenfolge:

- Metadaten für das Debian-Quellpaket
- Metadaten für das Debian-Binärpaket

See “Chapter 5 - Control files and their fields” of the “Debian Policy Manual” for the definition of each meta data.

#### Note



The **debmake** command sets the **debian/control** file with “**Build-Depends: debhelper-compat (= 13)**” to set the **debhelper** compatibility level.

#### Tip



If an existing package has lower than **debhelper** compatibility level 13, probably it's time to update its packaging.

<sup>5</sup>This is the default up to **debhelper** v13. At **debhelper** v14, it warns the default change. After **debhelper** v15, it will change the default to **DESTDIR=debian/tmp/**.

## 6.7 debian/changelog file

The **debian/changelog** file records the Debian package history.

- This should be edited using the **debchange** command (alias **dch**).
- This defines the upstream package version and the Debian revision in its first line.
- The changes need to be documented in the specific, formal, and concise style.
  - If Debian maintainer modification fixes reported bugs, add “**Closes:** #<bug\_number>” to close those bugs.
- Even if you are uploading your package by yourself, you must document all non-trivial user-visible changes such as:
  - sicherheitsrelevante Änderungen
  - Änderungen in der Benutzerschnittstelle
- If you are asking your sponsor to upload it, you should document changes more comprehensively, including all packaging related ones, to help reviewing your package.
  - The sponsor shouldn’t be forced to second guess your thought behind your package.
  - Die Zeit des Sponsorers ist wertvoller als Ihre.

After finishing your packaging and verifying its quality, please execute the “**dch -r**” command and save the finalized **debian/changelog** file with the suite normally set to **unstable**.<sup>6</sup> If you are packaging for backports, security updates, LTS, etc., please use the appropriate distribution names instead.

The **debmake** command creates the initial template file with the upstream package version and the Debian revision. The distribution is set to **UNRELEASED** to prevent accidental upload to the Debian archive.

### Tip



The date string used in the **debian/changelog** file can be manually generated by the “**LC\_ALL=C date -R**” command.

### Tip



Use a **debian/changelog** entry with a version string such as **1.0.1-1~rc1** when you experiment. Then, unclutter such **changelog** entries into a single entry for the official package.

The **debian/changelog** file is installed in the **/usr/share/doc/binarypackage** directory as **changelog.Debian.gz** by the **dh\_installchangelogs** command.

Der Changelog der Originalautoren wird als **changelog.gz** in das Verzeichnis **/usr/share/doc/Binärpaket** installiert.

The upstream changelog is automatically found by the **dh\_installchangelogs** using the case insensitive match of its file name to **changelog**, **changes**, **changelog.txt**, **changes.txt**, **history**, **history.txt**, or **changelog.md** and searched in the **./ doc/** or **docs/** directories.

## 6.8 debian/copyright file

Debian takes the copyright and license matters very seriously. The “Debian Policy Manual” enforces having a summary of them in the **debian/copyright** file in the package.

<sup>6</sup>If you are using the **vim** editor, make sure to save this with the “**:wq**” command.

- “[12.5. Copyright information](#)”
- “[2.3. Copyright considerations](#)”
- “[License information](#)”

The **debmake** command creates the initial **debian/copyright** template file.

- Please double check copyright with the **licensecheck(1)** command.
- Please format it as a “[machine-readable debian/copyright file \(DEP-5\)](#)”.

Unless specifically requested to be pedantic with the **-P** option, the **debmake** command skips reporting for auto-generated files with permissive licenses to be practical.

#### Caution



Die Datei **debian/copyright** sollte sortiert sein, um die generischen Dateimuster am Anfang der Liste zu behalten. Siehe “[Section 15.6](#)”.

#### Note



Falls Sie Probleme mit diesem Lizenzprüfer feststellen, reichen Sie bitten gegen das Paket **debmake** einen Fehlerbericht mit dem problematischen Teil des Textes, der das Copyright und die Lizenz enthält, ein.

## 6.9 debian/patches/\* files

As demonstrated in “[Section 5.9](#)”, the **debian/patches/** directory holds

- *patch-file-name.patch* files providing **-p1** patches and
- the **series** file which defines how these patches are applied.

See how these files are used in:

- “[Section 12.6](#)” to build the Debian source package
- “[Section 12.7](#)” to extract source files from the Debian source package

#### Note



Header texts of these patches should conform to “[DEP-3](#)”.

#### Note



If you want to use VCS tools such as **git**, **gbp** and **dggit** to create and manage these patches after learning basics here, please refer to later in “[Chapter 10](#)”.

## 6.10 debian/source/include-binaries file

The “**dpkg-source --commit**” command functions like **dquilt** but has one advantage over the **dquilt** command. While the **dquilt** command can’t handle modified binary files, the “**dpkg-source --commit**” command detects modified binary files and lists them in the **debian/source/include-binaries** file to include them in the Debian tarball as a part of the Debian source package.

## 6.11 debian/watch file

The **uscan(1)** command downloads the latest upstream version using the **debian/watch** file. E.g.:

**Basic debian/watch file:**

```
version=4
https://ftp.gnu.org/gnu/hello/ @PACKAGE@@ANY_VERSION@@ARCHIVE_EXT@
```

The **uscan** command may verify the authenticity of the upstream tarball with optional configuration (see “Section 6.12”).

See **uscan(1)**, “Section 8.4”, “Section 7.1”, and “Section 10.10” for more.

## 6.12 debian/upstream/signing-key.asc file

Some packages are signed by a GPG key and their authenticity can be verified using their public GPG key.

For example, “GNU hello” can be downloaded via HTTP from <https://ftp.gnu.org/gnu/hello/>. There are sets of files:

- **hello-version.tar.gz** (upstream source)
- **hello-version.tar.gz.sig** (detached signature)

Let’s pick the latest version set.

**Download the upstream tarball and its signature.**

```
$ wget https://ftp.gnu.org/gnu/hello/hello-2.9.tar.gz
...
$ wget https://ftp.gnu.org/gnu/hello/hello-2.9.tar.gz.sig
...
$ gpg --verify hello-2.9.tar.gz.sig
gpg: Signature made Thu 10 Oct 2013 08:49:23 AM JST using DSA key ID 80EE4A00
gpg: Can't check signature: public key not found
```

If you know the public GPG key of the upstream maintainer from the mailing list, use it as the **debian/upstream/signing-key.asc** file. Otherwise, use the hkp keyserver and check it via your [web of trust](#).

**Download public GPG key for the upstream**

```
$ gpg --keyserver hkp://keys.gnupg.net --recv-key 80EE4A00
gpg: requesting key 80EE4A00 from hkp server keys.gnupg.net
gpg: key 80EE4A00: public key "Reuben Thomas <rtr@sc3d.org>" imported
gpg: no ultimately trusted keys found
gpg: Total number processed: 1
gpg:             imported: 1
$ gpg --verify hello-2.9.tar.gz.sig
gpg: Signature made Thu 10 Oct 2013 08:49:23 AM JST using DSA key ID 80EE4A00
gpg: Good signature from "Reuben Thomas <rtr@sc3d.org>"
...
Primary key fingerprint: 9297 8852 A62F A5E2 85B2 A174 6808 9F73 80EE 4A00
```

### Tip



If your network environment blocks access to the HKP port **11371**, use “**hkp://keyserver.ubuntu.com:80**” instead.

After confirming the key ID **80EE4A00** is a trustworthy one, download its public key into the **debian/upstream/signing-key.asc** file.

**Set public GPG key to debian/upstream/signing-key.asc**

```
$ gpg --armor --export 80EE4A00 >debian/upstream/signing-key.asc
```

With the above **debian/upstream/signing-key.asc** file and the following **debian/watch** file, the **uscan** command can verify the authenticity of the upstream tarball after its download. E.g.:

**Improved debian/watch file with GPG support:**

```
version=4
opts="pgpsigurlmangle=s/${.sig/" \
https://ftp.gnu.org/gnu/hello/ @PACKAGE@@ANY_VERSION@@ARCHIVE_EXT@
```

## 6.13 debian/salsa-ci.yml file

Install [Salsa CI](#) configuration file. See “Section 10.3”.

## 6.14 Other debian/\* files

Optional configuration files may be added under the **debian/** directory. Most of them are to control **dh\_\*** commands offered by the **debhelper** package but there are some for **dpkg-source**, **lintian** and **gbp** commands.

### Tip



Even an upstream source without its build system can be packaged just by using these files. See “Section 13.2” as an example.

The alphabetical list of notable optional **debian/binarypackage.\*** configuration files listed below provides very powerful means to set the installation path of files. Please note:

- The “-x[01234]” superscript notation that appears in the following list indicates the minimum value for the **debmake -x** option that generates the associated template file. See “Section 15.9” or **debmake(1)** for details.
- For a single binary package, the “*binarypackage.*” part of the filename in the list may be removed.
- For a multi binary package, a configuration file missing the “*binarypackage*” part of the filename is applied to the first binary package listed in the **debian/control**.
- When there are many binary packages, their configurations can be specified independently by prefixing their name to their configuration filenames such as “*package-1.install*”, “*package-2.install*”, etc.
- Some template configuration files may not be created by the **debmake** command. In such cases, you need to create them with an editor.
- Some configuration template files generated by the **debmake** command with an extra **.ex** suffix need to be activated by removing that suffix.
- Nicht verwendete Vorlagendateien, die durch den Befehl **debmake** erstellt wurden, sollten entfernt werden.
- Kopieren Sie die Konfigurationsvorlagendateien wie benötigt nach den Dateinamen, die ihren Programm-paketnamen entsprechen.

**Binärpaket.bug-control**<sup>-x3</sup> installed as **usr/share/bug/binarypackage/control** in *binarypackage*. See “Section 8.11”.

**Binärpaket.bug-presubj**<sup>-x3</sup> installed as **usr/share/bug/binarypackage/presubj** in *binarypackage*. See “Section 8.11”.

**Binärpaket.bug-script**<sup>-x3</sup> installed as **usr/share/bug/binarypackage** or **usr/share/bug/binarypackage/script** in *binarypackage*. See “Section 8.11”.

**binarypackage.bash-completion** <sup>-x3</sup> List **bash** completion scripts to be installed.

The **bash-completion** package is required for both build and user environments.

Siehe **dh\_bash-completion**(1).

**clean** <sup>-x2</sup> List files that should be removed but are not cleaned by the **dh\_auto\_clean** command.

Siehe **dh\_auto\_clean**(1) und **dh\_clean**(1).

**compat** <sup>-x4</sup> Set the **debhelper** compatibility level. (deprecated)

Use “**Build-Depends: debhelper-compat (= 13)**” in **debian/control** to specify the compatibility level and remove **debian/compat**.

See “**COMPATIBILITY LEVELS**” in **debhelper**(7).

**binarypackage.conf** <sup>-x3</sup> This optional file is installed into the **DEBIAN** directory within the binary package while supplementing it with all the conffiles auto-detected by **debhelper**.

This file is primarily useful for using “special” entries such as the remove-on-upgrade feature from **dpkg**(1).

If the program you’re packaging requires every user to modify the configuration files in the **/etc** directory, there are two popular ways to arrange for them not to be conffiles, keeping the **dpkg** command happy and quiet.

- Create a symlink under the **/etc** directory pointing to a file under the **/var** directory generated by the maintainer scripts.
- Create a file generated by the maintainer scripts under the **/etc** directory.

Siehe **dh\_installdeb**(1).

**binarypackage.config** <sup>-x3</sup> This is the **debconf config** script used for asking any questions necessary to configure the package. See “Section 9.22”.

**Binärpaket.cron.hourly** <sup>-x3</sup> Installed into the **etc/cron/hourly/binarypackage** file in *binarypackage*.

Siehe **dh\_installcron**(1) und **cron**(8).

**Binärpaket.cron.daily** <sup>-x3</sup> Installed into the **etc/cron/daily/binarypackage** file in *binarypackage*.

Siehe **dh\_installcron**(1) und **cron**(8).

**Binärpaket.cron.weekly** <sup>-x3</sup> Installed into the **etc/cron/weekly/binarypackage** file in *binarypackage*.

Siehe **dh\_installcron**(1) und **cron**(8).

**Binärpaket.cron.monthly** <sup>-x3</sup> Installed into the **\*etc/cron/monthly/\*binarypackage** file in *binarypackage*.

Siehe **dh\_installcron**(1) und **cron**(8).

**Binärpaket.cron.d** <sup>-x3</sup> Installed into the **etc/cron.d/binarypackage** file in *binarypackage*.

Siehe **dh\_installcron**(1), **cron**(8) und **crontab**(5).

**Binärpaket.default** <sup>-x3</sup> If this exists, it is installed into **etc/default/binarypackage** in *binarypackage*.

Siehe **dh\_installinit**(1).

**binarypackage.dirs** <sup>-x1</sup> List directories to be created in *binarypackage*.

Siehe **dh\_installdirs**(1).

Usually, this is not needed since all **dh\_install\*** commands create required directories automatically. Use this only when you run into trouble.

**binarypackage.doc-base** <sup>-x1</sup> Installed as the **doc-base** control file in *binarypackage*.

See **dh\_installdocs**(1) and “[Debian doc-base Manual \(doc-base.html\)](#)” provided by the **doc-base** package.

**binarypackage.docs** <sup>-x1</sup> List documentation files to be installed in *binarypackage*.

Siehe **dh\_installdocs**(1).

**Binärpaket.emacsen-compat** <sup>-x3</sup> Installed into **usr/lib/emacsen-common/packages/compat/binarypackage** in *binarypackage*.

Siehe **dh\_installemacsen**(1).

**Binärpaket.emacsen-install** <sup>-x3</sup> Installed into **usr/lib/emacsen-common/packages/install/binarypackage** in *binarypackage*.

Siehe **dh\_installemacsen**(1).

- Binärpaket.emacsen-remove** <sup>-x3</sup> Installed into **usr/lib/emacsen-common/packages/remove/binarypackage** in *binarypackage*.  
Siehe **dh\_installemacsen(1)**.
- Binärpaket.emacsen-startup** <sup>-x3</sup> Installed into **usr/lib/emacsen-common/packages/startup/binarypackage** in *binarypackage*.  
Siehe **dh\_installemacsen(1)**.
- binarypackage.examples** <sup>-x1</sup> List example files or directories to be installed into **usr/share/doc/binarypackage/examples/** in *binarypackage*.  
Siehe **dh\_installexamples(1)**.
- gbp.conf** <sup>-x1</sup> Falls diese existiert, funktioniert sie als Konfigurationsdatei für den Befehl **gbp**.  
Siehe **gbp.conf(5)**, **gbp(1)** und **git-buildpackage(1)**.
- binarypackage.info** <sup>-x1</sup> Führt Info-Dateien auf, die in *Binärpaket* installiert werden.  
Siehe **dh\_installinfo(1)**.
- binarypackage.init** <sup>-x4</sup> Installed into **etc/init.d/binarypackage** in *binarypackage*. (deprecated)  
Siehe **dh\_installinit(1)**.
- binarypackage.install** <sup>-x1</sup> Liste der Dateien, die installiert werden sollten, aber nicht durch den Befehl **dh\_auto\_install** installiert wurden.  
Siehe **dh\_install(1)** und **dh\_auto\_install(1)**.
- binarypackage.links** <sup>-x1</sup> List pairs of source and destination files to be symlinked. Each pair should be put on its own line, with the source and destination separated by whitespace.  
Siehe **dh\_link(1)**.
- Binärpaket.lintian-overrides** <sup>-x3</sup> Installed into **usr/share/lintian/overrides/binarypackage** in the package build directory. This file is used to suppress erroneous **lintian** diagnostics.  
Siehe **dh\_lintian(1)**, **lintian(1)** und "[Lintian User's Manual](#)".
- binarypackage.maintscript** <sup>-x2</sup> If this optional file exists, **debhelper** uses this as the template to generate **DEBIAN/binarypackage.{pre,post}{inst,rm}** files within the binary package while adding "--" "\$@" to the **dpkg-maintscript-helper(1)** command.  
See **dh\_installdeb(1)** and "[Chapter 6 - Package maintainer scripts and installation procedure](#)" in the "Debian Policy Manual".
- manpage.\*** <sup>-x3</sup> These are manpage template files generated by the **debmake** command. Please rename these to appropriate file names and update their contents.  
Debian Policy requires that each program, utility, and function should have an associated manual page included in the same package. Manual pages are written in **nroff(1)**. If you are new to making a manpage, use **manpage.asciidoc** or **manpage.1** as the starting point.
- binarypackage.manpages** <sup>-x1</sup> List man pages to be installed.  
Siehe **dh\_installman(1)**.
- Binärpaket.menu** (veraltet, nicht mehr installiert) [tech-ctte #741573](#) decided "Debian should use **.desktop** files as appropriate".  
Debian menu file installed into **usr/share/menu/binarypackage** in *binarypackage*.  
See **menufile(5)** for its format. See **dh\_installmenu(1)**.
- NEWS** <sup>-x3</sup> Installed into **usr/share/doc/binarypackage/NEWS.Debian**.  
Siehe **dh\_installchangelogs(1)**.
- patches/\*** Collection of **-p1** patch files which are applied to the upstream source before building the source.  
No patch files are generated by the **debmake** command.  
Siehe **dpkg-source(1)**, "Section 4.4" und "Section 5.9".
- patches/series** <sup>-x1</sup> The application sequence of the **patches/\*** patch files.
- Binärpaket.preinst** <sup>-x2</sup>, **Binärpaket.postinst** <sup>-x2</sup>, **Binärpaket.prerm** <sup>-x2</sup>, **Binärpaket.postrm** <sup>-x2</sup> If these optional files exist, the corresponding files are installed into the **DEBIAN** directory within the binary package after enriched by **debhelper**. Otherwise, these files in the **DEBIAN** directory within the binary package is generated by **debhelper**.  
Whenever possible, simpler *binarypackage.maintscript* should be used instead.



See **dh\_installdeb**(1) and “Chapter 6 - Package maintainer scripts and installation procedure” in the “Debian Policy Manual”.

See also **debconf-devel**(7) and “3.9.1 Prompting in maintainer scripts” in the “Debian Policy Manual”.

**README.Debian** <sup>-x1</sup> Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/README.Debian**.

This file provides the information specific to the Debian package.

Siehe **dh\_installdocs**(1).

**README.source** <sup>-x1</sup> Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/README.source**.

If running “**dpkg-source -x**” on a source package doesn’t produce the source of the package, ready for editing, and allow one to make changes and run **dpkg-buildpackage** to produce a modified package without taking any additional steps, creating this file is recommended.

See “Debian policy manual section 4.14”.

**binarypackage.service** <sup>-x3</sup> If this exists, it is installed into **lib/systemd/system/binarypackage.service** in *binarypackage*.

Siehe **dh\_systemd\_enable**(1), **dh\_systemd\_start**(1) und **dh\_installinit**(1).

**source/format** <sup>-x1</sup> The Debian package format.

- Use “**3.0 (quilt)**” to make this non-native package (recommended)
- Use “**3.0 (native)**” to make this native package

See “SOURCE PACKAGE FORMATS” in **dpkg-source**(1).

**source/lintian-overrides** <sup>-x3</sup> These file is not installed, but are scanned by the **lintian** command to provide overrides for the source package.

Siehe **dh\_lintian**(1) und **lintian**(1).

**source/local-options** <sup>-x1</sup> The **dpkg-source** command uses this content as its options. Notable options are:

- **unapply-patches**
- **abort-on-upstream-changes**
- **auto-commit**
- **single-debian-patch**

This is not included in the generated source package and is meant to be committed to the VCS of the maintainer.

See “FILE FORMATS” in **dpkg-source**(1).

**source/local-patch-header** <sup>-x1</sup> Free form text that is put on top of the automatic patch generated.

This is not included in the generated source package and is meant to be committed to the VCS of the maintainer.

See “FILE FORMATS” in **dpkg-source**(1).

**source/options** <sup>-x3</sup> Use **source/local-options** instead to avoid issues with NMUs. See “FILE FORMATS” in **dpkg-source**(1).

**source/patch-header** <sup>-x4</sup> Use **source/local-patch-header** instead to avoid issues with NMUs. See “FILE FORMATS” in **dpkg-source**(1).

**binarypackage.symbols** <sup>-x1</sup> The symbols files, if present, are passed to the **dpkg-gensymbols** command to be processed and installed.

Siehe **dh\_makeshlibs**(1) und “Section 9.16”..

**binarypackage.templates** <sup>-x3</sup> This is the **debconf templates** file used for asking any questions necessary to configure the package. See “Section 9.22”.

**tests/control** <sup>-x1</sup> This is the RFC822-style test meta data file defined in [DEP-8](#). See **autopkgtest**(1) and “Section 9.4”.

**TODO** <sup>-x3</sup> Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/TODO.D**.

Siehe **dh\_installdocs**(1).

**Binärpaket.tmpfile** <sup>-x3</sup> If this exists, it is installed into **usr/lib/tmpfiles.d/binarypackage.conf** in *binarypackage*.

Siehe **dh\_systemd\_enable**(1), **dh\_systemd\_start**(1) und **dh\_installinit**(1).



**binarypackage.upstart** <sup>-x4</sup> If this exists, it is installed into **etc/init/package.conf** in the package build directory. (deprecated)

Siehe **dh\_installinit**(1).

**upstream/metadata** <sup>-x1</sup> Per-package machine-readable metadata about upstream ([DEP-12](#)). See “[Upstream Metadata Gathered with YAml \(UMEGAYA\)](#)”.

## Chapter 7

# Sanitization of the source

There are a few cases which require to sanitize the source to prevent contaminating the generated Debian source package.

- Non [DFSG](#) contents in the upstream source.
  - Debian takes software freedom seriously and follows the [DFSG](#).
- Extraneous auto-generated contents in the upstream source.
  - Debian package should rebuild them under the latest system.
- Extraneous VCS contents in the upstream source.
  - The **-i** and **-I** options set in “Section [4.5](#)” for the **dpkg-source(1)** command should avoid these.
    - \* The **-i** option is aimed at the non-native Debian package.
    - \* The **-I** is aimed at the native Debian package.

Es gibt mehrere Methoden, die Aufnahme ungewünschter Inhalte zu vermeiden

### 7.1 Fix with Files-Excluded

This is suitable for avoiding non [DFSG](#) contents in the upstream source tarball.

- List the files to be removed in the **Files-Excluded** stanza of the **debian/copyright** file.
- List the URL to download the upstream tarball in the **debian/watch** file.
- Führen Sie den Befehl **uscan** aus, um einen neuen Tarball der Originalautoren herunterzuladen.
  - Alternatively, use the “**gbp import-orig --uscan --pristine-tar**” command.
- **mk-origtargz** invoked from **uscan** removes excluded files from the upstream tarball and repack it as a clean tarball.
- Der resultierende Tarball hat die Versionsnummer mit einer zusätzlichen Endung **+dfsg**.

See “**COPYRIGHT FILE EXAMPLES**” in **mk-origtargz(1)**.

### 7.2 Fix with “debian/rules clean”

This is suitable for avoiding auto-generated files and removes them in the “**debian/rules clean**” target

#### Note



The “**debian/rules clean**” target is called before the “**dpkg-source --build**” command by the **dpkg-buildpackage** command and the “**dpkg-source --build**” command ignores removed files.

## 7.3 Fix with extend-diff-ignore

This is for the non-native Debian package.

The problem of extraneous diffs can be fixed by ignoring changes made to parts of the source tree by adding the “**extend-diff-ignore=...**” line in the **debian/source/options** file.

**debian/source/options to exclude the config.sub, config.guess and Makefile files:**

```
# Don't store changes on autogenerated files
extend-diff-ignore = "(^|/)(config\.sub|config\.guess|Makefile)$"
```

### Note



This approach always works, even when you can't remove the file. So it saves you having to make a backup of the unmodified file just to be able to restore it before the next build.

### Tip



If the **debian/source/local-options** file is used instead, you can hide this setting from the generated source package. This may be useful when the local non-standard VCS files interfere with your packaging.

## 7.4 Fix with tar-ignore

This is for the native Debian package.

You can exclude some files in the source tree from the generated tarball by tweaking the file glob by adding the “**tar-ignore=...**” lines in the **debian/source/options** or **debian/source/local-options** files.

### Note



If, for example, the source package of a native package needs files with the file extension **.o** as a part of the test data, the setting in “Section 4.5” is too aggressive. You can work around this problem by dropping the **-I** option for **DEB\_BUILD\_DPKG\_BUILDPACKAGE\_OPTS** in “Section 4.5” while adding the “**tar-ignore=...**” lines in the **debian/source/local-options** file for each package.

## 7.5 Fix with “git clean -dfx”

The problem of extraneous contents in the second build can be avoided by restoring the source tree by committing the source tree to the Git repository before the first build.

You can restore the source tree before the second package build. For example:

```
$ git reset --hard
$ git clean -dfx
```

This works because the **dpkg-source** command ignores the contents of the typical VCS files in the source tree with the **DEB\_BUILD\_DPKG\_BUILDPACKAGE\_OPTS** setting in “Section 4.5”.

**Tip**

If the source tree is not managed by a VCS, you should run “**git init; git add -A .; git commit**” before the first build.

## Chapter 8

# More on packaging

Let's describe more basics on Debian packaging.

### 8.1 Package customization

All customization data for the Debian source package resides in the **debian/** directory as presented in “Section 5.7”:

- The Debian package build system can be customized through the **debian/rules** file (see “Section 8.2”).
- The Debian package installation path etc. can be customized through the addition of configuration files such as *package.install* and *package.docs* in the **debian/** directory for the **dh\_\*** commands from the **debhelper** package (see “Section 6.14”).

When these are not sufficient to make a good Debian package, **-p1** patches of **debian/patches/\*** files are deployed to modify the upstream source. These are applied in the sequence defined in the **debian/patches/series** file before building the package as presented in “Section 5.9”.

You should address the root cause of the Debian packaging problem by the least invasive way. The generated package shall be more robust for future upgrades in this way.

#### Note



Schicken Sie den Patch, der das eigentliche Problem adressiert, an die Originalautoren, falls er für die Originalautoren nützlich ist.

### 8.2 Customized debian/rules

Flexible customization of the Section 6.5 is realized by adding appropriate **override\_dh\_\*** targets and their rules.

Whenever some special operation is required for a certain **dh\_foo** command invoked by the **dh** command, any automatic execution of it can be overridden by adding the makefile target **override\_dh\_foo** in the **debian/rules** file.

The build process may be customized via the upstream provided interface such as arguments to the standard source build system commands, such as:

- **configure**,
- **Makefile**,
- “**python -m build**”, or
- **Build.PL**.

If this is the case, you should add the **override\_dh\_auto\_build** target with “**dh\_auto\_build -- arguments**”. This ensures passing *arguments* to the build system after the default parameters that **dh\_auto\_build** usually passes.

**Tip**

Please try not to execute the bare build system commands directly if they are supported by the **dh\_auto\_build** command.

Siehe:

- “Section 5.7” for the basic example.
- “Section 9.3” to be reminded of the challenge involving the underlying build system.
- “Section 9.10” for multiarch customization.
- “Section 9.6” for hardening customization.

## 8.3 Variables for **debian/rules**

Some variable definitions useful for customizing **debian/rules** can be found in files under **/usr/share/dpkg/**. Notably:

**pkg-info.mk** Set **DEB\_SOURCE**, **DEB\_VERSION**, **DEB\_VERSION\_EPOCH\_UPSTREAM**, **DEB\_VERSION\_UPSTREAM**, and **DEB\_DISTRIBUTION** variables obtained from **dpkg-parsechangelog(1)**. (useful for backport support etc..)

**vendor.mk** Set **DEB\_VENDOR** and **DEB\_PARENT\_VENDOR** variables; and **dpkg\_vendor\_derives\_from** macro obtained from **dpkg-vendor(1)**. (useful for vendor support (Debian, Ubuntu, ...).)

**architecture.mk** Set **DEB\_HOST\_\*** and **DEB\_BUILD\_\*** variables obtained from **dpkg-architecture(1)**.

**buildflags.mk** Set **CFLAGS**, **CPPFLAGS**, **CXXFLAGS**, **OBJCFLAGS**, **OBJCXXFLAGS**, **GCJFLAGS**, **FFLAGS**, **FCFLAGS**, and **LDFLAGS** build flags obtained from **dpkg-buildflags(1)**.

Beispielsweise können Sie eine Zusatzoption zu **CONFIGURE\_FLAGS** für die Zielarchitektur **linux-any** durch Hinzufügen von folgendem zur **debian/rules** hinzufügen:

```
DEB_HOST_ARCH_OS ?= $(shell dpkg-architecture -qDEB_HOST_ARCH_OS)
...
ifeq ($(DEB_HOST_ARCH_OS), linux)
CONFIGURE_FLAGS += --enable-wayland
endif
```

Siehe “Section 9.10”, **dpkg-architecture(1)** und **dpkg-buildflags(1)**.

## 8.4 New upstream release

When a new upstream release tarball **foo-newversion.tar.gz** is released, the Debian source package can be updated by invoking commands in the old source tree as:

```
$ uscan
... foo-newversion.tar.gz downloaded
$ uupdate -v newversion ../foo-newversion.tar.gz
```

- The **debian/watch** file in the old source tree must be a valid one.
- This make symlink **../foo\_newversion.orig.tar.gz** pointing to **../foo-newversion.tar.gz**.
- Files are extracted from **../foo-newversion.tar.gz** to **../foo-newversion/**
- Files are copied from **../foo-oldversion/debian/** to **../foo-newversion/debian/**.

After the above, you should refresh **debian/patches/\*** files (see “Section 8.5”) and update **debian/changelog** with the **dch(1)** command.

When “**debian uupdate**” is specified at the end of line in the **debian/watch** file, **uscan** automatically executes **uupdate(1)** after downloading the tarball.

## 8.5 Manage patch queue with **dquilt**

You can add, drop, and refresh **debian/patches/\*** files with **dquilt** to manage patch queue.

- **Add** a new patch **debian/patches/bugname.patch** recording the upstream source modification on the file *buggy\_file* as:

```
$ dquilt push -a
$ dquilt new bugname.patch
$ dquilt add buggy_file
$ vim buggy_file
...
$ dquilt refresh
$ dquilt header -e
$ dquilt pop -a
```

- **Drop** (== disable) an existing patch
  - Comment out pertinent line in **debian/patches/series**
  - Erase the patch itself (optional)
- **Refresh** **debian/patches/\*** files to make “**dpkg-source -b**” work as expected after updating a Debian package to the new upstream release.

```
$ uscan; update # updating to the new upstream release
$ while dquilt push; do dquilt refresh ; done
$ dquilt pop -a
```

- If conflicts are encountered with “**dquilt push**” in the above, resolve them and run “**dquilt refresh**” manually for each of them.

## 8.6 Build commands

Here is a recap of popular low level package build commands. There are many ways to do the same thing.

- **dpkg-buildpackage** = core of package building tool
- **debuild** = **dpkg-buildpackage** + **lintian** (build under the sanitized environment variables)
- **schroot** = core of the Debian chroot environment tool
- **sbuild** = **dpkg-buildpackage** on custom **schroot** (build in the chroot)

## 8.7 Note on **sbuild**

The **sbuild(1)** command is a wrapper script of **dpkg-buildpackage** which builds Debian binary packages in a chroot environment managed by the **schroot(1)** command. For example, building for Debian **unstable** suite can be done as:

```
$ sudo sbuild -d unstable
```

In **schroot(1)** terminology, this builds a Debian package in a clean ephemeral **chroot** “**chroot:unstable-amd64-sbuild**” started as a copy of the clean minimal persistent **chroot** “**source:unstable-amd64-sbuild**”.

This build environment was set up as described in “Section 4.6” with “**sbuild-debian-developer-setup -s unstable**” which essentially did the following:

```
$ sudo mkdir -p /srv/chroot/dist-amd64-sbuild
$ sudo sbuild-createchroot unstable /srv/chroot/unstable-amd64-sbuild http://deb ↵
  .debian.org/debian
$ sudo usermod -a -G sbuild <your_user_name>
$ sudo newgrp -
```

The **schroot(1)** configuration for **unstable-amd64-sbuild** was generated at **/etc/schroot/chroot.d/unstable-amd64-sbuild.\$suffix** :

```
[unstable-amd64-sbuild]
description=Debian sid/amd64 autobuilder
groups=root,sbuild
root-groups=root,sbuild
profile=sbuild
type=directory
directory=/srv/chroot/unstable-amd64-sbuild
union-type=overlay
```

Hier:

- The profile defined in the **/etc/schroot/sbuild/** directory is used to setup the chroot environment.
- **/srv/chroot/unstable-amd64-sbuild** directory holds the chroot filesystem.
- **/etc/sbuild/unstable-amd64-sbuild** is symlinked to **/srv/chroot/unstable-amd64-sbuild** .

You can update this source chroot “**source:unstable-amd64-sbuild**” by:

```
$ sudo sbuild-update -udcar unstable
```

You can log into this source chroot “**source:unstable-amd64-sbuild**” by:

```
$ sudo sbuild-shell unstable
```

#### Tip



If your source chroot filesystem is missing packages such as **libeatmydata1**, **ccache**, and **lintian** for your needs, you may want to install these by logging into it.

## 8.8 Special build cases

The **orig.tar.gz** file may need to be uploaded for a Debian revision other than **0** or **1** under some exceptional cases (e.g., for a security upload).

When an essential package becomes a non-essential one (e.g., **adduser**), you need to remove it manually from the existing chroot environment for its use by **piuparts**.

## 8.9 Upload orig.tar.gz

When you first upload the package to the archive, you need to include the original **orig.tar.gz** source, too.

If the Debian revision number of the package is either **1** or **0**, this is the default. Otherwise, you must provide the **dpkg-buildpackage** option **-sa** to the **dpkg-buildpackage** command.

- **dpkg-buildpackage -sa**
- **debuild -sa**
- **sbuild**
- For “**gbp buildpackage**”, edit the **~/gbp.conf** file.



## Tip



On the other hand, the **-sd** option will force the exclusion of the original **orig.tar.gz** source.

## Tip



Security uploads require including the **orig.tar.gz** file.

## 8.10 Skipped uploads

If you created multiple entries in the **debian/changelog** while skipping uploads, you must create a proper **\*\_changes** file which includes all changes since the last upload. This can be done by specifying the **dpkg-buildpackage** option **-v** with the last uploaded version, e.g., **1.2**.

- **dpkg-buildpackage -v1.2**
- **debuild -v1.2**
- **sbuild --debbuildopts -v1.2**
- For **gbp buildpackage**, edit the **~/gbp.conf** file.

## 8.11 Bug reports

The **reportbug(1)** command used for the bug report of *binarypackage* can be customized by the files in **usr/share/bug/binarypackage/**.

The **dh\_bugfiles** command installs these files from the template files in the **debian/** directory.

- **debian/binarypackage.bug-control** → **usr/share/bug/binarypackage/control**
  - This file contains some directions such as redirecting the bug report to another package.
- **debian/binarypackage.bug-presubj** → **usr/share/bug/binarypackage/presubj**
  - This file is displayed to the user by the **reportbug** command.
- **debian/binarypackage.bug-script** → **usr/share/bug/binarypackage** or **usr/share/bug/binarypackage/script**
  - The **reportbug** command runs this script to generate a template file for the bug report.

See **dh\_bugfiles(1)** and “[reportbug’s Features for Developers \(README.developers\)](#)”

## Tip



If you always remind the bug reporter of something or ask them about their situation, use these files to automate it.

## Chapter 9

# Advanced packaging

Let's describe advanced topics on Debian packaging.

### 9.1 Historical perspective

Let me oversimplify historical perspective of Debian packaging practices focused on the non-native packaging.

[Debian was started in 1990s](#) when upstream packages were available from public FTP sites such as [Sunsite](#). In those early days, Debian packaging used Debian source format currently known as the Debian source format “**1.0**”:

- The Debian source package ships a set of files for the Debian source package.
  - *package\_version.orig.tar.gz* : symlink to or copy of the upstream released file.
  - *package\_version-revision.diff.gz* : “**One big patch**” for Debian modifications.
  - *package\_version-revision.dsc* : package description.
- Several workaround approaches such as **dpatch**, **db**s, or **cdb**s were deployed to manage multiple topic patches.

The modern Debian source format “**3.0 (quilt)**” was invented around 2008 (see “[ProjectsDebSrc3.0](#)”):

- The Debian source package ships a set of files for the Debian source package.
  - *package\_version.orig.tar.?z* : symlink to or copy of the upstream released file.
  - *package\_version-revision.debian.tar.?z* : tarball of **debian/** for Debian modifications.
    - \* The **debian/source/format** file contains “**3.0 (quilt)**”.
    - \* Optional multiple topic patches are stored in the **debian/patches/** directory.
  - *package\_version-revision.dsc* : package description.
- The standardized approach to manage multiple topic patches using **quilt**(1) is deployed for the Debian source format “**3.0 (quilt)**”.

Most Debian packages adopted the Debian source formats “**3.0 (quilt)**” and “**3.0 (native)**”.

Now, the **git**(1) is popular with upstream and Debian developers. The **git** and its associated tools are important part of the modern Debian packaging workflow. This modern workflow involving **git** will be mentioned later in “Chapter 10”.

### 9.2 Current trends

Current Debian packaging practices and their trends are moving target. See:

- “[Debian Trends](#)” — Hints for “De facto standard” of Debian practices
  - Build systems: **dh**
  - Debian source format: “**3.0 (quilt)**”
  - VCS: **git**

- VCS Hosting: [salsa](#)
- Rules-Requires-Root: adopted, fakeroot
- Copyright format: [DEP-5](#)
- “[debhelper-compat-upgrade-checklist\(7\)](#) manpage” — Upgrade checklist for **debhelper**
- “[DEP - Debian Enhancement Proposals](#)” — Formal proposals to enhance Debian

You can also search entire Debian source code data by yourself, too.

- “[Debian Sources](#)” — code search tool
  - “[Debian Code Search](#)” — wiki page describing its usage
- “[Debian Code Search](#)” — another code search tool

## 9.3 Note on build system

Auto-generated files of the build system may be found in the released upstream tarball. These should be regenerated when Debian package is build. E.g.:

- “**dh \$@ --with autoreconf**” should be used in the **debian/rules** if Autotools (**autoconf** + **automake**) are used.

Some modern build system may be able to download required source codes and binary files from arbitrary remote hosts to satisfy build requirements. Don’t use this download feature. The official Debian package is required to be build only with packages listed in **Build-Depends**: of the **debian/control** file.

## 9.4 Continuous integration

The **dh\_auto\_test(1)** command is a **debhelper** command that tries to automatically run the test suite provided by the upstream developer during the Debian package building process.

The **autopkgtest(1)** command can be used after the Debian package building process. It tests generated Debian binary packages in the virtual environment using the **debian/tests/control** RFC822-style metadata file as [continuous integration](#) (CI). See:

- Documents in the **/usr/share/doc/autopkgtest/** directory
- “[4. autopkgtest: Automatic testing for packages](#)” of the “Ubuntu Packaging Guide”

There are several other CI tools on Debian for you to explore.

- The [Salsa](#) offers “[Section 10.3](#)”.
- The **debci** package: CI platform on top of the **autopkgtest** package
- The **jenkins** package: generic CI platform

## 9.5 Bootstrapping

Debian cares about supporting new ports or flavours. The new ports or flavours require [bootstrapping](#) operation for the cross-build of the initial minimal native-building system. In order to avoid build-dependency loops during bootstrapping, the build-dependency needs to be reduced using the **DEB\_BUILD\_PROFILES** environment variable.

See Debian wiki: “[BuildProfileSpec](#)”.

### Tip



If a core package **foo** build depends on a package **bar** with deep build dependency chains but **bar** is only used in the **test** target in **foo**, you can safely mark the **bar** with **<!nocheck>** in the **Build-depends** of **foo** to avoid build loops.

## 9.6 Compiler hardening

The compiler hardening support spreading for Debian **jessie** (8.0) demands that we pay extra attention to the packaging.

You should read the following references in detail.

- Debian wiki: [“Hardening”](#)
- Debian wiki: [“Hardening Walkthrough”](#)

The **debmake** command adds template comments to the **debian/rules** file as needed for **DEB\_BUILD\_MAINT\_OPTIONS**, **DEB\_CFLAGS\_MAINT\_APPEND**, and **DEB\_LDFLAGS\_MAINT\_APPEND** (see “Chapter 5” and **dpkg-buildflags(1)**).

## 9.7 Reproduzierbares Bauen

Here are some recommendations to attain a reproducible build result.

- Betten Sie keine Zeitstempel, basierend auf der Systemzeit, ein.
- Don’t embed the file path of the build environment.
- Use “**dh \$@**” in the **debian/rules** to access the latest **debhelper** features.
- Export the build environment as “**LC\_ALL=C.UTF-8**” (see “Section 11.1”).
- Set the timestamp used in the upstream source from the value of the debhelper-provided environment variable **\$SOURCE\_DATE\_EPOCH**.
- Lesen Sie mehr unter [“Reproduzierbares Bauen”](#).
  - [“Reproduzierbares Bauen - Wie geht es”](#).
  - [“Reproduzierbares Bauen - Zeitstempelvorschlag”](#).

Die durch **dpkg-genbuildinfo(1)** erstellte Steuerdatei **source-name\_source-version\_arch.buildinfo** zeichnet die Bauumgebung auf. Siehe **deb-buildinfo(5)**

## 9.8 Substvar

The **debian/control** file also defines the package dependency in which the [“variable substitutions mechanism”](#) (substvar) may be used to free package maintainers from chores of tracking most of the simple package dependency cases. See **deb-substvars(5)**.

The **debmake** command supports the following substvars:

- **\${misc:Depends}** for all binary packages
- **\${misc:Pre-Depends}** for all multiarch packages
- **\${shlibs:Depends}** for all binary executable and library packages
- **\${python:Depends}** for all Python packages
- **\${python3:Depends}** for all Python3 packages
- **\${perl:Depends}** for all Perl packages
- **\${ruby:Depends}** for all Ruby packages

For the shared library, required libraries found simply by “**objdump -p /path/to/program | grep NEEDED**” are covered by the **shlib** substvar.

For Python and other interpreters, required modules found simply looking for lines with “**import**”, “**use**”, “**require**”, etc., are covered by the corresponding substvars.

For other programs which do not deploy their own substvars, the **misc** substvar covers their dependency.

For POSIX shell programs, there is no easy way to identify the dependency and no substvar covers their dependency.

For libraries and modules required via the dynamic loading mechanism including the [“GObject introspection”](#) mechanism, there is no easy way to identify the dependency and no substvar covers their dependency.

## 9.9 Bibliothekspaket

Die Paketierung von Bibliothekssoftware verlangt von Ihnen deutlich mehr Arbeit als normal. Es folgen ein paar Erinnerungen zur Paketierung von Bibliothekssoftware:

- The library binary package must be named as in “Section 9.17”.
- Debian ships shared libraries such as `/usr/lib/<triplet>/libfoo-0.1.so.1.0.0` (see “Section 9.10”).
- Debian encourages using versioned symbols in the shared library (see “Section 9.16”).
- Debian doesn’t ship `*.la` libtool library archive files.
- Debian discourages using and shipping `*.a` static library files.

Before packaging shared library software, see:

- “Chapter 8 - Shared libraries” of the “Debian Policy Manual”
- “10.2 Libraries” of the “Debian Policy Manual”
- “6.7.2. Libraries” of the “Debian Developer’s Reference”

For the historic background study, see:

- “Escaping the Dependency Hell” <sup>1</sup>
  - This encourages having versioned symbols in the shared library.
- “Debian Library Packaging guide” <sup>2</sup>
  - Please read the discussion thread following [its announcement](#), too.

## 9.10 Multiarch

Multiarch support for cross-architecture installation of binary packages (particularly **i386** and **amd64**, but also other combinations) in the **dpkg** and **apt** packages introduced in Debian **wheezy** (7.0, May 2013), demands that we pay extra attention to packaging.

You should read the following references in detail.

- Ubuntu wiki (upstream)
  - “[MultiarchSpec](#)”
- Debian wiki (Debian situation)
  - “[Debian multiarch support](#)”
  - “[Multiarch/Implementation](#)”

The multiarch is enabled by using the `<triplet>` value such as **i386-linux-gnu** and **x86\_64-linux-gnu** in the install path of shared libraries as `/usr/lib/<triplet>/`, etc..

- The `<triplet>` value required internally by **debhelper** scripts is implicitly set in themselves. The maintainer doesn’t need to worry.
- The `<triplet>` value used in **override\_dh\_\*** target scripts must be explicitly set in the **debian/rules** file by the maintainer. The `<triplet>` value is stored in the **\$(DEB\_HOST\_MULTIARCH)** variable in the following **debian/rules** snippet example:

```
DEB_HOST_MULTIARCH = $(shell dpkg-architecture -qDEB_HOST_MULTIARCH)
...
override_dh_install:
    mkdir -p package1/lib/$(DEB_HOST_MULTIARCH)
    cp -dR tmp/lib/. package1/lib/$(DEB_HOST_MULTIARCH)
```

<sup>1</sup>This document was written before the introduction of the **symbols** file.

<sup>2</sup>The strong preference is to use the SONAME versioned **-dev** package names over the single **-dev** package name in “Chapter 6. Development (-DEV) packages”, which does not seem to be shared by the former ftp-master (Steve Langasek). This document was written before the introduction of the **multiarch** system and the **symbols** file.

Siehe:

- “Section 8.3”
- “Section 15.2”
- “Section 9.12”
- “`dpkg-architecture(1)` manpage”

## 9.11 Aufteilung eines Debian-Binärpakets

For well behaving build systems, the split of a Debian binary package into small ones can be realized as follows.

- Create binary package entries for all binary packages in the **debian/control** file.
- List all file paths (relative to **debian/tmp**) in the corresponding **debian/binarypackage.install** files.

Bitte prüfen Sie die Beispiele in dieser Anleitung:

- “Section 13.11” (Autotools-basiert)
- “Section 13.12” (CMake-basiert)

An intuitive and flexible method to create the initial template **debian/control** file defining the split of the Debian binary packages is accommodated with the **-b** option. See “Section 15.2”.

## 9.12 Pakettrennungsszenarien und -beispiele

Here are some typical multiarch package split scenarios for the following upstream source examples using the **debmake** command:

- eine Bibliotheksquelle *libfoo-1.0.tar.gz*
- eine Werkzeugquelle *bar-1.0.tar.gz*, geschrieben in einer kompilierten Sprache
- eine Werkzeugquelle *baz-1.0.tar.gz*, geschrieben in einer interpretierten Sprache

<i>Binärpaket</i>	<i>Typ</i>	<i>Architecture:</i>	<i>Multi-Arch:</i>	<i>Paketinhalt</i>
<b>libfoo1</b>	<b>lib*</b>	any	same	die Laufzeitbibliothek, koinstallierbar
<b>libfoo-dev</b>	<b>dev*</b>	any	same	the shared library header files etc., co-installable
<b>libfoo-tools</b>	<b>bin*</b>	any	foreign	the run-time support programs, not co-installable
<b>libfoo-doc</b>	<b>doc*</b>	all	foreign	the shared library documentation files
<i>bar</i>	<b>bin*</b>	any	foreign	the compiled program files, not co-installable
<i>bar-doc</i>	<b>doc*</b>	all	foreign	the documentation files for the program
<i>baz</i>	<b>script</b>	all	foreign	the interpreted program files

## 9.13 Multiarch library path

Debian policy requires to comply with the “[Filesystem Hierarchy Standard \(FHS\), version 3.0](#)”, with the exceptions noted in “[File System Structure](#)”.

The most notable exception is the use of `/usr/lib/<triplet>/` instead of `/usr/lib<qual>/` (e.g., `/lib32/` and `/lib64/`) to support a multiarch library.

For Autotools based packages under the **debhelper** package (compat>=9), this path setting is automatically taken care by the **dh\_auto\_configure** command.

For other packages with non-supported build systems, you need to manually adjust the install path as follows.

**Table 9.2** The multiarch library path options

Classic path	i386 multiarch path	amd64 multiarch path
/lib/	/lib/i386-linux-gnu/	/lib/x86_64-linux-gnu/
/usr/lib/	/usr/lib/i386-linux-gnu/	/usr/lib/x86_64-linux-gnu/

- If “./configure” is used in the **override\_dh\_auto\_configure** target in **debian/rules**, make sure to replace it with “**dh\_auto\_configure --**” while re-targeting the install path from **/usr/lib/** to **/usr/lib/\$(DEB\_HOST\_MULTIARCH)/**.
- Replace all occurrences of **/usr/lib/** with **/usr/lib/\*/** in **debian/foo.install** files.

All files installed simultaneously as the multiarch package to the same file path should have exactly the same file content. You must be careful with differences generated by the data byte order and by the compression algorithm.

The shared library files in the default path **/usr/lib/** and **/usr/lib/<triplet>/** are loaded automatically.

For shared library files in another path, the GCC option **-l** must be set by the **pkg-config** command to make them load properly.

## 9.14 Multiarch header file path

GCC includes both **/usr/include/** and **/usr/include/<triplet>/** by default on the multiarch Debian system.

If the header file is not in those paths, the GCC option **-I** must be set by the **pkg-config** command to make “**#include <foo.h>**” work properly.

**Table 9.3** The multiarch header file path options

Classic path	i386 multiarch path	amd64 multiarch path
/usr/include/	/usr/include/i386-linux-gnu/	/usr/include/x86_64-linux-gnu/
/usr/include/ <i>packagename</i> /	/usr/include/i386-linux-gnu/ <i>packagename</i> /	/usr/include/x86_64-linux-gnu/ <i>packagename</i> /
	/usr/lib/i386-linux-gnu/ <i>packagename</i> /	/usr/lib/x86_64-linux-gnu/ <i>packagename</i> /

The use of the **/usr/lib/<triplet>/packagename/** path for the library files allows the upstream maintainer to use the same install script for the multiarch system with **/usr/lib/<triplet>** and the biarch system with **/usr/lib<qual>/**.  
3

The use of the file path containing *packagename* enables having more than 2 development libraries simultaneously installed on a system.

## 9.15 Multiarch \*.pc file path

The **pkg-config** program is used to retrieve information about installed libraries in the system. It stores its configuration parameters in the **\*.pc** file and is used for setting the **-I** and **-l** options for GCC.

**Table 9.4** The \*.pc file path options

Classic path	i386 multiarch path	amd64 multiarch path
/usr/lib/pkgconfig/	/usr/lib/i386-linux-gnu/pkgconfig/	/usr/lib/x86_64-linux-gnu/pkgconfig/

## 9.16 Bibliothekssymbole

The symbols support in **dpkg** introduced in Debian **lenny** (5.0, May 2009) helps us to manage the backward ABI compatibility of the library package with the same package name. The **DEBIAN/symbols** file in the binary package provides the minimal version associated with each symbol.

3This path is compliant with the FHS. “[Filesystem Hierarchy Standard: /usr/lib : Libraries for programming and packages](#)” states “Applications may use a single subdirectory under **/usr/lib**. If an application uses a subdirectory, all architecture-dependent data exclusively used by the application must be placed within that subdirectory.”

An oversimplified method for the library packaging is as follows.

- Extract the old **DEBIAN/symbols** file of the immediate previous binary package with the “**dpkg-deb -e**” command.
  - Alternatively, the **mc** command may be used to extract the **DEBIAN/symbols** file.
- Copy it to the **debian/binarypackage.symbols** file.
  - If this is the first package, use an empty content file instead.
- Build the binary package.
  - If the **dpkg-gensymbols** command warns about some new symbols:
    - \* Extract the updated **DEBIAN/symbols** file with the “**dpkg-deb -e**” command.
    - \* Trim the Debian revision such as **-1** in it.
    - \* Copy it to the **debian/binarypackage.symbols** file.
    - \* Re-build the binary package.
  - If the **dpkg-gensymbols** command does not warn about new symbols:
    - \* You are done with the library packaging.

For the details, you should read the following primary references.

- “[8.6.3 The symbols system](#)” of the “Debian Policy Manual”
- “**dh\_makeshlibs**(1) manpage”
- “**dpkg-gensymbols**(1) manpage”
- “**dpkg-shlibdeps**(1) manpage”
- “**deb-symbols**(5) manpage”

Sie sollten auch Folgendes prüfen:

- Debian wiki: “[UsingSymbolsFiles](#)”
- Debian wiki: “[Projects/ImprovedDpkgShlibdeps](#)”
- Debian kde team: “[Working with symbols files](#)”
- “Section [13.11](#)”
- “Section [13.12](#)”

#### Tip



For C++ libraries and other cases where the tracking of symbols is problematic, follow “[8.6.4 The shlibs system](#)” of the “Debian Policy Manual”, instead. Please make sure to erase the empty **debian/binarypackage.symbols** file generated by the **debmake** command. For this case, the **DEBIAN/shlibs** file is used.



## 9.17 Library package name

Let's consider that the upstream source tarball of the **libfoo** library is updated from **libfoo-7.0.tar.gz** to **libfoo-8.0.tar.gz** with a new SONAME major version which affects other packages.

The binary library package must be renamed from **libfoo7** to **libfoo8** to keep the **unstable** suite system working for all dependent packages after the upload of the package based on the **libfoo-8.0.tar.gz**.

### Warning



If the binary library package isn't renamed, many dependent packages in the **unstable** suite become broken just after the library upload even if a binNMU upload is requested. The binNMU may not happen immediately after the upload due to several reasons.

The **-dev** package must follow one of the following naming rules:

- Use the **unversioned -dev** package name: **libfoo-dev**
  - This is the typical one for leaf library packages.
  - Only one version of the library source package is allowed in the archive.
    - \* The associated library package needs to be renamed from **libfoo7** to **libfoo8** to prevent dependency breakage in the **unstable** suite during the library transition.
  - This approach should be used if the simple binNMU resolves the library dependency quickly for all affected packages. (ABI change by dropping the deprecated API while keeping the active API unchanged.)
  - This approach may still be a good idea if manual code updates, etc. can be coordinated and manageable within limited packages. (API change)
- Use the **versioned -dev** package names: **libfoo7-dev** and **libfoo8-dev**
  - This is typical for many major library packages.
  - Two versions of the library source packages are allowed simultaneously in the archive.
    - \* Make all dependent packages depend on **libfoo-dev**.
    - \* Make both **libfoo7-dev** and **libfoo8-dev** provide **libfoo-dev**.
    - \* The source package needs to be renamed as **libfoo7-7.0.tar.gz** and **libfoo8-8.0.tar.gz** respectively from **libfoo-?.0.tar.gz**.
    - \* The package specific install file path including **libfoo7** and **libfoo8** respectively for header files etc. needs to be chosen to make them co-installable.
  - Do not use this heavy handed approach, if possible.
  - This approach should be used if the update of multiple dependent packages require manual code updates, etc. (API change) Otherwise, the affected packages become RC buggy with FTBFS.

### Tip



If the data encoding scheme changes (e.g., latin1 to utf-8), the same care as the API change needs to be taken.

Siehe "Section 9.9".

## 9.18 Bibliotheksübergänge

When you package a new library package version which affects other packages, you must file a transition bug report against the **release.debian.org** pseudo package using the **reportbug** command with the **ben file** and wait for the approval for its upload from the [Release Team](#).

Release team has the “[transition tracker](#)”. See “[Transitions](#)”.

### Caution



Please make sure to rename binary packages as in “[Section 9.17](#)”.

## 9.19 binNMU-sicher

A “[binNMU](#)” is a binary-only non-maintainer upload performed for library transitions etc. In a binNMU upload, only the “**Architecture: any**” packages are rebuilt with a suffixed version number (e.g. version 2.3.4-3 will become 2.3.4-3+b1). The “**Architecture: all**” packages are not built.

The dependency defined in the **debian/control** file among binary packages from the same source package should be safe for the binNMU. This needs attention if there are both “**Architecture: any**” and “**Architecture: all**” packages involved in it.

- “**Architecture: any**” package: depends on “**Architecture: any**” *foo* package
  - **Depends:** *foo* (= **\${binary:Version}**)
- “**Architecture: any**” package: depends on “**Architecture: all**” *bar* package
  - **Depends:** *bar* (= **\${source:Version}**)
- “**Architecture: all**” package: depends on “**Architecture: any**” *baz* package
  - **Depends:** *baz* (**>= \${source:Version}**), *baz* (**<< \${source:Version}.0~**)

## 9.20 Fehlersuchinformationen

The Debian package is built with the debugging information but packaged into the binary package after stripping the debugging information as required by “[Chapter 10 - Files](#)” of the “Debian Policy Manual”.

Siehe

- “[6.7.9. Best practices for debug packages](#)” of the “Debian Developer’s Reference”.
- “[18.2 Debugging Information in Separate Files](#)” of the “Debugging with gdb”
- “**dh\_strip**(1) manapage”
- “**strip**(1) manapage”
- “**readelf**(1) manapage”
- “**objcopy**(1) manapage”
- Debian wiki: “[DebugPackage](#)”
- Debian wiki: “[AutomaticDebugPackages](#)”
- Debian debian-devel post: “[Status on automatic debug packages](#)” (2015-08-15)

## 9.21 -dbgsym package

The debugging information is automatically packaged separately as the debug package using the **dh\_strip** command with its default behavior. The name of such a debug package normally has the **-dbgsym** suffix.

- The **debian/rules** file shouldn't explicitly contain **dh\_strip**.
- Set the **Build-Depends** to **debhelper-compat (>=13)** while removing **Build-Depends** to **debhelper** in **debian/control**.

## 9.22 debconf

The **debconf** package enables us to configure packages during their installation in 2 main ways:

- non-interactively from the **debian-installer** pre-seeding.
- interactively from the menu interface (**dialog**, **gnome**, **kde**, ...)
  - the package installation: invoked by the **dpkg** command
  - the installed package: invoked by the **dpkg-reconfigure** command

All user interactions for the package installation must be handled by this **debconf** system using the following files.

- **debian/binarypackage.config**
  - This is the **debconf config** script used for asking any questions necessary to configure the package.
- **debian/binarypackage.template**
  - This is the **debconf templates** file used for asking any questions necessary to configure the package.

These **debconf** files are called by package configuration scripts in the binary Debian package

- **DEBIAN/binarypackage.preinst**
- **DEBIAN/binarypackage.prerm**
- **DEBIAN/binarypackage.postinst**
- **DEBIAN/binarypackage.postrm**

See **dh\_installdebconf(1)**, **debconf(7)**, **debconf-devel(7)** and “[3.9.1 Prompting in maintainer scripts](#)” in the “Debian Policy Manual”.

# Chapter 10

## Packaging with git

Up to “Chapter 9”, we focused on packaging operations without using [Git](#) or any other [VCS](#). These traditional packaging operations were based on the tarball released by the upstream as mentioned in “Section 9.1”.

Currently, the **git**(1) command is the de-facto platform for the VCS tool and is the essential part of both upstream development and Debian packaging activities. (See Debian wiki “[Debian git packaging maintainer branch formats and workflows](#)” for existing VCS workflows.)

### Note



Since the non-native Debian source package uses “**diff -u**” as its backend technology for the maintainer modification, it can't represent modification involving symlink, file permissions, nor binary data ([March 2022 discussion on debian-devel@l.d.o](#)). Please avoid making such maintainer modifications even though these can be recorded in the Git repository.

Since VCS workflows are complicated topic and there are many practice styles, I only touch on some key points with minimal information, here.

[Salsa](#) is the remote Git repository service with associated tools. It offers the collaboration platform for Debian packaging activities using a custom [GitLab](#) application instance. See:

- “Section [10.1](#)”
- “Section [10.2](#)”
- “Section [10.3](#)”

There are 2 styles of branch names for the Git repository used for the packaging. See “Section [10.4](#)”. There are 2 main usage styles for the Git repository for the packaging. See:

- “Section [10.5](#)”
- “Section [10.6](#)”

There are 2 notable Debian packaging tools for the Git repository for the packaging.

- **gbp**(1) and its subcommands:
  - This is a tool designed to work with “Section [10.5](#)”.
  - See “Section [10.7](#)”.
- **dg**it(1) and its subcommands:
  - This is a tool designed to work with both “Section [10.6](#)” and “Section [10.5](#)”.
  - This contains a tool to upload Debian packages using the **dg**it server.
  - See “Section [10.8](#)”.

## 10.1 Salsa repository

It is highly desirable to host Debian source code package on [Salsa](#). Over 90% of all Debian source code packages are hosted on [Salsa](#).<sup>1</sup>

The exact VCS repository hosting an existing Debian source code package can be identified by a metadata field `Vcs-*` which can be viewed with the `apt-cache showsrc <package-name>` command.

## 10.2 Salsa account setup

After signing up for an account on [Salsa](#), make sure that the following pages have the same e-mail address and GPG keys you have configured to be used with Debian, as well as your SSH key:

- <https://salsa.debian.org/-/profile/emails>
- [https://salsa.debian.org/-/user\\_settings/gpg\\_keys](https://salsa.debian.org/-/user_settings/gpg_keys)
- [https://salsa.debian.org/-/user\\_settings/ssh\\_keys](https://salsa.debian.org/-/user_settings/ssh_keys)

## 10.3 Salsa CI service

[Salsa](#) runs [Salsa CI](#) service as an instance of [GitLab CI](#) for “Section 9.4”.

For every “**git push**” instances, tests which mimic tests run on the official Debian package service can be run by setting [Salsa CI](#) configuration file “Section 6.13” as:

```
---
include:
  - https://salsa.debian.org/salsa-ci-team/pipeline/raw/master/recipes/debian.yml

# Customizations here
```

## 10.4 Branch names

The Git repository for the Debian packaging should have at least 2 branches:

- **debian-branch** to hold the current development work.
  - old style: **master** (or **debian**, **main**, **latest**, ...)
  - [DEP-14](#) style: **debian/sid**
- **upstream-branch** to hold the upstream releases.
  - old style: **upstream**
  - [DEP-14](#) style: **upstream/latest**

In this tutorial, old style branch names are used in examples for simplicity.

### Note



This **upstream-branch** may need to be created using the tarball released by the upstream independent of the upstream Git repository since it tends to contain automatically generated files.

The upstream Git repository content can co-exist in the local Git repository used for the Debian packaging by adding its copy. E.g.:

```
$ git remote add upstream-git <url-upstream-git-repo>
$ git fetch upstream-git master:upstream-master
```

This allows easy cherry-picking from the upstream Git repository for bug fixes.

<sup>1</sup>Use of [git.debian.org](#) or [alioth.debian.org](#) are deprecated now.

## 10.5 Patch unapplied Git repository

The patch unapplied Git repository can be summarized as:

- This seems to be the traditional practice as of 2024.
- The source tree matches extracted contents by “**dpkg-source -x --skip-patches**” of the Debian source package.
  - The upstream source is recorded in the Git repository without changes.
  - The maintainer modified contents are confined within the **debian/\*** directory.
  - Maintainer changes to the upstream source are recorded in **debian/patches/\*** files for the Debian source format “**3.0 (quilt)**”.
- This repository style is useful for all variants of traditional workflows and **gdb** based workflow:
  - “Section 5.7” (no patch)
  - “Section 5.10”
    - \* **debian/patches/\*** files can also be generated using “**git format-patch**”, “**git diff**”, or “**gitk**” from **git** commits in the through-away maintainer modification branch or from the upstream unreleased commits.
  - “Section 5.11” including the last “**dquilt pop -a**” step
  - “Section 10.9”
- Use helper scripts such as **dquilt(1)** and **gbp-pq(1)** to manage data in **debian/patches/\*** files.
  - Add **.pc** line to the **~/.gitignore** file if **dquilt** is used.
  - Add **unapply-patches** and **abort-on-upstream-changes** lines in the **debian/source/local-options** file.
- Use “**dpkg-source -b**” to build the Debian source package.
- Use **dput(1)** to upload the Debian source package.
  - Use “**dgkit --gbp push-source**” or “**dgkit --gbp push**” instead to upload the Debian package via the **dgkit** server (see “**dgkit-maint-gbp(7)**”).

### Note



The **debian/source/local-options** and **debian/source/local-patch-header** files are meant to be recorded by the **git** command. These aren't included in the Debian source package.

## 10.6 Patch applied Git repository

The patch applied Git repository can be summarized as:

- The source tree matches extracted contents by “**dpkg-source -x**” of the Debian source package.
  - The source tree is buildable and the same as what NMU maintainers see.
  - The source is recorded in the Git repository with maintainer changes including the **debian/** directory.
  - Maintainer changes to the upstream source are also recorded in **debian/patches/\*** files for the Debian source format “**3.0 (quilt)**”.

Use one of workflow styles:

- **dgkit-maint-merge(7)** workflow.

- Use this if you don’t intend to record topic patches in the Debian source package.
- Good enough for packages only with trivial modifications to the upstream.
- Only choice for packages with intertwined modification histories to the upstream
- Add **auto-commit** and **single-debian-patch** lines in the **debian/source/local-options** file
- Use “**git checkout upstream; git pull**” to pull the new upstream commit and use “**git checkout master ; git merge <new-version-tag>**” to merge it to the **master** branch.
- Use “**dpkg-source -b**” to build the Debian source package.
- Use “**dgit push-source**” or “**dgit push**” for uploading the Debian package via the **dgit** server.
- See “Section 5.12” for example.
- **dgit-maint-debrebase(7)** workflow.
  - Use this if you wish to commit maintainer changes to the patch applied Git repository with the same granularity as patches of “Section 10.9”.
  - Good for packages with multiple sequenced modifications to the upstream.
  - Use “**dgit build-source**” to build the Debian source package.
  - Use “**dgit push-source**” or “**dgit push**” for uploading the Debian package via the **dgit** server.
  - Details of this workflow are beyond the scope of this tutorial document. See “Section 10.12” for more.

## 10.7 Note on gbp

The **gbp** command is provided by the **git-buildpackage** package.

- This command is designed to manage contents of “Section 10.5” efficiently.
- Use “**gbp import-orig**” to import the new upstream tar to the git repository.
  - The “**--pristine-tar**” option for the “**git import-orig**” command enables storing the upstream tarball in the same git repository.
  - The “**--uscan**” option as the last argument of the “**gbp import-orig**” command enables downloading and committing the new upstream tarball into the git repository.
- Use “**gbp import-dsc**” to import the previous Debian source package to the git repository.
- Use “**gbp dch**” to generate the Debian changelog from the git commit messages.
- Use “**gbp buildpackage**” to build the Debian binary package from the git repository.
  - The **sbuild** package can be used as its clean chroot build backend either by configuration or adding “**--git-builder=sbuild -A -s --source-only-changes -v -d unstable**”
- Use “**gbp pull**” to update the **debian**, **upstream** and **pristine-tar** branches safely from the remote repository.
- Use “**gbp pq**” to manage quilt patches without using **dquilt** command.
- Use “**gbp clone REPOSITORY\_URL**” to clone and set up tracking branches for **debian**, **upstream** and **pristine-tar**.

Package history management with the **git-buildpackage** package is becoming the standard practice for many Debian maintainers. See more at:

- “[Building Debian Packages with git-buildpackage](#)”
- “[4 tips to maintain a “3.0 \(quilt\)” Debian source package in a VCS](#)”
- The **systemd** packaging practice documentation on “[Building from source](#)”
- The workflow mentioned in **dgit-maint-gbp(7)** which enables to use this **gbp** with **dgit**

## 10.8 Note on dgit

The **dgit** command is provided by the **dgit** package.

- This command is designed to manage contents of “Section 10.6” efficiently.
  - This enables to access the Debian package repository as if it is a **git** remote repository.
- This command supports uploading Debian packages using the **dgit** server from both “Section 10.5” and “Section 10.6”.

The new **dgit** package offers commands to automate packaging activities using the git repository as an alternative to still popular **gbp-buildpackage**. Please read their guide:

- **dgit-maint-merge(7)** — for the Debian source format “**3.0 (quilt)**” package with its changes flowing both ways between the upstream Git repository and the Debian Git repository which are tightly coupled using “Section 10.6”.
- **dgit-maint-debbase(7)** — for the Debian source format “**3.0 (quilt)**” package with its changes flowing mostly one way from the upstream Git repository to the Debian Git repository using “Section 10.6”.
- **dgit-maint-gbp(7)** — for the Debian source format “**3.0 (quilt)**” package with its Debian Git repository which is kept usable also for people using **gbp-buildpackage(1)** using “Section 10.5”.
- **dgit-maint-native(7)** — for the Debian source format “**3.0 (native)**” package in the Debian Git repository. (No maintainer changes)

The **dgit(1)** command can push the easy-to-trace change history to the <https://browse.dgit.debian.org/> site and can upload Debian package to the Debian repository properly without using **dput(1)**.

The concept around **dgit** is beyond this tutorial document. Please start reading relevant information:

- “[dgit: use the Debian archive as a git remote \(2015\)](#)”
- “[tag2upload \(2023\)](#)”

## 10.9 Patch by “gbp-pq” approach

For “Section 10.5”, you can generate **debian/patches/\*** files using the **gbp-pq(1)** command from **git** commits in the through-away **patch-queue** branch.

Unlike **dquilt** which offers similar functionality as seen “Section 5.11” and “Section 8.5”, **gbp-pq** doesn’t generate **.pc/\*** files.

### 10.10 Manage patch queue with gbp-pq

You can add, drop, and refresh **debian/patches/\*** files with **gbp-pq** to manage patch queue.

If the package is managed in “Section 10.5” using the **git-buildpackage** package, you can revise the upstream source to fix bug as the maintainer and release a new Debian revision using **gbp pq**.

- **Add** a new patch recording the upstream source modification on the file *buggy\_file* as:

```
$ git checkout master
$ gbp pq import
gbp:info: ... imported on 'patch-queue/master'
$ vim buggy_file
...
$ git add buggy_file
$ git commit
$ gbp pq export
gbp:info: On 'patch-queue/master', switching to 'master'
gbp:info: Generating patches from git (master..patch-queue/master)
$ git add debian/patches/*
$ dch -i
$ git commit -a -m "Closes: #<bug_number>"
$ git tag debian/<version>-<rev>
```



- **Drop** (== disable) an existing patch
  - Comment out pertinent line in **debian/patches/series**
  - Erase the patch itself (optional)
- **Refresh** **debian/patches/\*** files to make “**dpkg-source -b**” work as expected after updating a Debian package to the new upstream release.

```
$ git checkout master
$ gbp pq --force import # ensure patch-queue/master branch
gbp:info: ... imported on 'patch-queue/master'
$ git checkout master
$ gbp import-orig --pristine-tar --uscan
...
gbp:info: Successfully imported version ??? of ../packagename_???.orig. ↵
tar.gz
$ gbp pq rebase
... resolve conflicts and commit to patch-queue/master branch
$ gbp pq export
gbp:info: On 'patch-queue/master', switching to 'master'
gbp:info: Generating patches from git (master..patch-queue/master)
$ git add debian/patches
$ git commit -m "Update patches"
$ dch -v <newversion>-1
$ git commit -a -m "release <newversion>-1"
$ git tag debian/<newversion>-1
```

## 10.11 gbp import-dscs --debsnap

For Debian source packages named “<source-package>” recorded in the [snapshot.debian.org](https://snapshot.debian.org) archive, an initial git repository managed in “Section 10.5” with all of the Debian version history can be generated as follows.

```
$ gbp import-dscs --debsnap --pristine-tar <source-package>
```

## 10.12 Note on dgit-maint-debrebase workflow

Here are some hints around **dgit-maint-debrebase**(7). [2](#)

- Use “**dgit setup-new-tree**” to prepare the local **git** working repository.
- The first maintainer modification commit should contain files only in the **debian/** directory excluding files in the **debian/patches** directory.
- **debian/patches/\*** files are generated from the maintainer modification commit history using the “**dgit quilt-fixup**” command automatically invoked from “**dgit build**” and “**dgit push**”.
- Use “**git-debrebase new-version <new-version-tag>**” to rebase the maintainer modification commit history with automatically updated **debian/changelog**.
- Use “**git-debrebase conclude**” to make a new pseudomerge (== “**git merge -s ours**”) to record Debian package with clean ff-history.

See **dgit-maint-debrebase**(7), **dgit**(1) and **git-debrebase**(1) for more.

---

<sup>2</sup>I may be incorrect, here.

## 10.13 Quasi-native Debian packaging

The **quasi-native** packaging scheme packages a source without the real upstream tarball using the **non-native** package format.

### Tip



Some people promote this **quasi-native** packaging scheme even for programs written only for Debian since it helps to ease communication with the downstream distros such as Ubuntu for bug fixes etc.

This **quasi-native** packaging scheme involves 2 preparation steps:

- Organize its source tree almost like **native** Debian package (see “Section 6.4”) with **debian/\*** files with a few exceptions:
  - Make **debian/source/format** to contain “**3.0 (quilt)**” instead of “**3.0 (native)**” .
  - Make **debian/changelog** to contain *version-revision* instead of *version* .
- Generate missing upstream tarball preferably without **debian/\*** files.
  - For Debian source format “**3.0 (quilt)**”, removal of files under **debian/** directory is an optional action.

The rest is the same as the **non-native** packaging workflow as written in “Section 6.1”.

Although this can be done in many ways (“Section 15.4”), you can use the Git repository and “**git deborig**” as:

```
$ cd /path/to/<dirname>
$ dch -r
... set its <version>-<revision>, e.g., 1.0-1
$ git tag -s debian/1.0-1
$ git rm -rf debian
$ git tag -s upstream/1.0
$ git commit -m upstream/1.0
$ git reset --hard HEAD^
$ git deborig
$ sbuild
```

# Chapter 11

## Tipps

Please also read insightful pages linked from “[Notes on Debian](#)” by Russ Allbery (long time Debian developer) which have best practices for advanced packaging topics.

### 11.1 Build under UTF-8

The default locale of the build environment is **C**.

Some programs such as the **read** function of Python3 change their behavior depending on the locale.

Adding the following code to the **debian/rules** file ensures building the program under the **C.UTF-8** locale.

```
LC_ALL := C.UTF-8
export LC_ALL
```

### 11.2 UTF-8 conversion

If upstream documents are encoded in old encoding schemes, converting them to **UTF-8** is a good idea.

Use the **iconv** command in the **libc-bin** package to convert the encoding of plain text files.

```
$ iconv -f latin1 -t utf8 foo_in.txt > foo_out.txt
```

Use **w3m(1)** to convert from HTML files to UTF-8 plain text files. When you do this, make sure to execute it under UTF-8 locale.

```
$ LC_ALL=C.UTF-8 w3m -o display_charset=UTF-8 \
    -cols 70 -dump -no-graph -T text/html \
    < foo_in.html > foo_out.txt
```

Run these scripts in the **override\_dh\_\*** target of the **debian/rules** file.

### 11.3 Hints for Debugging

When you face build problems or core dumps of generated binary programs, you need to resolve them yourself. That's **debug**.

This is too deep a topic to describe here. So, let me just list few pointers and hints for some typical debug tools.

- Wikipedia: “[core dump](#)”
  - “**man core**”
  - Update the “**/etc/security/limits.conf**” file to include the following:

```
* soft core unlimited
```
  - “**ulimit -c unlimited**” in **~/.bashrc**
  - “**ulimit -a**” to check
  - Press **Ctrl-\** or “**kill -ABRT 'PID'**” to make a core dump file

- **gdb** - The GNU Debugger
  - “**info gdb**”
  - “Debugging with GDB” in `/usr/share/doc/gdb-doc/html/gdb/index.html`
- **strace** - Trace system calls and signals
  - Use **strace-graph** script found in `/usr/share/doc/strace/examples/` to make a nice tree view
  - “**man strace**”
- **ltrace** - Trace library calls
  - “**man ltrace**”
- “**sh -n script.sh**” - Syntax check of a Shell script
- “**sh -x script.sh**” - Trace a Shell script
- “**python3 -m py\_compile script.py**” - Syntax check of a Python script
- “**python3 -mtrace --trace script.py**” - Trace a Python script
- “**perl -I ./libpath -c script.pl**” - Syntax check of a Perl script
- “**perl -d:Trace script.pl**” - Trace a Perl script
  - Install the **libterm-readline-gnu-perl** package or its equivalent to add input line editing capability with history support.
- **lsuf** - List open files by processes
  - “**man lsuf**”

## Tip



Der Befehl **script** zeichnet Konsoleausgaben auf.

## Tip



Die Befehle **screen** und **tmux** bieten Ihnen im Zusammenspiel mit **ssh** eine sichere und robuste Verbindung zu fernen Terminals.

## Tip



A Python- and Shell-like REPL (=READ + EVAL + PRINT + LOOP) environment for Perl is offered by the **reply** command from the **libreply-perl** (new) package and the **re.pl** command from the **libdevel-repl-perl** (old) package.

## Tip



The **rlwrap** and **rlfe** commands add input line editing capability with history support to any interactive commands. E.g. “**rlwrap dash -i**”.

# Chapter 12

## Tool usages

Here are some notable tools around Debian packaging.

### Note



The description in this section is too terse to be useful for most of the prospective maintainers. This is the intentional choice of the author. You are highly encouraged to search and read all the pertinent documents associated with the commands used.

### Note



Examples here use the **gz**-compression. The **xz**-compression may be used instead.

## 12.1 debdiff

Sie können die Dateiinhalte in zwei Quellpaketen mit dem Befehl **debdiff** vergleichen.

```
$ debdiff old-package.dsc new-package.dsc
```

Sie können auch Dateilisten in zwei Gruppen von Debian-Binärpaketen mit dem Befehl **debdiff** vergleichen.

```
$ debdiff old-package.changes new-package.changes
```

Diese sind nützlich, um herauszufinden, was sich in Quellpaketen geändert hat und zu prüfen, ob unbeabsichtigte Änderungen beim Aktualisieren der Binärpakete erfolgten, wie beispielsweise falsch angeordnete oder entfernte Dateien.

Debian now enforces the source-only upload when developing packages. So there may be 2 different **\*.changes** files:

- `package_version-revision_source.changes` for the normal source-only upload
- `package_version-revision_arch.changes` for the binary upload

## 12.2 dget

Mit dem Befehl **dget** können Sie eine Gruppe von Dateien für das Debian-Quellpaket herunterladen.

```
$ dget https://www.example.org/path/to/package_version-rev.dsc
```

## 12.3 mk-origtargz

You can make the upstream tarball `../foo-newversion.tar.[xg]z` accessible from the Debian source tree as `../foo_newversion.orig.tar`.

## 12.4 origtargz

You can fetch the pre-existing orig tarball of a Debian package from various sources, and unpack it with **origtargz** command.

This is basically for -2, -3, ... revisions.

## 12.5 git deborig

If the upstream project is hosted on a Git repository without the official release of tarball, you can generate its orig tarball from the **git** repository for use by the Debian source package. Please, execute “git deborig” from the root of the checked-out source tree.

This is basically for -1 revisions.

## 12.6 dpkg-source -b

The “**dpkg-source -b**” command packs the upstream source tree into the Debian source package.

It expects a series of patches in the **debian/patches/** directory and their application sequence in **debian/patches/series**.

It is compatible with **dquilt** (see “Section 4.4”) operations and understands the patch application status from the existence of **.pc/applied-patches**.

The **dpkg-buildpackage** command invokes “**dpkg-source -b**”.

## 12.7 dpkg-source -x

The “**dpkg-source -x**” command extracts source tree and applies the patches in the **debian/patches/** directory using the sequence specified in **debian/patches/series** to the upstream source tree. It also adds **.pc/applied-patches**. (See “Section 10.6”.)

The “**dpkg-source -x --skip-patches**” command extracts source tree only. It doesn’t add **.pc/applied-patches**. (See “Section 10.5”.)

Both extracted source trees are ready for building Debian binary packages with **dpkg-buildpackage**, **dbuild**, **sbuild**, etc..

## 12.8 debc

Sie sollten erstellte Pakete mit dem Befehl **debc** lokal installieren, um sie zu testen.

```
$ debc package_version-rev_arch.changes
```

## 12.9 piuparts

You should install generated packages with the **piuparts** command to test it automatically.

```
$ sudo piuparts package_version-rev_arch.changes
```

### Note



This is a very slow process with remote APT package repository access.

## 12.10 bts

After uploading the package, you will receive bug reports. It is an important duty of a package maintainer to manage these bugs properly as described in “[5.8. Handling bugs](#)” of the “Debian Developer’s Reference”.

The **bts** command is a handy tool to manage bugs on the “[Debian Bug Tracking System](#)”.

```
$ bts severity 123123 wishlist , tags -1 pending
```

# Chapter 13

## Weitere Beispiele

There is an old Latin saying: “**fabricando fit faber**” (“practice makes perfect”).

Es wird nachdrücklich empfohlen, mit einfachen Paketen zu üben und mit allen Schritten der Debian-Paketierung zu experimentieren. Dieses Kapitel stellt Ihnen viele Fälle von Originalautoren zur Übung bereit.

Es sollte Ihnen auch mit einführenden Beispielen für viele Programmierthemen dienen.

- Programmieren in der POSIX-Shell, Python3 und C
- Methode, um ein Desktop-GUI-Programmstarter mit Icon-Graphiken zu erstellen.
- Conversion of a command from [CLI](#) to [GUI](#).
- Conversion of a program to use **gettext** for [internationalization and localization](#): POSIX shell and C sources.
- Overview of many build systems: Makefile, Python, Autotools, and CMake.

Bitte beachten Sie, dass Debian ein paar Dinge sehr Ernst nimmt:

- Freie Software (auch als Libre Software bekannt)
- Stabilität und Sicherheit des Betriebssystems
- Universelles Betriebssystem mittels:
  - freier Wahl der Quellen der Originalautoren
  - freier Wahl der CPU-Architektur und
  - freier Wahl der Sprachen für Oberflächen.

Das in “Chapter 5” dargestellte Beispiel ist die Voraussetzung für dieses Kapitel.

Some details are intentionally left vague in the following sections. Please try to read the pertinent documentation and practice yourself to find them out.

### Tip



The best source of a packaging example is the current Debian archive itself. Please use the “[Debian Code Search](#)” service to find pertinent examples.

### 13.1 Cherry-pick templates

Here is an example of creating a simple Debian package from a zero content source on an empty directory.

This is a good platform to get all the template files without making a mess in the upstream source tree you are working on.

Let’s assume this empty directory to be **debhello-0.1**.



```
$ mkdir debhello-0.1
$ tree
.
+-- debhello-0.1

2 directories, 0 files
```

Let's generate the maximum amount of template files.

Let's also use the “**-p debhello -t -u 0.1 -r 1**” options to make the missing upstream tarball with default **-x3** and **T** options.

```
$ cd /path/to/debhello-0.1
$ debmake -p debhello -t -u 0.1 -r 1
I: set parameters
...
```

Lassen Sie uns die erstellten Vorlagendateien anschauen.

```
$ cd /path/to
$ tree
.
+-- debhello-0.1
|   +-- debian
|       +-- README.Debian
|       +-- README.source
|       +-- changelog
|       +-- clean
|       +-- control
|       +-- copyright
|       +-- debhello.bug-control.ex
|       +-- debhello.bug-presubj.ex
|       +-- debhello.bug-script.ex
|       +-- debhello.conffiles.ex
|       +-- debhello.cron.d.ex
|       +-- debhello.cron.daily.ex
|       +-- debhello.cron.hourly.ex
|       +-- debhello.cron.monthly.ex
|       +-- debhello.cron.weekly.ex
|       +-- debhello.default.ex
|       +-- debhello.emacs-eninstall.ex
|       +-- debhello.emacs-enremove.ex
|       +-- debhello.emacs-enstartup.ex
|       +-- debhello.lintian-overrides.ex
|       +-- debhello.service.ex
|       +-- debhello.tmpfile.ex
|       +-- dirs
|       +-- gbp.conf
|       +-- install
|       +-- links
|       +-- maintscript.ex
|       +-- manpage.1.ex
|       +-- manpage.asciidoc.ex
|       +-- manpage.md.ex
|       +-- manpage.sgml.ex
|       +-- manpage.xml.ex
|       +-- patches
|       |   +-- series
|       +-- postinst.ex
|       +-- postrm.ex
|       +-- preinst.ex
|       +-- prerm.ex
|       +-- rules
|       +-- salsa-ci.yml
|       +-- source
```

```

|         | +-- format
|         | +-- lintian-overrides.ex
|         | +-- local-options.ex
|         | +-- local-patch-header.ex
|         | +-- options.ex
|         | +-- patch-header.ex
|         +-- tests
|         | +-- control
|         +-- upstream
|         | +-- metadata
|         +-- watch
+-- debhello-0.1.tar.gz
+-- debhello_0.1.orig.tar.gz -> debhello-0.1.tar.gz

7 directories, 50 files

```

Now you can copy any of these generated template files in the *debhello-0.1/debian/* directory to your package as needed while renaming them as needed.

## 13.2 Kein Makefile (Shell, CLI)

Here is an example of creating a simple Debian package from a POSIX shell CLI program without its build system.

Let's assume this upstream tarball to be **debhello-0.2.tar.gz**.

This type of source has no automated means and files must be installed manually.

Zum Beispiel:

```

$ tar -xzmf debhello-0.2.tar.gz
$ cd debhello-0.2
$ sudo cp scripts/hello /bin/hello
...

```

Let's get this source as tar file from a remote site and make it the Debian package.

**Laden Sie debhello-0.2.tar.gz herunter**

```

$ wget http://www.example.org/download/debhello-0.2.tar.gz
...
$ tar -xzmf debhello-0.2.tar.gz
$ tree
.
+-- debhello-0.2
|   +-- README.md
|   +-- data
|       | +-- hello.desktop
|       | +-- hello.png
|   +-- man
|       | +-- hello.1
|   +-- scripts
|       +-- hello
+-- debhello-0.2.tar.gz

5 directories, 6 files

```

Here, the POSIX shell script **hello** is a very simple one.

**hello (v=0.2)**

```

$ cat debhello-0.2/scripts/hello
#!/bin/sh -e
echo "Hello from the shell!"
echo ""
echo -n "Type Enter to exit this program: "
read X

```

Here, **hello.desktop** supports the “[Desktop Entry Specification](#)”.

**hello.desktop (v=0.2)**

```
$ cat debhello-0.2/data/hello.desktop
[Desktop Entry]
Name=Hello
Name[fr]=Bonjour
Comment=Greetings
Comment[fr]=Salutations
Type=Application
Keywords=hello
Exec=hello
Terminal=true
Icon=hello.png
Categories=Utility;
```

Here, **hello.png** is the icon graphics file.

Let's package this with the **debmake** command. Here, the **-b':sh'** option is used to specify that the generated binary package is a shell script.

```
$ cd /path/to/debhello-0.2
$ debmake -b':sh' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="0.2", rev="1"
I: *** start packaging in "debhello-0.2". ***
I: provide debhello_0.2.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-0.2.tar.gz debhello_0.2.orig.tar.gz
I: pwd = "/path/to/debhello-0.2"
I: parse binary package settings: :sh
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: analyze the source tree
I: build_type = Unknown
I: scan source for copyright+license text and file extensions
I: 25 %, ext = md
...
```

Let's inspect notable template files generated.

**The source tree after the basic debmake execution. (v=0.2)**

```
$ cd /path/to
$ tree
.
+-- debhello-0.2
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- debian
|       |   +-- README.Debian
|       |   +-- README.source
|       |   +-- changelog
|       |   +-- clean
|       |   +-- control
|       |   +-- copyright
|       |   +-- dirs
|       |   +-- gbp.conf
|       |   +-- install
|       |   +-- links
|       |   +-- patches
|       |       |   +-- series
|       |   +-- rules
|       |   +-- salsa-ci.yml
|       |   +-- source
|       |   +-- format
```

```

| | | +-- local-options.ex
| | | +-- local-patch-header.ex
| | +-- tests
| | | +-- control
| | +-- upstream
| | | +-- metadata
| | +-- watch
| +-- man
| | +-- hello.1
| +-- scripts
| +-- hello
+-- debhello-0.2.tar.gz
+-- debhello_0.2.orig.tar.gz -> debhello-0.2.tar.gz

10 directories, 26 files

```

#### debian/rules (Vorlagendatei, v=0.2):

```

$ cd /path/to/debhello-0.2
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1

%:
    dh $@

```

This is essentially the standard **debian/rules** file with the **dh** command. Since this is the script package, this template **debian/rules** file has no build flag related contents.

#### debian/control (Vorlagendatei, v=0.2):

```

$ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/debhello

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: ${misc:Depends}
Description: auto-generated package by debmake
 This Debian binary package was auto-generated by the
 debmake(1) command provided by the debmake package.

```

Since this is the shell script package, the **debmake** command sets “**Architecture: all**” and “**Multi-Arch: foreign**”. Also, it sets required **substvar** parameters as “**Depends: \${misc:Depends}**”. These are explained in “Chapter 6”.

Since this upstream source lacks the upstream **Makefile**, that functionality needs to be provided by the maintainer. This upstream source contains only a script file and data files and no C source files; the **build** process can be skipped but the **install** process needs to be implemented. For this case, this is achieved cleanly by adding the **debian/install** and **debian/manpages** files without complicating the **debian/rules** file.

Let’s make this Debian package better as the maintainer.

#### debian/rules (Betreuerversion, v=0.2):

```

$ cd /path/to/debhello-0.2
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules

```

```
#!/usr/bin/make -f
export DH_VERBOSE = 1
```

```
%:
    dh $@
```

#### debian/control (Betreuerversion, v=0.2):

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: ${misc:Depends}
Description: Simple packaging example for debmake
 This Debian binary package is an example package.
 (This is an example only)
```

#### Warning



If you leave “**Section: unknown**” in the template **debian/control** file unchanged, the **lintian** error may cause a build failure.

#### debian/install (Betreuerversion, v=0.2):

```
$ vim debian/install
... hack, hack, hack, ...
$ cat debian/install
data/hello.desktop usr/share/applications
data/hello.png usr/share/pixmaps
scripts/hello usr/bin
```

#### debian/manpages (Betreuerversion, v=0.2):

```
$ vim debian/manpages
... hack, hack, hack, ...
$ cat debian/manpages
man/hello.1
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

#### Vorlagendateien unter debian/. (v=0.2):

```
$ rm -f debian/clean debian/dirs debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
```

```
+-- copyright
+-- gbp.conf
+-- install
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch
```

4 directories, 13 files

You can create a non-native Debian package using the **debuild** command (or its equivalents) in this source tree. The command output is very verbose and explains what it does as follows.

```
$ cd /path/to/debhello-0.2
$ debuild
dpkg-buildpackage -us -uc -ui -i
dpkg-buildpackage: info: source package debhello
dpkg-buildpackage: info: source version 0.2-1
dpkg-buildpackage: info: source distribution unstable
dpkg-buildpackage: info: source changed by Osamu Aoki <osamu@debian.org>
dpkg-source -i --before-build .
dpkg-buildpackage: info: host architecture amd64
debian/rules clean
dh clean
  dh_clean
    rm -f debian/debhelper-build-stamp
  ...
debian/rules binary
dh binary
  dh_update_autotools_config
  dh_autoreconf
  create-stamp debian/debhelper-build-stamp
  dh_prep
    rm -f -- debian/debhello.substvars
    rm -fr -- debian/.debhelper/generated/debhello/ debian/debhello/ debi...
  dh_auto_install --destdir=debian/debhello/
  ...
Finished running lintian.
```

Lassen Sie uns die Ergebnisse anschauen.

**The generated files of debhello version 0.2 by the debuild command:**

```
$ cd /path/to
$ tree -FL 1
./
+-- debhello-0.2/
+-- debhello-0.2.tar.gz
+-- debhello_0.2-1.debian.tar.xz
+-- debhello_0.2-1.dsc
+-- debhello_0.2-1_all.deb
+-- debhello_0.2-1_amd64.build
+-- debhello_0.2-1_amd64.buildinfo
+-- debhello_0.2-1_amd64.changes
+-- debhello_0.2.orig.tar.gz -> debhello-0.2.tar.gz
```

2 directories, 8 files

You see all the generated files.

- The **debhello\_0.2.orig.tar.gz** file is a symlink to the upstream tarball.

- The **debhello\_0.2-1.debian.tar.xz** file contains the maintainer generated contents.
- The **debhello\_0.2-1.dsc** file is the meta data file for the Debian source package.
- Die Datei **debhello\_0.2-1\_all.deb** ist das Debian-Binärpaket.
- The **debhello\_0.2-1\_amd64.build** file is the build log file.
- The **debhello\_0.2-1\_amd64.buildinfo** file is the meta data file generated by **dpkg-genbuildinfo(1)**.
- The **debhello\_0.2-1\_amd64.changes** file is the meta data file for the Debian binary package.

The **debhello\_0.2-1.debian.tar.xz** file contains the Debian changes to the upstream source as follows.

**The compressed archive contents of debhello\_0.2-1.debian.tar.xz:**

```
$ tar -tzf debhello-0.2.tar.gz
debhello-0.2/
debhello-0.2/data/
debhello-0.2/data/hello.desktop
debhello-0.2/data/hello.png
debhello-0.2/man/
debhello-0.2/man/hello.1
debhello-0.2/scripts/
debhello-0.2/scripts/hello
debhello-0.2/README.md
$ tar --xz -tf debhello_0.2-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/gbp.conf
debian/install
debian/manpages
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/tests/
debian/tests/control
debian/upstream/
debian/upstream/metadata
debian/watch
```

The **debhello\_0.2-1\_amd64.deb** file contains the files to be installed as follows.

**The binary package contents of debhello\_0.2-1\_all.deb:**

```
$ dpkg -c debhello_0.2-1_all.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/bin/
-rwxr-xr-x root/root ... ./usr/bin/hello
drwxr-xr-x root/root ... ./usr/share/
drwxr-xr-x root/root ... ./usr/share/applications/
-rw-r--r-- root/root ... ./usr/share/applications/hello.desktop
drwxr-xr-x root/root ... ./usr/share/doc/
drwxr-xr-x root/root ... ./usr/share/doc/debhello/
-rw-r--r-- root/root ... ./usr/share/doc/debhello/README.Debian
-rw-r--r-- root/root ... ./usr/share/doc/debhello/changelog.Debian.gz
-rw-r--r-- root/root ... ./usr/share/doc/debhello/copyright
drwxr-xr-x root/root ... ./usr/share/man/
drwxr-xr-x root/root ... ./usr/share/man/man1/
-rw-r--r-- root/root ... ./usr/share/man/man1/hello.1.gz
drwxr-xr-x root/root ... ./usr/share/pixmaps/
-rw-r--r-- root/root ... ./usr/share/pixmaps/hello.png
```

Dies ist die erstellte Abhängigkeitsliste von **debhello\_0.2-1\_all.deb**.

**The generated dependency list of debhello\_0.2-1\_all.deb:**

```
$ dpkg -f debhello_0.2-1_all.deb pre-depends \
    depends recommends conflicts breaks
```

(No extra dependency packages required since this is a POSIX shell program.)

#### Note



If you wish to replace upstream provided PNG file **data/hello.png** with maintainer provided one **debian/hello.png**, editing **debian/install** isn't enough. When you add **debian/hello.png**, you need to add a line "include-binaries" to **debian/source/options** since PNG is a binary file. See **dpkg-source(1)**.

## 13.3 Makefile (Shell, CLI)

Here is an example of creating a simple Debian package from a POSIX shell CLI program using the **Makefile** as its build system.

Let's assume its upstream tarball to be **debhello-1.0.tar.gz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

```
$ tar -xzmf debhello-1.0.tar.gz
$ cd debhello-1.0
$ make install
```

Debian packaging requires changing this "**make install**" process to install files to the target system image location instead of the normal location under **/usr/local**.

Let's get the source and make the Debian package.

**Laden Sie debhello-1.0.tar.gz herunter**

```
$ wget http://www.example.org/download/debhello-1.0.tar.gz
...
$ tar -xzmf debhello-1.0.tar.gz
$ tree
.
+-- debhello-1.0
|   +-- Makefile
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- hello.1
|   +-- scripts
|       +-- hello
+-- debhello-1.0.tar.gz

5 directories, 7 files
```

Here, the **Makefile** uses **\$(DESTDIR)** and **\$(prefix)** properly. All other files are the same as in "Section 13.2" and most of the packaging activities are the same.

**Makefile (v=1.0)**

```
$ cat debhello-1.0/Makefile
prefix = /usr/local

all:
    : # do nothing

install:
```



```

install -D scripts/hello \
        $(DESTDIR)$(prefix)/bin/hello
install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    : # do nothing

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop
    -rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    -rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1

.PHONY: all install clean distclean uninstall

```

Let's package this with the **debmake** command. Here, the **-b':sh'** option is used to specify that the generated binary package is a shell script.

```

$ cd /path/to/debhello-1.0
$ debmake -b':sh' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.0", rev="1"
I: *** start packaging in "debhello-1.0". ***
I: provide debhello_1.0.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.0.tar.gz debhello_1.0.orig.tar.gz
I: pwd = "/path/to/debhello-1.0"
I: parse binary package settings: :sh
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: analyze the source tree
I: build_type = make
I: scan source for copyright+license text and file extensions
I: 25 %, ext = md
...

```

Let's inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=1.0):**

```

$ cd /path/to/debhello-1.0
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1

%:
    dh $@

#override_dh_auto_install:
#    dh_auto_install -- prefix=/usr

#override_dh_install:
#    dh_install --list-missing -X.pyc -X.pyo

```

Let's make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=1.0):**

```
$ cd /path/to/debhello-1.0
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1

%:
    dh $@

override_dh_auto_install:
    dh_auto_install -- prefix=/usr
```

Since this upstream source has the proper upstream **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

The **debian/control** file is exactly the same as the one in “Section 13.2”.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

**Vorlagendateien unter debian/. (v=1.0):**

```
$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 11 files
```

The rest of the packaging activities are practically the same as the ones in “Section 13.2”.

## 13.4 pyproject.toml (Python3, CLI)

Here is an example of creating a simple Debian package from a Python3 CLI program using **pyproject.toml**.

Let’s get the source and make the Debian package.

**Laden Sie debhello-1.1.tar.gz herunter**

```
$ wget http://www.example.org/download/debhello-1.1.tar.gz
...
$ tar -xzmf debhello-1.1.tar.gz
$ tree
.
+-- debhello-1.1
|   +-- LICENSE
|   +-- MANIFEST.in
|   +-- README.md
|   +-- data
|   |   +-- hello.desktop
|   |   +-- hello.png
|   +-- manpages
```

```
| | +-- hello.1
| +-- pyproject.toml
| +-- src
|     +-- debhello
|         +-- __init__.py
|         +-- main.py
+-- debhello-1.1.tar.gz
```

6 directories, 10 files

Here, the content of this **debhello** source tree as follows.

#### **pyproject.toml (v=1.1) — PEP 517 configuration**

```
$ cat debhello-1.1/pyproject.toml
[build-system]
requires = ["setuptools >= 61.0"] # REQUIRED if [build-system] table is used...
build-backend = "setuptools.build_meta" # If not defined, then legacy behavi...

[project]
name = "debhello"
version = "1.1.0"
description = "Hello Python (CLI)"
readme = {file = "README.md", content-type = "text/markdown"}
requires-python = ">=3.12"
license = {file = "LICENSE.txt"}
keywords = ["debhello"]
authors = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
maintainers = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
classifiers = [
    "Development Status :: 5 - Production/Stable",
    "Intended Audience :: Developers",
    "Topic :: System :: Archiving :: Packaging",
    "License :: OSI Approved :: MIT License",
    "Programming Language :: Python :: 3",
    "Programming Language :: Python :: 3.12",
    "Programming Language :: Python :: 3 :: Only",
    # Others
    "Operating System :: POSIX :: Linux",
    "Natural Language :: English",
]
[project.urls]
"Homepage" = "https://salsa.debian.org/debian/debmake"
"Bug Reports" = "https://salsa.debian.org/debian/debmake/issues"
"Source" = "https://salsa.debian.org/debian/debmake"
[project.scripts]
hello = "debhello.main:main"
[tool.setuptools]
package-dir = {"" = "src"}
packages = ["debhello"]
include-package-data = true
```

#### **MANIFEST.in (v=1.1) — for tar-ball.**

```
$ cat debhello-1.1/MANIFEST.in
include data/*
include manpages/*
```

#### **src/debhello/\_\_init\_\_.py (v=1.1)**

```
$ cat debhello-1.1/src/debhello/__init__.py
"""
debhello program (CLI)
```

```

"""

src/debhello/main.py (v=1.1) — command entry point

$ cat debhello-1.1/src/debhello/main.py
"""
debhello program
"""

import sys

__version__ = '1.1.0'

def main(): # needed for console script
    print(' ===== Hello Python3 =====')
    print('argv = {}'.format(sys.argv))
    print('version = {}'.format(debhello.__version__))
    return

if __name__ == "__main__":
    sys.exit(main())

```

Let's package this with the **debmake** command. Here, the **-b':py3'** option is used to specify the generated binary package containing Python3 script and module files.

```

$ cd /path/to/debhello-1.1
$ debmake -b':py3' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.1", rev="1"
I: *** start packaging in "debhello-1.1". ***
I: provide debhello_1.1.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.1.tar.gz debhello_1.1.orig.tar.gz
I: pwd = "/path/to/debhello-1.1"
I: parse binary package settings: :py3
I: binary package=debhello Type=python3 / Arch=all M-A=foreign
I: analyze the source tree
W: setuptools build system.
I: build_type = Python (pyproject.toml: PEP-518, PEP-621, PEP-660)
I: scan source for copyright+license text and file extensions
...

```

Let's inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=1.1):**

```

$ cd /path/to/debhello-1.1
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1

%:
    dh $@ --with python3 --buildsystem=pybuild

```

This is essentially the standard **debian/rules** file with the **dh** command.

The use of the **--with python3** option invokes **dh\_python3** to calculate Python dependencies, add maintainer scripts to byte compiled files, etc. See **dh\_python3(1)**.

The use of the **--buildsystem=pybuild** option invokes various build systems for requested Python versions in order to build modules and extensions. See **pybuild(1)**.

**debian/control (Vorlagendatei, v=1.1):**

```

$ cat debian/control
Source: debhello

```

```

Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends: debhelper-compat (= 13),
               dh-python,
               pybuild-plugin-pyproject,
               python3-all,
               python3-setuptools
Standards-Version: 4.6.2
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/debhello
#X-Python3-Version: >= 3.7

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: ${misc:Depends}, ${python3:Depends}
Description: auto-generated package by debmake
 This Debian binary package was auto-generated by the
 debmake(1) command provided by the debmake package.

```

Since this is the Python3 package, the **debmake** command sets “**Architecture: all**” and “**Multi-Arch: foreign**”. Also, it sets required **substvar** parameters as “**Depends: \${python3:Depends}, \${misc:Depends}**”. These are explained in “Chapter 6”.

Let’s make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=1.1):**

```

$ cd /path/to/debhello-1.1
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export PYBUILD_NAME=debhello
export PYBUILD_VERBOSE=1
export DH_VERBOSE=1

%:
    dh $@ --with python3 --buildsystem=pybuild

```

**debian/control (Betreuerversion, v=1.1):**

```

$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13),
               pybuild-plugin-pyproject,
               python3-all
Standards-Version: 4.6.2
Rules-Requires-Root: no
Vcs-Browser: https://salsa.debian.org/debian/debmake-doc
Vcs-Git: https://salsa.debian.org/debian/debmake-doc.git
Homepage: https://salsa.debian.org/debian/debmake-doc

Package: debhello
Architecture: all
Depends: ${misc:Depends}, ${python3:Depends}
Description: Simple packaging example for debmake
 This is an example package to demonstrate Debian packaging using
 the debmake command.

```

```
.
The generated Debian package uses the dh command offered by the
debhelper package and the dpkg source format `3.0 (quilt)'.
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

This **debhello** command comes with the upstream-provided manpage and desktop file but the upstream **pyproject.toml** doesn't install them. So you need to update **debian/install** and **debian/manpages** as follows:

**debian/install (Betreuerversion, v=1.1):**

```
$ vim debian/copyright
... hack, hack, hack, ...
$ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright: 2015-2024 Osamu Aoki <osamu@debian.org>
License:    Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

**debian/manpages (Betreuerversion, v=1.1):**

```
$ vim debian/install
... hack, hack, hack, ...
$ cat debian/install
data/hello.desktop usr/share/applications
data/hello.png usr/share/pixmaps
```

The rest of the packaging activities are practically the same as the ones in “Section 13.3”.

**Vorlagendateien unter debian/. (v=1.1):**

```
$ rm -f debian/clean debian/dirs debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- install
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
```

```
|  +-- format
+-- tests/
|  +-- control
+-- upstream/
|  +-- metadata
+-- watch

4 directories, 13 files
```

Hier ist die erstellte Abhängigkeitsliste von **debhello\_1.1-1\_all.deb**.

**The generated dependency list of debhello\_1.1-1\_all.deb:**

```
$ dpkg -f debhello_1.1-1_all.deb pre-depends \
    depends recommends conflicts breaks
Depends: python3:any
```

## 13.5 Makefile (Shell, GUI)

Here is an example of creating a simple Debian package from a POSIX shell GUI program using the **Makefile** as its build system.

This upstream is based on “Section 13.3” with enhanced GUI support.

Let’s assume its upstream tarball to be **debhello-1.2.tar.gz**.

Let’s get the source and make the Debian package.

**Laden Sie debhello-1.2.tar.gz herunter**

```
$ wget http://www.example.org/download/debhello-1.2.tar.gz
...
$ tar -xzmf debhello-1.2.tar.gz
$ tree
.
+-- debhello-1.2
|  +-- Makefile
|  +-- README.md
|  +-- data
|  |  +-- hello.desktop
|  |  +-- hello.png
|  +-- man
|  |  +-- hello.1
|  +-- scripts
|  +-- hello
+-- debhello-1.2.tar.gz

5 directories, 7 files
```

Here, the **hello** has been re-written to use the **zenity** command to make this a GTK+ GUI program.

**hello (v=1.2)**

```
$ cat debhello-1.2/scripts/hello
#!/bin/sh -e
zenity --info --title "hello" --text "Hello from the shell!"
```

Here, the desktop file is updated to be **Terminal=false** as a GUI program.

**hello.desktop (v=1.2)**

```
$ cat debhello-1.2/data/hello.desktop
[Desktop Entry]
Name=Hello
Name[fr]=Bonjour
Comment=Greetings
Comment[fr]=Salutations
Type=Application
Keywords=hello
Exec=hello
```

```
Terminal=false
Icon=hello.png
Categories=Utility;
```

Alle anderen Dateien sind identisch zu “Section 13.3”.

Let’s package this with the **debmake** command. Here, the “-b’:sh’” option is used to specify that the generated binary package is a shell script.

```
$ cd /path/to/debhello-1.2
$ debmake -b':sh' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.2", rev="1"
I: *** start packaging in "debhello-1.2". ***
I: provide debhello_1.2.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.2.tar.gz debhello_1.2.orig.tar.gz
I: pwd = "/path/to/debhello-1.2"
I: parse binary package settings: :sh
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: analyze the source tree
I: build_type = make
I: scan source for copyright+license text and file extensions
I: 25 %, ext = md
...
```

Let’s inspect the notable template files generated.

**debian/control (Vorlagendatei, v=1.2):**

```
$ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/debhello

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: ${misc:Depends}
Description: auto-generated package by debmake
 This Debian binary package was auto-generated by the
 debmake(1) command provided by the debmake package.
```

Let’s make this Debian package better as the maintainer.

**debian/control (Betreuerversion, v=1.2):**

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no
```



```

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: zenity, ${misc:Depends}
Description: Simple packaging example for debmake
 This Debian binary package is an example package.
 (This is an example only)

```

Please note the manually added **zenity** dependency.

The **debian/rules** file is exactly the same as the one in “Section 13.3”.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

**Template files under debian/. (v=1.2):**

```

$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 11 files

```

Die restlichen Paketieraktivitäten sind praktisch die gleichen wie in “Section 13.3”.

Hier ist die erstellte Abhängigkeitsliste von **debhello\_1.2-1\_all.deb**.

**The generated dependency list of debhello\_1.2-1\_all.deb:**

```

$ dpkg -f debhello_1.2-1_all.deb pre-depends \
    depends recommends conflicts breaks
Depends: zenity

```

## 13.6 pyproject.toml (Python3, GUI)

Here is an example of creating a simple Debian package from a Python3 GUI program using **pyproject.toml**.

Let’s assume this upstream tarball to be **debhello-1.3.tar.gz**.

Let’s get the source and make the Debian package.

**Download debhello-1.3.tar.gz**

```

$ wget http://www.example.org/download/debhello-1.3.tar.gz
...
$ tar -xzmf debhello-1.3.tar.gz
$ tree
.
+-- debhello-1.3
|   +-- LICENSE
|   +-- MANIFEST.in
|   +-- README.md
|   +-- data
|       +-- hello.desktop
|       +-- hello.png

```

```
| +-- manpages
| | +-- hello.1
| +-- pyproject.toml
| +-- src
|     +-- debhello
|         +-- __init__.py
|         +-- main.py
+-- debhello-1.3.tar.gz
```

6 directories, 10 files

Here, the content of this **debhello** source tree as follows.

#### **pyproject.toml (v=1.3) — PEP 517 configuration**

```
$ cat debhello-1.3/pyproject.toml
[build-system]
requires = ["setuptools >= 61.0"] # REQUIRED if [build-system] table is used...
build-backend = "setuptools.build_meta" # If not defined, then legacy behavi...

[project]
name = "debhello"
version = "1.3.0"
description = "Hello Python (GUI)"
readme = {file = "README.md", content-type = "text/markdown"}
requires-python = ">=3.12"
license = {file = "LICENSE.txt"}
keywords = ["debhello"]
authors = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
maintainers = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
classifiers = [
    "Development Status :: 5 - Production/Stable",
    "Intended Audience :: Developers",
    "Topic :: System :: Archiving :: Packaging",
    "License :: OSI Approved :: MIT License",
    "Programming Language :: Python :: 3",
    "Programming Language :: Python :: 3.12",
    "Programming Language :: Python :: 3 :: Only",
    # Others
    "Operating System :: POSIX :: Linux",
    "Natural Language :: English",
]
[project.urls]
"Homepage" = "https://salsa.debian.org/debian/debmake"
"Bug Reports" = "https://salsa.debian.org/debian/debmake/issues"
"Source" = "https://salsa.debian.org/debian/debmake"
[project.scripts]
hello = "debhello.main:main"
[tool.setuptools]
package-dir = {"" = "src"}
packages = ["debhello"]
include-package-data = true
```

#### **MANIFEST.in (v=1.3) — for tar-ball.**

```
$ cat debhello-1.3/MANIFEST.in
include data/*
include manpages/*
```

#### **src/debhello/\_\_init\_\_.py (v=1.3)**

```
$ cat debhello-1.3/src/debhello/__init__.py
"""
```

```
debhello program (GUI)
"""
```

#### src/debhello/main.py (v=1.3) — command entry point

```
$ cat debhello-1.3/src/debhello/main.py
#!/usr/bin/python3
from gi.repository import Gtk

__version__ = '1.3.0'

class TopWindow(Gtk.Window):

    def __init__(self):
        Gtk.Window.__init__(self)
        self.title = "Hello World!"
        self.counter = 0
        self.border_width = 10
        self.set_default_size(400, 100)
        self.set_position(Gtk.WindowPosition.CENTER)
        self.button = Gtk.Button(label="Click me!")
        self.button.connect("clicked", self.on_button_clicked)
        self.add(self.button)
        self.connect("delete-event", self.on_window_destroy)

    def on_window_destroy(self, *args):
        Gtk.main_quit(*args)

    def on_button_clicked(self, widget):
        self.counter += 1
        widget.set_label("Hello, World!\nClick count = %i" % self.counter)

def main():
    window = TopWindow()
    window.show_all()
    Gtk.main()

if __name__ == '__main__':
    main()
```

Let's package this with the **debmake** command. Here, the **-b':py3'** option is used to specify that the generated binary package contains Python3 script and module files.

```
$ cd /path/to/debhello-1.3
$ debmake -b':py3' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.3", rev="1"
I: *** start packaging in "debhello-1.3". ***
I: provide debhello_1.3.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.3.tar.gz debhello_1.3.orig.tar.gz
I: pwd = "/path/to/debhello-1.3"
I: parse binary package settings: :py3
I: binary package=debhello Type=python3 / Arch=all M-A=foreign
I: analyze the source tree
W: setuptools build system.
I: build_type = Python (pyproject.toml: PEP-518, PEP-621, PEP-660)
I: scan source for copyright+license text and file extensions
...
```

The result is practically the same as in “Section 13.4”.

Let's make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=1.3):**

```
$ cd /path/to/debhello-1.3
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export PYBUILD_NAME=debhello
export PYBUILD_VERBOSE=1
export DH_VERBOSE=1

%:
    dh $@ --with python3 --buildsystem=pybuild
```

#### debian/control (Betreuerversion, v=1.3):

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13),
               pybuild-plugin-pyproject,
               python3-all
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends: gir1.2-gtk-3.0, python3-gi, ${misc:Depends}, ${python3:Depends}
Description: Simple packaging example for debmake
 This Debian binary package is an example package.
 (This is an example only)
```

Please note the manually added **python3-gi** and **gir1.2-gtk-3.0** dependencies.  
 The rest of the packaging activities are practically the same as in <pyproject>.  
 Hier ist die erstellte Abhängigkeitsliste von **debhello\_1.3-1\_all.deb**.

#### The generated dependency list of debhello\_1.3-1\_all.deb:

```
$ dpkg -f debhello_1.3-1_all.deb pre-depends \
    depends recommends conflicts breaks
Depends: gir1.2-gtk-3.0, python3-gi, python3:any
```

## 13.7 Makefile (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using the **Makefile** as its build system.

This is an enhanced upstream source example for “Chapter 5”. This comes with the manpage, the desktop file, and the desktop icon. This also links to an external library **libm** to be a more practical example.

Let’s assume this upstream tarball to be **debhello-1.4.tar.gz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

```
$ tar -xzmf debhello-1.4.tar.gz
$ cd debhello-1.4
$ make
$ make install
```

Debian packaging requires changing this “**make install**” process to install files into the target system image location instead of the normal location under **/usr/local**.

Let’s get the source and make the Debian package.

**Laden Sie debhello-1.4.tar.gz herunter**

```

$ wget http://www.example.org/download/debhello-1.4.tar.gz
...
$ tar -xzmf debhello-1.4.tar.gz
$ tree
.
+-- debhello-1.4
|   +-- LICENSE
|   +-- Makefile
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- hello.1
|   +-- src
|       +-- config.h
|       +-- hello.c
+-- debhello-1.4.tar.gz

5 directories, 9 files

```

Here, the contents of this source are as follows.

**src/hello.c (v=1.4):**

```

$ cat debhello-1.4/src/hello.c
#include "config.h"
#include <math.h>
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\\n");
    printf("4.0 * atan(1.0) = %10f8\\n", 4.0*atan(1.0));
    return 0;
}

```

**src/config.h (v=1.4):**

```

$ cat debhello-1.4/Makefile
prefix = /usr/local

all: src/hello

src/hello: src/hello.c
    $(CC) $(CPPFLAGS) $(CFLAGS) $(LDFLAGS) -o $@ $^ -lm

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello
    install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
    install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop

```

```
-rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
-rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1
```

```
.PHONY: all install clean distclean uninstall
```

#### Makefile (v=1.4):

```
$ cat debhello-1.4/src/config.h
#define PACKAGE_AUTHOR "Osamu Aoki"
```

Please note that this **Makefile** has the proper **install** target for the manpage, the desktop file, and the desktop icon.

Let's package this with the **debmake** command.

```
$ cd /path/to/debhello-1.4
$ debmake -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.4", rev="1"
I: *** start packaging in "debhello-1.4". ***
I: provide debhello_1.4.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.4.tar.gz debhello_1.4.orig.tar.gz
I: pwd = "/path/to/debhello-1.4"
I: parse binary package settings:
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: analyze the source tree
I: build_type = make
I: scan source for copyright+license text and file extensions
I: 33 %, ext = c
...
```

The result is practically the same as in “Section 5.6”.

Let's make this Debian package, which is practically the same as in “Section 5.7”, better as the maintainer.

If the **DEB\_BUILD\_MAINT\_OPTIONS** environment variable is not exported in **debian/rules**, lintian warns “W: debhello: hardening-no-relro usr/bin/hello” for the linking of **libm**.

The **debian/control** file makes it exactly the same as the one in “Section 5.7”, since the **libm** library is always available as a part of **libc6** (Priority: required).

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

#### Vorlagendateien unter debian/. (v=1.4):

```
$ rm -f debian/clean debian/dirs debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- gbp.conf
+-- install
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 12 files
```

The rest of the packaging activities are practically the same as the one in “Section 5.8”.

Here is the generated dependency list of all binary packages.

**Die erstellte Abhängigkeitsliste aller Binärpakete (v=1.4):**

```
$ dpkg -f debhello-dbgSYM_1.4-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: debhello (= 1.4-1)
$ dpkg -f debhello_1.4-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libc6 (>= 2.34)
```

## 13.8 Makefile.in + configure (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using **Makefile.in** and **configure** as its build system.

This is an enhanced upstream source example for “Section 13.7”. This also links to an external library, **libm**, and this source is configurable using arguments to the **configure** script, which generates the **Makefile** and **src/config.h** files.

Nehmen wir an, dass der Tarball der Originalautoren **debhello-1.5.tar.gz** ist.

This type of source is meant to be installed as a non-system file, for example, as:

```
$ tar -xzf debhello-1.5.tar.gz
$ cd debhello-1.5
$ ./configure --with-math
$ make
$ make install
```

Let’s get the source and make the Debian package.

**Laden Sie debhello-1.5.tar.gz herunter**

```
$ wget http://www.example.org/download/debhello-1.5.tar.gz
...
$ tar -xzf debhello-1.5.tar.gz
$ tree
.
+-- debhello-1.5
|   +-- LICENSE
|   +-- Makefile.in
|   +-- README.md
|   +-- configure
|   +-- data
|       | +-- hello.desktop
|       | +-- hello.png
|   +-- man
|       | +-- hello.1
|   +-- src
|       +-- hello.c
+-- debhello-1.5.tar.gz

5 directories, 9 files
```

Here, the contents of this source are as follows.

**src/hello.c (v=1.5):**

```
$ cat debhello-1.5/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
int
main()
{
```

```

    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\n");
#endif
    return 0;
}

```

**Makefile.in (v=1.5):**

```

$ cat debhello-1.5/Makefile.in
prefix = @prefix@

all: src/hello

src/hello: src/hello.c
    $(CC) @VERBOSE@ \
        $(CPPFLAGS) \
        $(CFLAGS) \
        $(LDFLAGS) \
        -o $@ $^ \
        @LINKLIB@

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello
    install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
    install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop
    -rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    -rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1

.PHONY: all install clean distclean uninstall

```

**configure (v=1.5):**

```

$ cat debhello-1.5/configure
#!/bin/sh -e
# default values
PREFIX="/usr/local"
VERBOSE=""
WITH_MATH="0"
LINKLIB=""
PACKAGE_AUTHOR="John Doe"

# parse arguments
while [ "${1}" != "" ]; do
    VAR="${1%=*}" # Drop suffix =*
    VAL="${1#*=}" # Drop prefix *=
    case "${VAR}" in
        --prefix)
            PREFIX="${VAL}"

```



```

;;
--verbose|-v)
    VERBOSE="-v"
;;
--with-math)
    WITH_MATH="1"
    LINKLIB="-lm"
;;
--author)
    PACKAGE_AUTHOR="${VAL}"
;;
*)
    echo "W: Unknown argument: ${1}"
esac
shift
done

# setup configured Makefile and src/config.h
sed -e "s,@prefix@,{PREFIX}," \
    -e "s,@VERBOSE@,{VERBOSE}," \
    -e "s,@LINKLIB@,{LINKLIB}," \
    <Makefile.in >Makefile
if [ "${WITH_MATH}" = 1 ]; then
echo "#define WITH_MATH" >src/config.h
else
echo "/* not defined: WITH_MATH */" >src/config.h
fi
echo "#define PACKAGE_AUTHOR \"${PACKAGE_AUTHOR}\"" >>src/config.h

```

Please note that the **configure** command replaces strings with **@...@** in **Makefile.in** to produce **Makefile** and creates **src/config.h**.

Let's package this with the **debmake** command.

```

$ cd /path/to/debhello-1.5
$ debmake -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.5", rev="1"
I: *** start packaging in "debhello-1.5". ***
I: provide debhello_1.5.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.5.tar.gz debhello_1.5.orig.tar.gz
I: pwd = "/path/to/debhello-1.5"
I: parse binary package settings:
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: analyze the source tree
I: build_type = configure
I: scan source for copyright+license text and file extensions
I: 17 %, ext = in
...

```

Das Ergebnis ist ähnlich zu "Section 5.6", aber nicht exakt identisch.

Let's inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=1.5):**

```

$ cd /path/to/debhello-1.5
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1

```

```
%:
    dh $@

Let's make this Debian package better as the maintainer.
debian/rules (Betreuerversion, v=1.5):

$ cd /path/to/debhello-1.5
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- \
        --with-math \
        --author="Osamu Aoki"
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in “Section 5.8”.

## 13.9 Autotools (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using Autotools = Autoconf and Automake (**Makefile.am** and **configure.ac**) as its build system.

This source usually comes with the upstream auto-generated **Makefile.in** and **configure** files, too. This source can be packaged using these files as in “Section 13.8” with the help of the **autotools-dev** package.

The better alternative is to regenerate these files using the latest Autoconf and Automake packages if the upstream provided **Makefile.am** and **configure.ac** are compatible with the latest version. This is advantageous for porting to new CPU architectures, etc. This can be automated by using the “**--with autoreconf**” option for the **dh** command.

Let's assume this upstream tarball to be **debhello-1.6.tar.gz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
$ tar -xzmf debhello-1.6.tar.gz
$ cd debhello-1.6
$ autoreconf -ivf # optional
$ ./configure --with-math
$ make
$ make install
```

Let's get the source and make the Debian package.

**Laden Sie debhello-1.6.tar.gz herunter**

```
$ wget http://www.example.org/download/debhello-1.6.tar.gz
...
$ tar -xzmf debhello-1.6.tar.gz
$ tree
.
+-- debhello-1.6
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|   |   +-- hello.desktop
```

```
| | +-- hello.png
| +-- man
| | +-- Makefile.am
| | +-- hello.1
| +-- src
|     +-- Makefile.am
|     +-- hello.c
+-- debhello-1.6.tar.gz
```

5 directories, 11 files

Here, the contents of this source are as follows.

**src/hello.c (v=1.6):**

```
$ cat debhello-1.6/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\\n");
#endif
    return 0;
}
```

**Makefile.am (v=1.6):**

```
$ cat debhello-1.6/Makefile.am
SUBDIRS = src man
$ cat debhello-1.6/man/Makefile.am
dist_man_MANS = hello.1
$ cat debhello-1.6/src/Makefile.am
bin_PROGRAMS = hello
hello_SOURCES = hello.c
```

**configure.ac (v=1.6):**

```
$ cat debhello-1.6/configure.ac
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([debhello],[2.1],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])
AM_INIT_AUTOMAKE([foreign])
# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
echo "Add --with-math option functionality to ./configure"
AC_ARG_WITH([math],
    [AS_HELP_STRING([--with-math],
        [compile with math library @<:@default=yes@:>@])],
    [],
    [with_math="yes"])
echo "==== withval    := \"$withval\""
echo "==== with_math := \"$with_math\""
# m4sh if-else construct
```

```

AS_IF([test "x$with_math" != "xno"],[
  echo "==== Check include: math.h"
  AC_CHECK_HEADER(math.h,[],[
    AC_MSG_ERROR([Couldn't find math.h.] )
  ])
  echo "==== Check library: libm"
  AC_SEARCH_LIBS(atan, [m])
  #AC_CHECK_LIB(m, atan)
  echo "==== Build with LIBS := \"\$LIBS\""
  AC_DEFINE(WITH_MATH, [1], [Build with the math library])
],[
  echo "==== Skip building with math.h."
  AH_TEMPLATE(WITH_MATH, [Build without the math library])
])
# Checks for programs.
AC_PROG_CC
AC_CONFIG_FILES([Makefile
                  man/Makefile
                  src/Makefile])
AC_OUTPUT

```

### Tip



Without “**foreign**” strictness level specified in **AM\_INIT\_AUTOMAKE()** as above, **automake** defaults to “**gnu**” strictness level requiring several files in the top-level directory. See “3.2 Strictness” in the **automake** document.

Let’s package this with the **debmake** command.

```

$ cd /path/to/debhello-1.6
$ debmake -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.6", rev="1"
I: *** start packaging in "debhello-1.6". ***
I: provide debhello_1.6.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.6.tar.gz debhello_1.6.orig.tar.gz
I: pwd = "/path/to/debhello-1.6"
I: parse binary package settings:
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: analyze the source tree
I: build_type = Autotools with autoreconf
I: scan source for copyright+license text and file extensions
I: 33 %, ext = am
...

```

The result is similar to “Section 13.8” but not exactly the same.

Let’s inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=1.6):**

```

$ cd /path/to/debhello-1.6
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1

```

```
%:
    dh $@ --with autoreconf

#override_dh_install:
#    dh_install --list-missing -X.la -X.pyc -X.pyo
```

Let's make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=1.6):**

```
$ cd /path/to/debhello-1.6
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@ --with autoreconf

override_dh_auto_configure:
    dh_auto_configure -- \
        --with-math
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in “Section 5.8”.

## 13.10 CMake (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using CMake (**CMakeLists.txt** and some files such as **config.h.in**) as its build system.

The **cmake** command generates the **Makefile** file based on the **CMakeLists.txt** file and its **-D** option. It also configures the file as specified in its **configure\_file(...)** by replacing strings with **@...@** and changing the **#cmakedefine ...** line.

Let's assume this upstream tarball to be **debhello-1.7.tar.gz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
$ tar -xzf debhello-1.7.tar.gz
$ cd debhello-1.7
$ mkdir obj-x86_64-linux-gnu # for out-of-tree build
$ cd obj-x86_64-linux-gnu
$ cmake ..
$ make
$ make install
```

Let's get the source and make the Debian package.

**Download debhello-1.7.tar.gz**

```
$ wget http://www.example.org/download/debhello-1.7.tar.gz
...
$ tar -xzf debhello-1.7.tar.gz
$ tree
.
+-- debhello-1.7
|   +-- CMakeLists.txt
|   +-- LICENSE
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
```

```
| | +-- CMakeLists.txt
| | +-- hello.1
| +-- src
|     +-- CMakeLists.txt
|     +-- config.h.in
|     +-- hello.c
+-- debhello-1.7.tar.gz
```

5 directories, 11 files

Here, the contents of this source are as follows.

**src/hello.c (v=1.7):**

```
$ cat debhello-1.7/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\n");
#endif
    return 0;
}
```

**src/config.h.in (v=1.7):**

```
$ cat debhello-1.7/src/config.h.in
/* name of the package author */
#define PACKAGE_AUTHOR "@PACKAGE_AUTHOR@"
/* math library support */
#cmakedefine WITH_MATH
```

**CMakeLists.txt (v=1.7):**

```
$ cat debhello-1.7/CMakeLists.txt
cmake_minimum_required(VERSION 2.8)
project(debhello)
set(PACKAGE_AUTHOR "Osamu Aoki")
add_subdirectory(src)
add_subdirectory(man)
$ cat debhello-1.7/man/CMakeLists.txt
install(
  FILES ${CMAKE_CURRENT_SOURCE_DIR}/hello.1
  DESTINATION share/man/man1
)
$ cat debhello-1.7/src/CMakeLists.txt
# Always define HAVE_CONFIG_H
add_definitions(-DHAVE_CONFIG_H)
# Interactively define WITH_MATH
option(WITH_MATH "Build with math support" OFF)
#variable_watch(WITH_MATH)
# Generate config.h from config.h.in
configure_file(
  "${CMAKE_CURRENT_SOURCE_DIR}/config.h.in"
  "${CMAKE_CURRENT_BINARY_DIR}/config.h"
)
include_directories("${CMAKE_CURRENT_BINARY_DIR}")
add_executable(hello hello.c)
install(TARGETS hello
```

```
RUNTIME DESTINATION bin
)
```

Let's package this with the **debmake** command.

```
$ cd /path/to/debhello-1.7
$ debmake -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="1.7", rev="1"
I: *** start packaging in "debhello-1.7". ***
I: provide debhello_1.7.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-1.7.tar.gz debhello_1.7.orig.tar.gz
I: pwd = "/path/to/debhello-1.7"
I: parse binary package settings:
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: analyze the source tree
I: build_type = Cmake
I: scan source for copyright+license text and file extensions
I: 33 %, ext = text
...
```

The result is similar to “Section 13.8” but not exactly the same.

Let's inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=1.7):**

```
$ cd /path/to/debhello-1.7
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1

%:
    dh $@

#override_dh_auto_configure:
#    dh_auto_configure -- \
#        -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_TARGET_MULTIARCH)"
```

**debian/control (template file, v=1.7):**

```
$ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends: cmake, debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/debhello

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: auto-generated package by debmake
    This Debian binary package was auto-generated by the
    debmake(1) command provided by the debmake package.
```

Let's make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=1.7):**

```
$ cd /path/to/debhello-1.7
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- -DWITH-MATH=1
```

**debian/control (Betreuerversion, v=1.7):**

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: cmake, debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: Simple packaging example for debmake
 This Debian binary package is an example package.
 (This is an example only)
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in “Section 13.8”.

## 13.11 Autotools (Paket mit mehreren Programmen)

Here is an example of creating a set of Debian binary packages including the executable package, the shared library package, the development file package, and the debug symbol package from a simple C source program using Autotools = Autoconf and Automake (which use **Makefile.am** and **configure.ac** as their input files) as its build system.

Let's package this in the same way as in “Section 13.9”.

Let's assume this upstream tarball to be **debhello-2.0.tar.gz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
$ tar -xzmf debhello-2.0.tar.gz
$ cd debhello-2.0
$ autoreconf -ivf # optional
$ ./configure --with-math
$ make
$ make install
```

Let's get the source and make the Debian package.

**Download debhello-2.0.tar.gz**



```

$ wget http://www.example.org/download/debhello-2.0.tar.gz
...
$ tar -xzmf debhello-2.0.tar.gz
$ tree
.
+-- debhello-2.0
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- lib
|       |   +-- Makefile.am
|       |   +-- sharedlib.c
|       |   +-- sharedlib.h
|   +-- man
|       |   +-- Makefile.am
|       |   +-- hello.1
|   +-- src
|       +-- Makefile.am
|       +-- hello.c
+-- debhello-2.0.tar.gz

6 directories, 14 files

```

Here, the contents of this source are as follows.

**src/hello.c (v=2.0):**

```

$ cat debhello-2.0/src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
    sharedlib();
    return 0;
}

```

**lib/sharedlib.h und lib/sharedlib.c (v=1.6):**

```

$ cat debhello-2.0/lib/sharedlib.h
int sharedlib();
$ cat debhello-2.0/lib/sharedlib.c
#include <stdio.h>
int
sharedlib()
{
    printf("This is a shared library!\n");
    return 0;
}

```

**Makefile.am (v=2.0):**

```

$ cat debhello-2.0/Makefile.am
# recursively process `Makefile.am` in SUBDIRS
SUBDIRS = lib src man
$ cat debhello-2.0/man/Makefile.am
# manpages (distributed in the source package)
dist_man_MANS = hello.1
$ cat debhello-2.0/lib/Makefile.am
# libtool libraries to be produced

```

```

lib_LTLIBRARIES = libsharedlib.la

# source files used for lib_LTLIBRARIES
libsharedlib_la_SOURCES = sharedlib.c

# C pre-processor flags used for lib_LTLIBRARIES
#libsharedlib_la_CPPFLAGS =

# Headers files to be installed in <prefix>/include
include_HEADERS = sharedlib.h

# Versioning Libtool Libraries with version triplets
libsharedlib_la_LDFLAGS = -version-info 1:0:0
$ cat debhello-2.0/src/Makefile.am
# program executables to be produced
bin_PROGRAMS = hello

# source files used for bin_PROGRAMS
hello_SOURCES = hello.c

# C pre-processor flags used for bin_PROGRAMS
AM_CPPFLAGS = -I$(srcdir) -I$(top_srcdir)/lib

# Extra options for the linker for hello
# hello_LDFLAGS =

# Libraries the `hello` binary to be linked
hello_LDADD = $(top_srcdir)/lib/libsharedlib.la

```

**configure.ac (v=2.0):**

```

$ cat debhello-2.0/configure.ac
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([debhello],[2.2],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])

AM_INIT_AUTOMAKE([foreign])

# Set default to --enable-shared --disable-static
LT_INIT([shared disable-static])

# find the libltdl sources in the libltdl sub-directory
LT_CONFIG_LTDL_DIR([libltdl])

# choose one
LTDL_INIT([recursive])
#LTDL_INIT([subproject])
#LTDL_INIT([nonrecursive])

# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
# Checks for programs.
AC_PROG_CC

# only for the recursive case
AC_CONFIG_FILES([Makefile
                 lib/Makefile
                 man/Makefile
                 src/Makefile])

```

## AC\_OUTPUT

Let's package this with the **debmake** command into multiple packages:

- **debhello**: type = **bin**
- **libsharedlib1**: type = **lib**
- **libsharedlib-dev**: type = **dev**

Here, the **-b',libsharedlib1,libsharedlib-dev'** option is used to specify the generated binary packages.

```
$ cd /path/to/debhello-2.0
$ debmake -b',libsharedlib1,libsharedlib-dev' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="2.0", rev="1"
I: *** start packaging in "debhello-2.0". ***
I: provide debhello_2.0.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-2.0.tar.gz debhello_2.0.orig.tar.gz
I: pwd = "/path/to/debhello-2.0"
I: parse binary package settings: ,libsharedlib1,libsharedlib-dev
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: binary package=libsharedlib1 Type=lib / Arch=any M-A=same
I: binary package=libsharedlib-dev Type=dev / Arch=any M-A=same
I: analyze the source tree
I: build_type = Autotools with autoreconf
...
```

The result is similar to “Section 13.8” but with more template files.

Let's inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=2.0):**

```
$ cd /path/to/debhello-2.0
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1

%:
    dh $@ --with autoreconf

#override_dh_install:
#    dh_install --list-missing -X.la -X.pyc -X.pyo
```

Let's make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=2.0):**

```
$ cd /path/to/debhello-2.0
$ vim debian/rules
... hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@ --with autoreconf
```

```
override_dh_missing:
    dh_missing -X.la
```

**debian/control (Betreuerversion, v=2.0):**

```
$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: debhelper-compat (= 13), dh-autoreconf
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends: libsharedlib1 (= ${binary:Version}),
        ${misc:Depends},
        ${shlibs:Depends}
Description: Simple packaging example for debmake
    This package contains the compiled binary executable.
.
    This Debian binary package is an example package.
    (This is an example only)

Package: libsharedlib1
Section: libs
Architecture: any
Multi-Arch: same
Pre-Depends: ${misc:Pre-Depends}
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: Simple packaging example for debmake
    This package contains the shared library.

Package: libsharedlib-dev
Section: libdevel
Architecture: any
Multi-Arch: same
Depends: libsharedlib1 (= ${binary:Version}), ${misc:Depends}
Description: Simple packaging example for debmake
    This package contains the development files.
```

**debian/\*.install (Betreuerversion, v=2.0):**

```
$ vim debian/copyright
... hack, hack, hack, ...
$ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright:  2015-2021 Osamu Aoki <osamu@debian.org>
License:    Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
```

```
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

Since this upstream source creates the proper auto-generated **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

#### **Vorlagendateien unter debian/. (v=2.0):**

```
$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ rm -rf debian/patches
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- debhello.dirs
+-- debhello.doc-base
+-- debhello.docs
+-- debhello.examples
+-- debhello.info
+-- debhello.install
+-- debhello.links
+-- debhello.manpages
+-- gbp.conf
+-- libsharedlib-dev.install
+-- libsharedlib1.install
+-- libsharedlib1.symbols
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 22 files
```

The rest of the packaging activities are practically the same as the one in “Section 13.8”.

Here are the generated dependency list of all binary packages.

#### **The generated dependency list of all binary packages (v=2.0):**

```
$ dpkg -f debhello-dbgsym_2.0-1_amd64.deb pre-depends \
depends recommends conflicts breaks
Depends: debhello (= 2.0-1)
$ dpkg -f debhello_2.0-1_amd64.deb pre-depends \
depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1), libc6 (>= 2.34)
$ dpkg -f libsharedlib-dev_2.0-1_amd64.deb pre-depends \
depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1)
$ dpkg -f libsharedlib1-dbgsym_2.0-1_amd64.deb pre-depends \
```

```

        depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1)
$ dpkg -f libsharedlib1_2.0-1_amd64.deb pre-depends \
        depends recommends conflicts breaks
Depends: libc6 (>= 2.2.5)

```

## 13.12 CMake (multi-binary package)

Here is an example of creating a set of Debian binary packages including the executable package, the shared library package, the development file package, and the debug symbol package from a simple C source program using CMake (**CMakeLists.txt** and some files such as **config.h.in**) as its build system.

Let's assume this upstream tarball to be **debhhello-2.1.tar.gz**.

This type of source is meant to be installed as a non-system file, for example, as:

```

$ tar -xzf debhhello-2.1.tar.gz
$ cd debhhello-2.1
$ mkdir obj-x86_64-linux-gnu
$ cd obj-x86_64-linux-gnu
$ cmake ..
$ make
$ make install

```

Let's get the source and make the Debian package.

**Download debhhello-2.1.tar.gz**

```

$ wget http://www.example.org/download/debhhello-2.1.tar.gz
...
$ tar -xzf debhhello-2.1.tar.gz
$ tree
.
+-- debhhello-2.1
|   +-- CMakeLists.txt
|   +-- LICENSE
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- lib
|       |   +-- CMakeLists.txt
|       |   +-- sharedlib.c
|       |   +-- sharedlib.h
|   +-- man
|       |   +-- CMakeLists.txt
|       |   +-- hello.1
|   +-- src
|       +-- CMakeLists.txt
|       +-- config.h.in
|       +-- hello.c
+-- debhhello-2.1.tar.gz

6 directories, 14 files

```

Here, the contents of this source are as follows.

**src/hello.c (v=2.1):**

```

$ cat debhhello-2.1/src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
}

```

```

        sharedlib();
        return 0;
}

```

#### src/config.h.in (v=2.1):

```

$ cat debhello-2.1/src/config.h.in
/* name of the package author */
#define PACKAGE_AUTHOR "@PACKAGE_AUTHOR@"

```

#### lib/sharedlib.c und lib/sharedlib.h (v=2.1):

```

$ cat debhello-2.1/lib/sharedlib.h
int sharedlib();
$ cat debhello-2.1/lib/sharedlib.c
#include <stdio.h>
int
sharedlib()
{
    printf("This is a shared library!\n");
    return 0;
}

```

#### CMakeLists.txt (v=2.1):

```

$ cat debhello-2.1/CMakeLists.txt
cmake_minimum_required(VERSION 2.8)
project(debhello)
set(PACKAGE_AUTHOR "Osamu Aoki")
add_subdirectory(lib)
add_subdirectory(src)
add_subdirectory(man)
$ cat debhello-2.1/man/CMakeLists.txt
install(
    FILES ${CMAKE_CURRENT_SOURCE_DIR}/hello.1
    DESTINATION share/man/man1
)
$ cat debhello-2.1/src/CMakeLists.txt
# Always define HAVE_CONFIG_H
add_definitions(-DHAVE_CONFIG_H)
# Generate config.h from config.h.in
configure_file(
    "${CMAKE_CURRENT_SOURCE_DIR}/config.h.in"
    "${CMAKE_CURRENT_BINARY_DIR}/config.h"
)
include_directories("${CMAKE_CURRENT_BINARY_DIR}")
include_directories("${CMAKE_SOURCE_DIR}/lib")

add_executable(hello hello.c)
target_link_libraries(hello sharedlib)
install(TARGETS hello
    RUNTIME DESTINATION bin
)

```

Let's package this with the **debmake** command.

```

$ cd /path/to/debhello-2.1
$ debmake -b',libsharedlib1,libsharedlib-dev' -x1
I: set parameters
...
I: sanity check of parameters
I: pkg="debhello", ver="2.1", rev="1"
I: *** start packaging in "debhello-2.1". ***
I: provide debhello_2.1.orig.tar.gz for non-native Debian package
I: pwd = "/path/to"
I: $ ln -sf debhello-2.1.tar.gz debhello_2.1.orig.tar.gz

```

```

I: pwd = "/path/to/debhello-2.1"
I: parse binary package settings: , libsharedlib1, libsharedlib-dev
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: binary package=libsharedlib1 Type=lib / Arch=any M-A=same
I: binary package=libsharedlib-dev Type=dev / Arch=any M-A=same
I: analyze the source tree
I: build_type = Cmake
...

```

The result is similar to “Section 13.8” but not exactly the same.

Let’s inspect the notable template files generated.

**debian/rules (Vorlagendatei, v=2.1):**

```

$ cd /path/to/debhello-2.1
$ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
#export DH_VERBOSE = 1
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1

%:
    dh $@

#override_dh_auto_configure:
#    dh_auto_configure -- \
#        -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_TARGET_MULTIARCH)"

```

Let’s make this Debian package better as the maintainer.

**debian/rules (Betreuerversion, v=2.1):**

```

$ cd /path/to/debhello-2.1
$ vim debian/rules
... hack, hack, hack, ...
$ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl, --as-needed
DEB_HOST_MULTIARCH ?= $(shell dpkg-architecture -qDEB_HOST_MULTIARCH)

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- \
        -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_HOST_MULTIARCH)"

```

**debian/control (Betreuerversion, v=2.1):**

```

$ vim debian/control
... hack, hack, hack, ...
$ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends: cmake, debhelper-compat (= 13)
Standards-Version: 4.6.2
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello

```



```

Architecture: any
Multi-Arch: foreign
Depends: libsharedlib1 (= ${binary:Version}),
        ${misc:Depends},
        ${shlibs:Depends}
Description: Simple packaging example for debmake
 This package contains the compiled binary executable.
.
 This Debian binary package is an example package.
 (This is an example only)

Package: libsharedlib1
Section: libs
Architecture: any
Multi-Arch: same
Pre-Depends: ${misc:Pre-Depends}
Depends: ${misc:Depends}, ${shlibs:Depends}
Description: Simple packaging example for debmake
 This package contains the shared library.

Package: libsharedlib-dev
Section: libdevel
Architecture: any
Multi-Arch: same
Depends: libsharedlib1 (= ${binary:Version}), ${misc:Depends}
Description: Simple packaging example for debmake
 This package contains the development files.

```

#### **debian/\*.install (Betreuerversion, v=2.1):**

```

$ vim debian/copyright
... hack, hack, hack, ...
$ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright: 2015-2021 Osamu Aoki <osamu@debian.org>
License:    Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

```

This upstream CMakeList.txt needs to be patched to cope with the multiarch path.

#### **debian/patches/\* (Betreuerversion, v=2.1):**

```

... hack, hack, hack, ...
$ cat debian/libsharedlib1.symbols
libsharedlib.so.1 libsharedlib1 #MINVER#

```

sharedlib@Base 2.1

Since this upstream source creates the proper auto-generated **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

**Vorlagendateien unter debian/. (v=2.1):**

```
$ rm -f debian/clean debian/dirs debian/install debian/links
$ rm -f debian/README.source debian/source/*.ex
$ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- debhello.dirs
+-- debhello.doc-base
+-- debhello.docs
+-- debhello.examples
+-- debhello.info
+-- debhello.install
+-- debhello.links
+-- debhello.manpages
+-- gbp.conf
+-- libsharedlib-dev.install
+-- libsharedlib1.install
+-- libsharedlib1.symbols
+-- patches/
|   +-- 000-cmake-multiarch.patch
|   +-- series
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

5 directories, 24 files
```

The rest of the packaging activities are practically the same as the one in “Section 13.8”.

Here are the generated dependency list of all binary packages.

**The generated dependency list of all binary packages (v=2.1):**

```
$ dpkg -f debhello-dbgSYM_2.1-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: debhello (= 2.1-1)
$ dpkg -f debhello_2.1-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1), libc6 (>= 2.34)
$ dpkg -f libsharedlib-dev_2.1-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1)
$ dpkg -f libsharedlib1-dbgSYM_2.1-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1)
$ dpkg -f libsharedlib1_2.1-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libc6 (>= 2.2.5)
```

## 13.13 Internationalization

Here is an example of updating the simple upstream C source **debhello-2.0.tar.gz** presented in “Section 13.11” for internationalization (i18n) and creating the updated upstream C source **debhello-2.0.tar.gz**.

In the real situation, the package should already be internationalized. So this example is educational for you to understand how this internationalization is implemented.

### Tip



The routine maintainer activity for the i18n is simply to add translation po files reported to you via the Bug Tracking System (BTS) to the **po/** directory and to update the language list in the **po/LINGUAS** file.

Let’s get the source and make the Debian package.

#### Download debhello-2.0.tar.gz (i18n)

```
$ wget http://www.example.org/download/debhello-2.0.tar.gz
...
$ tar -xzmf debhello-2.0.tar.gz
$ tree
.
+-- debhello-2.0
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|       | +-- hello.desktop
|       | +-- hello.png
|   +-- lib
|       | +-- Makefile.am
|       | +-- sharedlib.c
|       | +-- sharedlib.h
|   +-- man
|       | +-- Makefile.am
|       | +-- hello.1
|   +-- src
|       +-- Makefile.am
|       +-- hello.c
+-- debhello-2.0.tar.gz

6 directories, 14 files
```

Internationalize this source tree with the **gettextize** command and remove files auto-generated by Autotools.

#### run gettextize (i18n):

```
$ cd /path/to/debhello-2.0
$ gettextize
Creating po/ subdirectory
Creating build-aux/ subdirectory
Copying file ABOUT-NLS
Copying file build-aux/config.rpath
Not copying intl/ directory.
Copying file po/Makefile.in.in
Copying file po/Makevars.template
Copying file po/Rules-quot
Copying file po/boldquot.sed
Copying file po/en@boldquot.header
Copying file po/en@quot.header
Copying file po/insert-header.sin
Copying file po/quot.sed
Copying file po/remove-potcddate.sin
```

```

Creating initial po/POTFILES.in
Creating po/ChangeLog
Creating directory m4
Copying file m4/gettext.m4
Copying file m4/iconv.m4
Copying file m4/lib-ld.m4
Copying file m4/lib-link.m4
Copying file m4/lib-prefix.m4
Copying file m4/nls.m4
Copying file m4/po.m4
Copying file m4/progtest.m4
Creating m4/ChangeLog
Updating Makefile.am (backup is in Makefile.am~)
Updating configure.ac (backup is in configure.ac~)
Creating ChangeLog

```

Please use `AM_GNU_GETTEXT([external])` in order to cause autoconfiguration to look for an external `libintl`.

Please create `po/Makevars` from the template in `po/Makevars.template`. You can then remove `po/Makevars.template`.

Please fill `po/POTFILES.in` as described in the documentation.

Please run `'aclocal'` to regenerate the `aclocal.m4` file. You need `aclocal` from GNU automake 1.9 (or newer) to do this. Then run `'autoconf'` to regenerate the `configure` file.

You will also need `config.guess` and `config.sub`, which you can get from the CV... of the 'config' project at <http://savannah.gnu.org/>. The commands to fetch th... are

```

$ wget 'http://savannah.gnu.org/cgi-bin/viewcvs/*checkout*/config/config/conf...'
$ wget 'http://savannah.gnu.org/cgi-bin/viewcvs/*checkout*/config/config/conf...'

```

You might also want to copy the convenience header file `gettext.h` from the `/usr/share/gettext` directory into your package. It is a wrapper around `<libintl.h>` that implements the `configure --disable-nl...` option.

Press Return to acknowledge the previous 6 paragraphs.

```
$ rm -rf m4 build-aux *~
```

Let's check generated files under the **po/** directory.

**Dateien in po (i18n):**

```

$ ls -l po
total 60
-rw-rw-r-- 1 osamu osamu 494 Jul 24 10:14 ChangeLog
-rw-rw-r-- 1 osamu osamu 17577 Jul 24 10:14 Makefile.in.in
-rw-rw-r-- 1 osamu osamu 3376 Jul 24 10:14 Makevars.template
-rw-rw-r-- 1 osamu osamu 59 Jul 24 10:14 POTFILES.in
-rw-rw-r-- 1 osamu osamu 2203 Jul 24 10:14 Rules-quot
-rw-rw-r-- 1 osamu osamu 217 Jul 24 10:14 boldquot.sed
-rw-rw-r-- 1 osamu osamu 1337 Jul 24 10:14 en@boldquot.header
-rw-rw-r-- 1 osamu osamu 1203 Jul 24 10:14 en@quot.header
-rw-rw-r-- 1 osamu osamu 672 Jul 24 10:14 insert-header.sin
-rw-rw-r-- 1 osamu osamu 153 Jul 24 10:14 quot.sed
-rw-rw-r-- 1 osamu osamu 432 Jul 24 10:14 remove-potcdate.sin

```

Let's update the **configure.ac** by adding `"AM_GNU_GETTEXT([external])"`, etc..

**configure.ac (i18n):**

```

$ vim configure.ac
... hack, hack, hack, ...
$ cat configure.ac

```

```
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([dehello],[2.2],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])

AM_INIT_AUTOMAKE([foreign])

# Set default to --enable-shared --disable-static
LT_INIT([shared disable-static])

# find the libltdl sources in the libltdl sub-directory
LT_CONFIG_LTDL_DIR([libltdl])

# choose one
LTDL_INIT([recursive])
#LTDL_INIT([subproject])
#LTDL_INIT([nonrecursive])

# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
# Checks for programs.
AC_PROG_CC

# desktop file support required
AM_GNU_GETTEXT_VERSION([0.19.3])
AM_GNU_GETTEXT([external])

# only for the recursive case
AC_CONFIG_FILES([Makefile
                 po/Makefile.in
                 lib/Makefile
                 man/Makefile
                 src/Makefile])
AC_OUTPUT
```

Let's create the **po/Makevars** file from the **po/Makevars.template** file.  
**po/Makevars (i18n):**

```
... hack, hack, hack, ...
$ diff -u po/Makevars.template po/Makevars
--- po/Makevars.template      2024-07-24 10:14:46.440850967 +0900
+++ po/Makevars 2024-07-24 10:14:46.520852183 +0900
@@ -18,14 +18,14 @@
# or entity, or to disclaim their copyright. The empty string stands for
# the public domain; in this case the translators are expected to disclaim
# their copyright.
-COPYRIGHT HOLDER = Free Software Foundation, Inc.
+COPYRIGHT HOLDER = Osamu Aoki <osamu@debian.org>

# This tells whether or not to prepend "GNU " prefix to the package
# name that gets inserted into the header of the $(DOMAIN).pot file.
# Possible values are "yes", "no", or empty. If it is empty, try to
# detect it automatically by scanning the files in $(top_srcdir) for
# "GNU packagename" string.
-PACKAGE_GNU =
+PACKAGE_GNU = no

# This is the email address or URL to which the translators shall report
# bugs in the untranslated strings:
$ rm po/Makevars.template
```

Let's update C sources for the i18n version by wrapping strings with `_(...)`.

**src/hello.c (I18n):**

```
... hack, hack, hack, ...
$ cat src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
#include <libintl.h>
#define _(string) gettext (string)
int
main()
{
    printf(_("Hello, I am " PACKAGE_AUTHOR "!\n"));
    sharedlib();
    return 0;
}
```

**lib/sharedlib.c (I18n):**

```
... hack, hack, hack, ...
$ cat lib/sharedlib.c
#include <stdio.h>
#include <libintl.h>
#define _(string) gettext (string)
int
sharedlib()
{
    printf(_("This is a shared library!\n"));
    return 0;
}
```

The new **gettext** (v=0.19) can handle the i18n version of the desktop file directly.

**data/hello.desktop.in (I18n):**

```
$ fgrep -v '[ja]=' data/hello.desktop > data/hello.desktop.in
$ rm data/hello.desktop
$ cat data/hello.desktop.in
[Desktop Entry]
Name=Hello
Comment=Greetings
Type=Application
Keywords=hello
Exec=hello
Terminal=true
Icon=hello.png
Categories=Utility;
```

Let's list the input files to extract translatable strings in **po/POTFILES.in**.

**po/POTFILES.in (I18n):**

```
... hack, hack, hack, ...
$ cat po/POTFILES.in
src/hello.c
lib/sharedlib.c
data/hello.desktop.in
```

Here is the updated root **Makefile.am** with **po** added to the **SUBDIRS** environment variable.

**Makefile.am (I18n):**

```
$ cat Makefile.am
# recursively process `Makefile.am` in SUBDIRS
SUBDIRS = po lib src man

ACLOCAL_AMFLAGS = -I m4

EXTRA_DIST = build-aux/config.rpath m4/ChangeLog
```

Let's make a translation template file, **debhello.pot**.

**po/debhello.pot (I18n):**

```
$ xgettext -f po/POTFILES.in -d debhello -o po/debhello.pot -k_
$ cat po/debhello.pot
# SOME DESCRIPTIVE TITLE.
# Copyright (C) YEAR THE PACKAGE'S COPYRIGHT HOLDER
# This file is distributed under the same license as the PACKAGE package.
# FIRST AUTHOR <EMAIL@ADDRESS>, YEAR.
#
#, fuzzy
msgid ""
msgstr ""
"Project-Id-Version: PACKAGE VERSION\n"
"Report-Msgid-Bugs-To: \n"
"POT-Creation-Date: 2024-07-24 10:14+0900\n"
"PO-Revision-Date: YEAR-MO-DA HO:MI+ZONE\n"
"Last-Translator: FULL NAME <EMAIL@ADDRESS>\n"
"Language-Team: LANGUAGE <LL@li.org>\n"
"Language: \n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=CHARSET\n"
"Content-Transfer-Encoding: 8bit\n"

#: src/hello.c:9
#, c-format
msgid "Hello, I am "
msgstr ""

#: lib/sharedlib.c:7
#, c-format
msgid "This is a shared library!\n"
msgstr ""

#: data/hello.desktop.in:3
msgid "Hello"
msgstr ""

#: data/hello.desktop.in:4
msgid "Greetings"
msgstr ""

#: data/hello.desktop.in:6
msgid "hello"
msgstr ""
```

Lassen Sie uns eine französische Übersetzung hinzufügen.

**po/LINGUAS und po/fr.po (I18n):**

```
$ echo 'fr' > po/LINGUAS
$ cp po/debhello.pot po/fr.po
$ vim po/fr.po
... hack, hack, hack, ...
$ cat po/fr.po
# SOME DESCRIPTIVE TITLE.
# This file is put in the public domain.
# FIRST AUTHOR <EMAIL@ADDRESS>, YEAR.
#
msgid ""
msgstr ""
"Project-Id-Version: debhello 2.2\n"
"Report-Msgid-Bugs-To: foo@example.org\n"
"POT-Creation-Date: 2015-03-01 20:22+0900\n"
"PO-Revision-Date: 2015-02-21 23:18+0900\n"
"Last-Translator: Osamu Aoki <osamu@debian.org>\n"
```

```

"Language-Team: French <LL@li.org>\n"
"Language: ja\n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=UTF-8\n"
"Content-Transfer-Encoding: 8bit\n"

#: src/hello.c:34
#, c-format
msgid "Hello, my name is %s!\n"
msgstr "Bonjour, je m'appelle %s!\n"

#: lib/sharedlib.c:29
#, c-format
msgid "This is a shared library!\n"
msgstr "Ceci est une bibliothèque partagée!\n"

#: data/hello.desktop.in:3
msgid "Hello"
msgstr ""

#: data/hello.desktop.in:4
msgid "Greetings"
msgstr "Salutations"

#: data/hello.desktop.in:6
msgid "hello"
msgstr ""

#: data/hello.desktop.in:9
msgid "hello.png"
msgstr ""

```

The packaging activities are practically the same as the one in “Section 13.11”.  
 You can find more i18n examples by following “Section 13.14”.

## 13.14 Details

Actual details of the examples presented and their variants can be obtained by the following.

### Wie Sie die Details erhalten

```

$ apt-get source debmake-doc
$ cd debmake-doc*
$ cd examples
$ view examples/README.md

```

Follow the exact instruction in **examples/README.md**.

```

$ cd examples
$ make

```

Now, each directory named as **examples/debhello-?.\_build-?** contains the Debian packaging example.

- emulated console command line activity log: the **.log** file
- emulated console command line activity log (short): the **.slog** file
- snapshot source tree image after the **debmake** command: the **debmake** directory
- snapshot source tree image after proper packaging: the **packge** directory
- snapshot source tree image after the **debuild** command: the **test** directory

Notable examples are:

- das POSIX-Shell-Skript mit Makefile mit i18n (v=3.0),



- die C-Quelle mit Makefile.in + configure mit i18n (v=3.2),
- die C-Quelle mit Autotools mit i18n (v=3.3) und
- die C-Quelle mit CMake mit i18n (v=3.4).

## Chapter 14

# debmake(1)-Handbuchseite

### 14.1 BEZEICHNUNG

debmake - Programm zur Erstellung eines Debian-Quellpakets

### 14.2 ÜBERSICHT

**debmake** [-h] [-c | -k] [-n | -a *package-version.orig.tar.gz* | -d | -t ] [-p *package*] [-u *version*] [-r *revision*] [-z *extension*] [-b "*binarypackage[:type], ...*"] [-e *foo@example.org*] [-f "*firstname lastname*"] [-i "*buildtool*" | -j] [-l *license\_file*] [-m] [-o *file*] [-q] [-s] [-v] [-w "*addon, ...*"] [-x [*01234*]] [-y] [-L] [-P] [-T]

### 14.3 BESCHREIBUNG

**debmake** hilft beim Bau eines Debian-Pakets aus den Originalquellen. Normalerweise erfolgt dies wie folgt:

- Der Tarball der Originalautoren wird als Datei *Paket-Version.tar.gz* heruntergeladen.
- Sie wird mit Tar entpackt, um viele Dateien unterhalb des Verzeichnisses *Paket-Version/* zu erstellen.
- Debmake wird mit dem Verzeichnis *Paket-Version/*, möglicherweise ohne Argumente, aufgerufen:
- Dateien im Verzeichnis *Paket-Version/debian/* werden manuell angepasst.
- **dpkg-buildpackage** (normalerweise in seinem Wrapper **debuild** oder **sbuild**) wird mit dem Verzeichnis *Paket-Version/* aufgerufen, um Debian-Pakete zu erstellen.

Stellen Sie sicher, dass die Argumente **-b**, **-f**, **-l** und **-w** durch Maskieren vor dem Einfluss der Shell geschützt sind.

#### 14.3.1 Optionale Argumente:

**-h, --help** zeigt diese Hilfe und beendet das Programm.

**-c, --copyright** überprüft die Quellen auf Urheberrechte und Lizenztexte und beendet das Programm.

- **-c**: einfacher Ausgabestil
- **-cc**: normaler Ausgabestil (ähnlich der Datei **debian/copyright**)
- **-ccc**: Fehlersuchausgabestil

**-k, --kludge** vergleicht die Datei **debian/copyright** mit den Quellen und beendet das Programm.

Die Datei **debian/copyright** muss so organisiert sein, dass die allgemeinen Dateimuster vor den besonderen Ausnahmen aufgeführt sind.

- **-k**: grundlegender Ausgabestil
- **-kk**: ausführlicher Ausgabestil

**-n, --native** make a native Debian source package without **.orig.tar.gz**. This makes a Debian source format “**3.0 (native)**” package.

If you are thinking of packaging a Debian-specific source tree with **debian/** in it into a native Debian package, please think otherwise. You can use the “**debmake -d -i debuild**” or “**debmake -t -i debuild**” commands to make a Debian non-native package using the Debian source format “**3.0 (quilt)**”. The only difference is that the **debian/changelog** file must use the non-native version scheme: *version-revision*. The non-native package is more friendly to downstream distributions.

**-a Paketversion.tar.gz, --archive Paketversion.tar.gz** use the upstream source tarball directly. (**-p, -u, -z**: overridden)

The upstream tarball may be specified as *package\_version.orig.tar.gz* and **tar.gz**. For other cases, it may be **tar.bz2**, or **tar.xz**.

If the specified upstream tarball name contains uppercase letters, the Debian package name is generated by converting them to lowercase letters.

If the specified argument is the URL (**http://**, **https://**, or **ftp://**) to the upstream tarball, the upstream tarball is downloaded from the URL using **wget** or **curl**.

**-d, --dist** run the “**make dist**” command equivalents first to generate the upstream tarball and use it.

The “**debmake -d**” command is designed to run in the *package/* directory hosting the upstream VCS with the build system supporting the “**make dist**” command equivalents. (**automake/autoconf**, ...)

**-t, --tar** run the “**tar**” command to generate the upstream tarball and use it.

The “**debmake -t**” command is designed to run in the *package/* directory hosting the upstream VCS. Unless you provide the upstream version with the **-u** option or with the **debian/changelog** file, a snapshot upstream version is generated in the **0~%y%m%d%H%M** format, e.g., **0~1403012359**, from the UTC date and time. The generated tarball excludes the **debian/** directory found in the upstream VCS. (It also excludes typical VCS directories: **.git/**, **.hg/**, **.svn/**, **.CVS/**.)

**-p Pakete, --package Paket** setzt den Debian-Paketnamen.

**-u Version, --upstreamversion Version** setzt die Paketversion der Originalautoren.

**-r Revision, --revision Revision** setzt die Debian-Paketrevision.

**-z extension, --targz extension** set the tarball type, *extension*=(**tar.gz|tar.bz2|tar.xz**). (alias: **z, b, x**)

**-b "binarypackage[:type],...", --binaryspec "binarypackage[:type],..."** set the binary package specs by a comma separated list of *binarypackage:type* pairs. Here, *binarypackage* is the binary package name, and the optional *type* is chosen from the following *type* values:

- **bin**: C/C++ compiled ELF binary code package (any, foreign) (default, alias: **""**, i.e., **null-string**)
- **data**: Data (fonts, graphics, ...) package (all, foreign) (alias: **da**)
- **dev**: Library development package (any, same) (alias: **de**)
- **doc**: Documentation package (all, foreign) (alias: **do**)
- **lib**: Library package (any, same) (alias: **l**)
- **perl**: Perl script package (all, foreign) (alias: **pl**)
- **python3**: Python (version 3) script package (all, foreign) (alias: **py3, python, py**)
- **ruby**: Ruby script package (all, foreign) (alias: **rb**)
- **nodejs**: Node.js based JavaScript package (all, foreign) (alias: **js**)
- **script**: Shell and other interpreted language script package (all, foreign) (alias: **sh**)

The pair values in the parentheses, such as (any, foreign), are the **Architecture** and **Multi-Arch** stanza values set in the **debian/control** file. In many cases, the **debmake** command makes good guesses for *type* from *binarypackage*. If *type* is not obvious, *type* is set to **bin**.

Here are examples for typical binary package split scenarios where the upstream Debian source package name is **foo**:

- Generating an executable binary package **foo**:

- “**-b’foo:bin**”, or its short form “**-b’-’**”, or no **-b** option
- Generating an executable (python3) binary package **python3-foo**:
  - “**-b’python3-foo:py**”, or its short form “**-b’python3-foo**”
- Generating a data package **foo**:
  - “**-b’foo:data**”, or its short form “**-b’-:data**”
- Generating an executable binary package **foo** and a documentation one **foo-doc**:
  - “**-b’foo:bin,foo-doc:doc**”, or its short form “**-b’-:-doc**”
- Generating an executable binary package **foo**, a library package **libfoo1**, and a library development package **libfoo-dev**:
  - “**-b’foo:bin,libfoo1:lib,libfoo-dev:dev**” or its short form “**-b’-,libfoo1,libfoo-dev**”

If the source tree contents do not match settings for *type*, the **debmake** command warns you.

**-e foo@example.org, --email foo@example.org** set e-mail address.

The default is taken from the value of the environment variable **\$DEBEMAIL**.

**-f "Vorname Nachname", --fullname "Vorname Nachname"** set the fullname.

The default is taken from the value of the environment variable **\$DEBFULLNAME**.

**-i "buildtool", --invoke "buildtool"** invoke “*buildtool*” at the end of execution. *buildtool* may be “**dpkg-buildpackage**”, “**debuild**”, “**sbuild**”, etc.

The default is not to execute any program.

Setting this option automatically sets the **--local** option.

**-j, --judge** run **dpkg-depcheck** to judge build dependencies and identify file paths. Log files are in the parent directory.

- **package.build-dep.log**: Log file for **dpkg-depcheck**.
- **package.install.log**: Log file recording files in the **debian/tmp** directory.

**-l "license\_file,...", --license "license\_file,..."** add formatted license text to the end of the **debian/copyright** file holding license scan results.

The default is to add **COPYING** and **LICENSE**, and *license\_file* needs to list only the additional file names all separated by “,”.

**-m, --monoarch** force packages to be non-multiarch.

**-o Datei, --option Datei** read optional parameters from *file*. (This is not for everyday use.)

The content of *file* is sourced as the Python code at the end of **para.py**. For example, the package description can be specified by the following file.

```
para['desc'] = 'program short description'
para['desc_long'] = '''\
program long description which you wish to include.
.
Empty line is space + .
You keep going on ...
'''
```

**-q, --quitearly** quit early before creating files in the **debian/** directory.

**-s, --spec** use upstream spec (**pyproject.py** for Python, etc.) for the package description.

**-v, --version** show version information.

**-w "addon,...", --with "addon,..."** add extra arguments to the **--with** option of the **dh(1)** command as *addon* in **debian/rules**.

The *addon* values are listed all separated by “;”, e.g., “**-w "python3,autoreconf"**”.

For Autotools based packages, **autoreconf** as *addon* to run “**autoreconf -i -v -f**” for every package building is default behavior of the **dh(1)** command.

For Autotools based packages, if they install Python (version 3) programs, setting **python3** as *addon* to the **debmake** command argument is needed since this is non-obvious. But for **pyproject.toml** based Python packages, setting **python3** as *addon* to the **debmake** command argument is not needed since this is obvious and the **debmake** command automatically set it to the **dh(1)** command.

**-x n, --extra n** generate configuration files as templates. (Please note **debian/changelog**, **debian/control**, **debian/copyright**, and **debian/rules** are bare minimum configuration files to build a Debian binary package.)

The number *n* determines which configuration templates are generated.

- **-x0**: all required configuration template files. (selected option if any of these files already exist)
- **-x1**: all **-x0** files + desirable configuration template files with binary package type supports.
- **-x2**: all **-x1** files + normal configuration template files with maintainer script supports.
- **-x3**: all **-x2** files + optional configuration template files. (default option)
- **-x4**: all **-x3** files + deprecated configuration template files.

Some configuration template files are generated with the extra **.ex** suffix to ease their removal. To activate these, rename their file names to the ones without the **.ex** suffix and edit their contents. Existing configuration files are never overwritten. If you wish to update some of the existing configuration files, please rename them before running the **debmake** command and manually merge the generated configuration files with the old renamed ones.

**-y, --yes** “force yes” for all prompts. (without option: “ask [Y/n]”; doubled option: “force no”)

**-L, --local** generate configuration files for the local package to fool **lintian(1)** checks.

**-P, --pedantic** pedantically check auto-generated files.

**-T, --tutorial** output tutorial comment lines in template files. default when **-x3** or **-x4** is set.

## 14.4 BEISPIELE

For a well behaving source, you can build a good-for-local-use installable single Debian binary package easily with one command. Test install of such a package generated in this way offers a good alternative to the traditional “**make install**” command installing into the **/usr/local** directory since the Debian package can be removed cleanly by the “**dpkg -P '...'**” command. Here are some examples of how to build such test packages. (These should work in most cases. If the **-d** option does not work, try the **-t** option instead.)

For a typical C program source tree packaged with **autoconf/automake**:

- **debmake -d -i debuild**

Für einen typischen Python-(Version 3-)Modulquellbaum:

- **debmake -s -d -b":python3" -i debuild**

Für ein typisches Python-(Version 3-)Modul im Archiv *Paket-Version.tar.gz*:

- **debmake -s -a package-version.tar.gz -b":python3" -i debuild**

Für ein typisches Perl-Modul im Archiv *Paket-Version.tar.gz*:

- **debmake -a package-version.tar.gz -b":perl" -i debuild**

## 14.5 HELFERPAKETE

Die Paketierung könnte die Installation einiger zusätzlicher, spezialisierter Helferpakete benötigen.

- Python (version 3) programs may require the **pybuild-plugin-pyproject** package.
- The Autotools (**autoconf** + **automake**) build system may require **autotools-dev** or **dh-autoreconf** package.
- Ruby-Programme könnten das Paket **gem2deb** benötigen.
- Node.js based JavaScript programs may require the **pkg-js-tools** package.
- Java-Programme könnten das Paket **javahelper** benötigen.
- Gnome-Programme könnten das Paket **gobject-introspection** benötigen.
- usw.

## 14.6 CAVEAT

Although **debmake** is meant to provide template files for the package maintainer to work on, actual packaging activities are often performed without using **debmake** while referencing only existing similar packages and “[Debian Policy Manual](#)”. All template files generated by **debmake** are required to be modified manually.

There are 2 positive points for **debmake**:

- **debmake** helps to write terse packaging tutorial “[Guide for Debian Maintainers](#)” (**debmake-doc** package).
- **debmake** provides short extracted license texts as **debian/copyright** in decent accuracy to help license review.

Please double check copyright with the **licensecheck(1)** command.

There are some limitations for what characters may be used as a part of the Debian package. The most notable limitation is the prohibition of uppercase letters in the package name. Here is a summary as a set of regular expressions:

- Upstream package name (**-p**): `[ - + . a - z 0 - 9 ] { 2 , }`
- Binary package name (**-b**): `[ - + . a - z 0 - 9 ] { 2 , }`
- Upstream version (**-u**): `[ 0 - 9 ] [ - + . : ~ a - z 0 - 9 A - Z ] *`
- Debian revision (**-r**): `[ 0 - 9 ] [ + . ~ a - z 0 - 9 A - Z ] *`

See the exact definition in “[Chapter 5 - Control files and their fields](#)” in the “Debian Policy Manual”.

**debmake** assumes relatively simple packaging cases. So all programs related to the interpreter are assumed to be “**Architecture: all**”. This is not always true.

## 14.7 DEBUG

Bitte berichten Sie Fehler (auf Englisch) mittels des Befehls **reportbug** gegen das Paket **debmake**.

The character set in the environment variable **\$DEBUG** determines the logging output level.

- **i**: `main.py` logging
- **p**: `para.py` logging
- **s**: `checkdep5.py check_format_style()` logging
- **y**: `checkdep5.py split_years_name()` logging
- **b**: `checkdep5.py parse_lines()` 1 logging — `content_state` scan loop: begin-loop
- **m**: `checkdep5.py parse_lines()` 2 logging — `content_state` scan loop: after regex match
- **e**: `checkdep5.py parse_lines()` 3 logging — `content_state` scan loop: end-loop

- **a**: `checkdep5.py parse_lines()` 4 logging — print author/translator section text
- **f**: `checkdep5.py check_all_license()` 1 logging — input filename for the copyright scan
- **l**: `checkdep5.py check_all_license()` 2 logging — print license section text
- **c**: `checkdep5.py check_all_license()` 3 logging — print copyright section text
- **k**: `checkdep5.py check_all_license()` 4 logging — sort key for debian/copyright stanza
- **r**: `sed.py` logging
- **w**: `cat.py` logging
- **n**: `kludge.py` logging (“**debmake -k**”)

Use this feature as:

```
$ DEBUG=ipsybmeaflckrwn debmake ...
```

See **README.developer** in the source for more.

## 14.8 **AUTOR**

Copyright © 2014-2024 Osamu Aoki <[osamu@debian.org](mailto:osamu@debian.org)>

## 14.9 **LIZENZ**

Expat-Lizenz

## 14.10 **SIEHE AUCH**

The **debmake-doc** package provides the “[Guide for Debian Maintainers](#)” in plain text, HTML and PDF formats under the `/usr/share/doc/debmake-doc/` directory.

Siehe auch die Handbuchseiten **dpkg-source**(1), **deb-control**(5), **debhelper**(7), **dh**(1), **dpkg-buildpackage**(1), **debuild**(1), **quilt**(1), **dpkg-depcheck**(1), **sbuild**(1), **gbp-buildpackage**(1), and **gbp-pq**(1) manpages.

# Chapter 15

## debmake options

Here are some additional explanation for **debmake** options.

### 15.1 Shortcut options (-a, -i)

Der Befehl **debmake** bietet 2 Abkürzungsoptionen.

- **-a**: öffnen des Tarballs der Originalautoren
- **-i**: Ausführen der Skripte zum Bau des Binärpakets

Das Beispiel in obigem “Chapter 5” kann so einfach wie folgt sein.

```
$ debmake -a package-1.0.tar.gz -i debuild
```

#### Tip



A URL such as “<https://www.example.org/DL/package-1.0.tar.gz>” may be used for the **-a** option.

#### Tip



A URL such as “<https://arm.koji.fedoraproject.org/packages/ibus/1.5.7-3.fc21/src/ibus-1.5.7-3.fc21.src.rpm>” may be used for the **-a** option, too.

### 15.2 debmake -b

The **debmake** command with the **-b** option provides an intuitive and flexible method to create the initial template **debian/control** file defining the split of the Debian binary packages with following stanzas:

- **Package:**
- **Architecture:** (e.g. **amd64**)
- **Multi-Arch:** (see “Section 9.10”)
- **Depends:**
- **Pre-Depends:**



The **debmake** command also sets an appropriate set of substvars used in each pertinent dependency stanza. Let's quote the pertinent part from the **debmake** manpage here.

**-b "binarypackage[:type],..."**, **--binaryspec "binarypackage[:type],..."** set the binary package specs by a comma separated list of *binarypackage:type* pairs. Here, *binarypackage* is the binary package name, and the optional *type* is chosen from the following *type* values:

- **bin**: C/C++ compiled ELF binary code package (any, foreign) (default, alias: "", i.e., **null-string**)
- **data**: Data (fonts, graphics, ...) package (all, foreign) (alias: **da**)
- **dev**: Library development package (any, same) (alias: **de**)
- **doc**: Documentation package (all, foreign) (alias: **do**)
- **lib**: Library package (any, same) (alias: **l**)
- **perl**: Perl script package (all, foreign) (alias: **pl**)
- **python3**: Python (version 3) script package (all, foreign) (alias: **py3**, **python**, **py**)
- **ruby**: Ruby script package (all, foreign) (alias: **rb**)
- **nodejs**: Node.js based JavaScript package (all, foreign) (alias: **js**)
- **script**: Shell and other interpreted language script package (all, foreign) (alias: **sh**)

The pair values in the parentheses, such as (any, foreign), are the **Architecture** and **Multi-Arch** stanza values set in the **debian/control** file. In many cases, the **debmake** command makes good guesses for *type* from *binarypackage*. If *type* is not obvious, *type* is set to **bin**.

Here are examples for typical binary package split scenarios where the upstream Debian source package name is **foo**:

- Generating an executable binary package **foo**:
  - “**-b'foo:bin'**”, or its short form “**-b'-'**”, or no **-b** option
- Generating an executable (python3) binary package **python3-foo**:
  - “**-b'python3-foo:py'**”, or its short form “**-b'python3-foo'**”
- Generating a data package **foo**:
  - “**-b'foo:data'**”, or its short form “**-b'-:data'**”
- Generating a executable binary package **foo** and a documentation one **foo-doc**:
  - “**-b'foo:bin,foo-doc:doc'**”, or its short form “**-b'-:-doc'**”
- Generating a executable binary package **foo**, a library package **libfoo1**, and a library development package **libfoo-dev**:
  - “**-b'foo:bin,libfoo1:lib,libfoo-dev:dev'**” or its short form “**-b'-,libfoo1,libfoo-dev'**”

If the source tree contents do not match settings for *type*, the **debmake** command warns you.

## 15.3 debmake -cc

The **debmake** command with the **-cc** option can make a summary of the copyright and license for the entire source tree to standard output.

```
$ tar -xvzf package-1.0.tar.gz
$ cd package-1.0
$ debmake -cc | less
```

With the **-c** option, this provides shorter report.

## 15.4 Snapshot upstream tarball (-d, -t)

This test building scheme is good for the git repository organized as described in **gbp-buildpackage**(7) which uses the master, upstream, and pristine-tar branches.

The upstream snapshot from the upstream source tree in the upstream VCS can be made with the **-d** option if the upstream supports the “**make dist**” equivalence.

```
$ cd /path/to/upstream-vcs
$ debmake -d -i debuild
```

Alternatively, the same can be made with the **-t** option if the upstream tarball can be made with the **tar** command.

```
$ cd /path/to/upstream-vcs
$ debmake -p package -t -i debuild
```

Unless you provide the upstream version with the **-u** option or with the **debian/changelog** file, a snapshot upstream version is generated in the **0~%y%m%d%H%M** format, e.g., **0~1403012359**, from the UTC date and time.

If the upstream VCS is hosted in the *package/* directory instead of the *upstream-vcs/* directory, the “**-p package**” can be skipped.

If the upstream source tree in the VCS contains the **debian/\*** files, the **debmake** command with either the **-d** option or the **-t** option combined with the **-i** option automates the making of a non-native Debian package from the VCS snapshot while using these **debian/\*** files.

```
$ cp -r /path/to/package-0~1403012359/debian/. /path/to/upstream-vcs/debian
$ dch
... update debian/changelog
$ git add -A .; git commit -m "vcs with debian/*"
$ debmake -t -p package -i debuild
```

This **non-native** Debian binary package building scheme without the real upstream tarball is considered as the **quasi-native** Debian package. See “Section 10.13”.

## 15.5 debmake -j

This is an experimental feature.

The generation of a functioning multi-binary package always requires more manual work than that of a functioning single binary package. The test build of the source package is the essential part of it.

For example, let’s package the same *package-1.0.tar.gz* (see “Chapter 5”) into a multi binary package.

- Invoke the **debmake** command with the **-j** option for the test building and the report generation.

```
$ debmake -j -a package-1.0.tar.gz
```

- Check the last lines of the *package.build-dep.log* file to judge build dependencies for **Build-Depends**. (You do not need to list packages used by **debhelper**, **perl**, or **fakeroot** explicitly in **Build-Depends**. This technique is useful for the generation of a single binary package, too.)
- Check the contents of the *package.install.log* file to identify the install paths for files to decide how you split them into multiple packages.
- Start packaging with the **debmake** command.

```
$ rm -rf package-1.0
$ tar -xvzf package-1.0.tar.gz
$ cd package-1.0
$ debmake -b"package1:type1, ..."
```

- Update **debian/control** and **debian/binarypackage.install** files using the above information.
- Update other **debian/\*** files as needed.
- Build the Debian package with the **debuild** command or its equivalent.

```
$ debuild
```

- All binary package entries specified in the **debian/binarypackage.install** file are generated as *binarypackage\_version-revision\_arch.deb*.

#### Note



The **-j** option for the **debmake** command invokes **dpkg-depcheck(1)** to run **debian/rules** under **strace(1)** to obtain library dependencies. Unfortunately, this is very slow. If you know the library package dependencies from other sources such as the SPEC file in the source, you may just run the "**debmake ...**" command without the **-j** option and run the "**debian/rules install**" command to check the install paths of the generated files.

## 15.6 **debmake -k**

This is an experimental feature.

When updating a package for the new upstream release, the **debmake** command can verify the content of the existing **debian/copyright** file against the copyright and license situation of the entire updated source tree.

```
$ cd package-vcs
$ gbp import-orig --uscan --pristine-tar
... update source with the new upstream release
$ debmake -k | less
```

The "**debmake -k**" command parses the **debian/copyright** file from the top to the bottom and compares the license of all the non-binary files in the current package with the license described in the last matching file pattern entry of the **debian/copyright** file.

When editing the auto-generated **debian/copyright** file, please make sure to keep the generic file patterns at the top of the list.

#### Tip



For all new upstream releases, run the "**debmake -k**" command to ensure that the **debian/copyright** file is current.

## 15.7 **debmake -P**

The **debmake** command invoked with the **-P** option pedantically checks auto-generated files for copyright+license text even if they are with permissive license.

This option affects not only the content of the **debian/copyright** file generated by normal execution, but also the output by the execution with the **-k**, **-c**, **-cc**, and **-ccc** options.

## 15.8 **debmake -T**

The **debmake** command invoked with the **-T** option additionally prints verbose tutorial comment lines. The lines marked with **###** in the template files are part of the verbose tutorial comment lines.

## 15.9 **debmake** -x

The amount of template files generated by the **debmake** command depends on the **-x**[01234] option.

- See “Section [13.1](#)” for cherry-picking of the template files.

### Note



None of the existing configuration files are modified by the **debmake** command.